

Package ‘structToolbox’

April 12, 2022

Type Package

Title Data processing & analysis tools for Metabolomics and other omics

Version 1.6.1

Description An extensive set of data (pre-)processing and analysis methods and tools for metabolomics and other omics, with a strong emphasis on statistics and machine learning. This toolbox allows the user to build extensive and standardised workflows for data analysis. The methods and tools have been implemented using class-based templates provided by the struct (Statistics in R Using Class-based Templates) package. The toolbox includes pre-processing methods (e.g. signal drift and batch correction, normalisation, missing value imputation and scaling), univariate (e.g. ttest, various forms of ANOVA, Kruskal–Wallis test and more) and multivariate statistical methods (e.g. PCA and PLS, including cross-validation and permutation testing) as well as machine learning methods (e.g. Support Vector Machines). The STATistics Ontology (STATO) has been integrated and implemented to provide standardised definitions for the different methods, inputs and outputs.

License GPL-3

Encoding UTF-8

Collate 'AUC_metric_class.R' 'entity_objects.R' 'DFA_class.R' 'zzz.R'
'anova_class.R' 'HSD_class.R' 'mixed_effect_class.R'
'HSDem_class.R' 'MTBLS79_dataset_class.R' 'PCA_class.R'
'PCA_plotfens.R' 'PLSDA_class.R' 'PLSDA_charts.R'
'PLSR_class.R' 'as_data_frame_doc.R' 'autoscale_class.R'
'balanced_accuracy_class.R' 'blank_filter_class.R'
'bootstrap_class.R' 'calculate_doc.R' 'chart_plot_doc.R'
'classical_lsq_class.R' 'confounders_clsq_class.R'
'constant_sum_norm_class.R' 'corr_coef_class.R'
'd_ratio_filter_class.R' 'dataset_chart_classes.R'
'factor_barchart_class.R' 'feature_plot_array_class.R'
'feature_profile_class.R' 'filter_by_name_class.R'
'filter_na_count.R' 'filter_smeta_class.R'
'fisher_exact_class.R' 'fold_change_class.R'
'fold_change_int_class.R' 'forward_selection_by_rank_class.R'

'ggplot_theme_pub.R' 'glog_class.R' 'grid_search_1d_class.R'
 'hca_class.R' 'kfold_xval_class.R' 'kfold_xval_charts.R'
 'knn_impute_class.R' 'kw_rank_sum_class.R'
 'linear_model_class.R' 'log_transform.R' 'mean_centre_class.R'
 'mean_of_medians.R' 'model_apply_doc.R' 'model_predict_doc.R'
 'model_reverse_doc.R' 'model_train_doc.R'
 'mv_feature_filter_class.R' 'mv_sample_filter_class.R'
 'nroot_transform_class.R' 'pairs_filter_class.R'
 'paretoscale_class.R' 'permutation_test_class.R'
 'permute_sample_order_class.R' 'plsda_vip_summary_chart.R'
 'pqn_norm_method_class.R' 'prop_na_class.R' 'r_squared_class.R'
 'rsd_filter.R' 'run_doc.R' 'sb_corr.R' 'split_data_class.R'
 'stratified_split_class.R' 'structToolbox.R'
 'svm_classifier_class.R' 'tSNE_class.R' 'tic_chart_class.R'
 'ttest_class.R' 'vec_norm_class.R' 'wilcox_test_class.R'

Depends R (>= 4.0), struct (>= 1.5.1)

Imports ggplot2, ggthemes, grid, gridExtra, methods, scales, sp,
 stats, utils

RoxygenNote 7.1.2

Suggests agricolae, BiocFileCache, BiocStyle, car, covr, cowplot,
 e1071, emmeans, ggdendro, knitr, magick, nlme, openxlsx, pls,
 pmp, reshape2, ropls, rmarkdown, Rtsne, testthat, rappdirs

VignetteBuilder knitr

biocViews WorkflowStep, Metabolomics

git_url <https://git.bioconductor.org/packages/structToolbox>

git_branch RELEASE_3_14

git_last_commit 29455a0

git_last_commit_date 2022-02-04

Date/Publication 2022-04-12

Author Gavin Rhys Lloyd [aut, cre],
 Ralf Johannes Maria Weber [aut]

Maintainer Gavin Rhys Lloyd <g.r.lloyd@bham.ac.uk>

R topics documented:

ANOVA	5
as_data_frame	6
AUC	7
autoscale	7
balanced_accuracy	8
blank_filter	9
blank_filter_hist	10
bootstrap	11
calculate,AUC-method	11

chart_plot,dfa_scores_plot,DFA-method	12
classical_lsq	16
compare_dist	17
confounders_clsq	17
confounders_lsq_barchart	19
confounders_lsq_boxplot	20
constant_sum_norm	20
corr_coef	21
DatasetExperiment_boxplot	22
DatasetExperiment_dist	23
DatasetExperiment_factor_boxplot	24
DatasetExperiment_heatmap	25
DFA	26
dfa_scores_plot	26
dratio_filter	28
feature_boxplot	29
feature_profile	30
feature_profile_array	31
filter_by_name	32
filter_na_count	33
filter_smeta	34
fisher_exact	34
fold_change	36
fold_change_int	37
fold_change_plot	39
forward_selection_by_rank	40
fs_line	41
glog_opt_plot	42
glog_transform	43
grid_search_1d	44
gs_line	45
HCA	46
hca_dendrogram	47
HSD	48
HSDEM	49
kfoldxcv_grid	50
kfoldxcv_metric	51
kfold_xval	52
knn_impute	53
kw_p_hist	54
kw_rank_sum	54
linear_model	55
log_transform	56
mean_centre	57
mean_of_medians	58
mixed_effect	58
model_apply,ANOVA,DatasetExperiment-method	60
model_predict,DFA,DatasetExperiment-method	62

model_reverse,autoscale,DatasetExperiment-method	64
model_train,DFA,DatasetExperiment-method	65
MTBLS79_DatasetExperiment	66
mv_boxplot	67
mv_feature_filter	68
mv_feature_filter_hist	69
mv_histogram	70
mv_sample_filter	71
mv_sample_filter_hist	72
nroot_transform	72
ontology_cache	73
pairs_filter	73
pareto_scale	74
PCA	74
pca_biplot	75
pca_correlation_plot	77
pca_dstat_plot	77
pca_loadings_plot	78
pca_scores_plot	79
pca_scree_plot	80
permutation_test	81
permutation_test_plot	81
permute_sample_order	82
PLSDA	83
plsda_predicted_plot	84
plsda_regcoeff_plot	85
plsda_roc_plot	86
plsda_scores_plot	87
plsda_vip_plot	88
plsda_vip_summary_plot	89
PLSR	90
plsr_cook_dist	91
plsr_prediction_plot	92
plsr_qq_plot	92
plsr_residual_hist	93
pqn_norm	93
pqn_norm_hist	95
prop_na	95
rsd_filter	96
rsd_filter_hist	97
run,bootstrap,DatasetExperiment,metric-method	98
r_squared	99
sb_corr	99
split_data	101
stratified_split	101
structToolbox	102
SVM	102
svm_plot_2d	104

tic_chart	105
tSNE	105
tSNE_scatter	107
ttest	108
vec_norm	109
wilcox_p_hist	110
wilcox_test	110

Index	112
--------------	------------

ANOVA	<i>Analysis of Variance</i>
-------	-----------------------------

Description

Analysis of Variance (ANOVA) is a univariate method used to analyse the difference among group means. Multiple test corrected p-values are computed to indicate significance for each feature.

Usage

```
ANOVA(alpha = 0.05, mtc = "fdr", formula, ss_type = "III", ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
formula	(formula) A symbolic description of the model to be fitted.
ss_type	(character) ANOVA sum of squares. Allowed values are limited to the following: <ul style="list-style-type: none"> • "I": Type I sum of squares. • "II": Type II sum of squares. • "III": Type III sum of squares. The default is "III".
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- car

Value

A ANOVA object with the following output slots:

f_statistic (data.frame) The value of the calculated statistic.
 p_value (data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
 significant (data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

References

Fox J, Weisberg S (2019). *An R Companion to Applied Regression*, Third edition. Sage, Thousand Oaks CA. <https://socialsciences.mcmaster.ca/jfox/Books/Companion/>.

Examples

```
D = iris_DatasetExperiment()
M = ANOVA(formula=y~Species)
M = model_apply(M,D)
```

as_data_frame	<i>Convert to data.frame</i>
---------------	------------------------------

Description

Convert the outputs of the input model into a data.frame.

Usage

```
## S4 method for signature 'filter_na_count'
as_data_frame(M)

## S4 method for signature 'ttest'
as_data_frame(M)

## S4 method for signature 'wilcox_test'
as_data_frame(M)
```

Arguments

M a model object

Value

A data.frame of model outputs

Examples

```
D = iris_DatasetExperiment()
M = filter_na_count(threshold=50, factor_name='Species')
M= model_apply(M,D)
df = as_data_frame(M)
```

AUC

*Area under ROC curve***Description**

The area under the ROC curve of a classifier is estimated using the trapezoid method.

Usage

```
AUC(...)
```

Arguments

```
... Additional slots and values passed to struct_class.
```

Value

A AUC object. This object has no output slots.

Examples

```
D = iris_DatasetExperiment()
XCV = kfold_xval(folds=5, factor_name='Species') *
      (mean_centre() + PLSDA(number_components=2, factor_name='Species'))
MET = AUC()
XCV = run(XCV,D,MET)
```

autoscale

*Autoscaling***Description**

Each variable/feature is mean centred and scaled by the standard deviation. The transformed variables have zero-mean and unit-variance.

Usage

```
autoscale(mode = "data", ...)
```

Arguments

mode (character) Mode of action. Allowed values are limited to the following:

- "data": Autoscaling is applied to the data matrix only.
- "sample_meta": Autoscaling is applied to the sample_meta data only.
- "both": Autoscaling is applied to both the data matrix and the meta data.

The default is "data".

... Additional slots and values passed to struct_class.

Value

A autoscale object with the following output slots:

autoscaled	(DatasetExperiment)
mean_data	(numeric)
sd_data	(numeric)
mean_sample_meta	(numeric)
sd_sample_meta	(numeric)

Examples

```
D = iris_DatasetExperiment()
M = autoscale()
M = model_train(M,D)
M = model_predict(M,D)
```

balanced_accuracy *Balanced Accuracy*

Description

Balanced Accuracy is the average proportion of correctly classified samples across all groups.

Usage

```
balanced_accuracy(...)
```

Arguments

... Additional slots and values passed to struct_class.

Value

A balanced_accuracy object. This object has no output slots.

Examples

```
D = iris_DatasetExperiment()
XCV = kfold_xval(folds=5, factor_name='Species') *
      (mean_centre() + PLSDA(number_components=2, factor_name='Species'))
MET = balanced_accuracy()
XCV = run(XCV,D,MET)
```

blank_filter

Blank filter

Description

A blank filter filters features by comparing the median intensity of blank samples to the median intensity of samples. Features where the relative intensity (fold change) is not large when compared to the blank are removed. The number of times a feature is detected across all blank samples may also be considered. If the feature is not detected in a high enough proportion of the blanks then it is not removed.

Usage

```
blank_filter(
  fold_change = 20,
  blank_label = "blank",
  qc_label = "QC",
  factor_name,
  fraction_in_blank = 0,
  ...
)
```

Arguments

fold_change	(numeric) Features with fold change less than this value are removed. The default is 20.
blank_label	(character) The label used to identify blank samples. The default is "blank".
qc_label	(character, NULL) The label used to identify QC samples. If set to NULL then the median of the samples is used. The default is "QC".
factor_name	(character) The name of a sample-meta column to use.
fraction_in_blank	(numeric) Features present in less than this proportion of the blanks are not considered for removal. The default is 0.
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A blank_filter object with the following output slots:

filtered (DatasetExperiment) A DatasetExperiment object containing the filtered data.
flags (data.frame) A flag indicating whether the feature was rejected or not.

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
D = iris_DatasetExperiment()
M = blank_filter(fold_change=2,
                 factor_name='Species',
                 blank_label='setosa',
                 qc_label='versicolor')
M = model_apply(M,D)
```

blank_filter_hist *Histogram of blank filter fold changes*

Description

A histogram of the calculated fold changes for the blank filter (median samples divided by median blanks)

Usage

```
blank_filter_hist(...)
```

Arguments

... Additional slots and values passed to struct_class.

Value

A blank_filter_hist object. This object has no output slots. See [chart_plot](#) in the struct package to plot this chart object.

Examples

```
C = blank_filter_hist()
```

bootstrap	<i>Bootstrap resampling</i>
-----------	-----------------------------

Description

In bootstrap resampling a subset of samples is selected at random with replacement to form a training set. Any sample not selected for training is included in the test set. This process is repeated many times, and performance metrics are computed for each repetition.

Usage

```
bootstrap(number_of_repetitions = 100, collect, ...)
```

Arguments

number_of_repetitions	(numeric, integer) The number of bootstrap repetitions. The default is 100.
collect	(character) The name of a model output to collect over all bootstrap repetitions, in addition to the input metric.
...	Additional slots and values passed to <code>struct_class</code> .

Value

A bootstrap object with the following output slots:

results	(data.frame)
metric	(data.frame)
collected	(logical, list)

Examples

```
I = bootstrap(number_of_repetitions = 10, collect = 'vip')
```

calculate,AUC-method	<i>Calculate metric</i>
----------------------	-------------------------

Description

Calculate metric

Usage

```
## S4 method for signature 'AUC'
calculate(obj, Y, Yhat)
```

```
## S4 method for signature 'balanced_accuracy'  
calculate(obj, Y, Yhat)
```

```
## S4 method for signature 'r_squared'  
calculate(obj, Y, Yhat)
```

Arguments

obj	a metric object
Y	the true values/group labels
Yhat	the predicted values/group labels

Value

a modified metric object

Examples

```
MET = metric()  
calculate(MET)
```

chart_plot,dfa_scores_plot,DFA-method
chart_plot method

Description

Plots a chart object

Usage

```
## S4 method for signature 'dfa_scores_plot,DFA'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'pca_correlation_plot,PCA'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'pca_scores_plot,PCA'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'pca_biplot,PCA'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'pca_loadings_plot,PCA'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'pca_scree_plot,PCA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'pca_dstat_plot,PCA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_scores_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_predicted_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_roc_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_vip_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_regcoeff_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsr_prediction_plot,PLSR'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsr_residual_hist,PLSR'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsr_qq_plot,PLSR'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsr_cook_dist,PLSR'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'blank_filter_hist,blank_filter'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'confounders_lsq_barchart,confounders_clsq'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'confounders_lsq_boxplot,confounders_clsq'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'feature_boxplot,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'mv_histogram,DatasetExperiment'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'mv_boxplot,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'DatasetExperiment_dist,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'DatasetExperiment_boxplot,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'compare_dist,DatasetExperiment'  
chart_plot(obj, dobj, eobj)  
  
## S4 method for signature 'DatasetExperiment_heatmap,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'DatasetExperiment_factor_boxplot,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'feature_profile_array,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'feature_profile,DatasetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'fold_change_plot,fold_change'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'fs_line,forward_selection_by_rank'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'glog_opt_plot,glog_transform'  
chart_plot(obj, dobj, gobj)  
  
## S4 method for signature 'gs_line,grid_search_1d'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'hca_dendrogram,HCA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'kfoldxcv_grid,kfold_xval'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'kfoldxcv_metric,kfold_xval'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'kw_p_hist,kw_rank_sum'  
chart_plot(obj, dobj)
```

```
## S4 method for signature 'mv_feature_filter_hist,mv_feature_filter'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'mv_sample_filter_hist,mv_sample_filter'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'permutation_test_plot,permutation_test'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'plsda_vip_summary_plot,PLSDA'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'pqn_norm_hist,pqn_norm'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'rsd_filter_hist,rsd_filter'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'feature_profile,sb_corr'  
chart_plot(obj, dobj, gobj)  
  
## S4 method for signature 'svm_plot_2d,SVM'  
chart_plot(obj, dobj, gobj)  
  
## S4 method for signature 'tSNE_scatter,tSNE'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'tic_chart,DataSetExperiment'  
chart_plot(obj, dobj)  
  
## S4 method for signature 'wilcox_p_hist,wilcox_test'  
chart_plot(obj, dobj)
```

Arguments

obj	a chart object
dobj	a struct object
eobj	a second DataSetExperiment object to compare with the first
gobj	The DataSetExperiment object before signal correction was applied.

Value

a plot object

Examples

```
C = example_chart()  
chart_plot(C,iris_DatasetExperiment())
```

classical_lsq

*Univariate Classical Least Squares Regression***Description**

In univariate classical least squares regression a line is fitted between each feature/variable and a response variable. The fitted line minimises the sum of squared differences between the true response and the predicted response. The coefficients (offset, gradient) of the fit can be tested for significance.

Usage

```
classical_lsq(alpha = 0.05, mtc = "fdr", factor_names, intercept = TRUE, ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
factor_names	(character) The name of sample meta column(s) to use.
intercept	(logical) Model intercept. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": An intercept term is included in the model. • "FALSE": An intercept term is not included in the model. The default is TRUE.
...	Additional slots and values passed to struct_class.

Value

A classical_lsq object with the following output slots:

coefficients	(data.frame) The regression coefficients for each term in the model.
p_value	(data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
significant	(data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.
r_squared	(data.frame) The value of R Squared for the fitted model.
adj_r_squared	(data.frame) The value of Adjusted R Squared for the fitted model.

Examples

```
D = iris_DatasetExperiment()
M = classical_lsq(factor_names = 'Species')
M = model_apply(M,D)
```

compare_dist	<i>Compare distributions</i>
--------------	------------------------------

Description

Histograms and boxplots computed across samples and features are used to visually compare two datasets e.g. before and after filtering and/or normalisation.

Usage

```
compare_dist(factor_name, ...)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Value

A `compare_dist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D1=MTBLS79_DatasetExperiment(filtered=FALSE)
D2=MTBLS79_DatasetExperiment(filtered=TRUE)
C = compare_dist(factor_name='Class')
chart_plot(C,D1,D2)
```

confounders_clsq	<i>Check for confounding factors</i>
------------------	--------------------------------------

Description

Univariate least squares regression models are used to compare models with and without potential confounding factors included. The change in coefficients (delta) is then computed for each potential confounding factor. Factors with a large delta are said to be having a large impact on the model and are therefore confounding. p-values are computed for models with confounders included to reduce potential false positives. Only suitable for main factors with 2 levels.

Usage

```

confounders_clsq(
  alpha = 0.05,
  mtc = "fdr",
  factor_name,
  confounding_factors,
  threshold = 0.15,
  ...
)

```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
factor_name	(character) The name of the main factor with which other factors may be confounding.
confounding_factors	(character) The name(s) of factor(s) that are potential confounding factors.
threshold	(numeric) Factors with a delta greater than the the threshold are considered to be confounding. The default is 0.15.
...	Additional slots and values passed to struct_class.

Value

A confounders_clsq object with the following output slots:

coefficients	(data.frame)
p_value	(data.frame)
significant	(data.frame)
percent_change	(data.frame)
potential_confounders	(list)

Examples

```

D = MTBLS79_DatasetExperiment()
M = filter_by_name(mode='include',dimension='variable',
  names=colnames(D$data)[1:10]) + # first 10 features
  filter_smeta(mode='exclude',levels='QC',
  factor_name='Class') + # reduce to two group comparison
  confounders_clsq(factor_name = 'Class',

```

```

confounding_factors=c('run_order', 'Batch'))
M = model_apply(M,D)

```

confounders_lsq_barchart

Confounding factor relative change barchart

Description

A barchart of the relative change (delta) in regression coefficient when potential confounding factors are included, and excluded, from the model. Factors with a large delta are considered to be confounding factors.

Usage

```
confounders_lsq_barchart(feature_to_plot, threshold = 10, ...)
```

Arguments

feature_to_plot	(numeric, character, integer) The column name of the feature to be plotted.
threshold	(numeric) A horizontal line is plotted to indicate the threshold. The default is 10.
...	Additional slots and values passed to struct_class.

Value

A `confounders_lsq_barchart` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```

D = MTBLS79_DatasetExperiment()
M = filter_by_name(mode='include', dimension='variable',
  names=colnames(D$data)[1:10]) + # first 10 features
  filter_smeta(mode='exclude', levels='QC',
  factor_name='Class') + # reduce to two group comparison
  confounders_clsq(factor_name = 'Class',
  confounding_factors=c('run_order', 'Batch'))
M = model_apply(M,D)
C = C=confounders_lsq_barchart(feature_to_plot=1, threshold=15)
chart_plot(C,M[3])

```

confounders_lsq_boxplot

Confounding factor relative change boxplot

Description

A boxplot of the relative change (delta) in regression coefficient when potential confounding factors are included, and excluded, from the model. Factors with a large delta are considered to be confounding factors.

Usage

```
confounders_lsq_boxplot(threshold = 10, ...)
```

Arguments

`threshold` (numeric) A horizontal line is plotted to indicate the threshold. The default is 10.

`...` Additional slots and values passed to `struct_class`.

Value

A `confounders_lsq_boxplot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment()
M = filter_by_name(mode='include',dimension='variable',
  names=colnames(D$data)[1:10]) + # first 10 features
  filter_smeta(mode='exclude',levels='QC',
  factor_name='Class') + # reduce to two group comparison
  confounders_clsq(factor_name = 'Class',
  confounding_factors=c('run_order','Batch'))
M = model_apply(M,D)
C = C=confounders_lsq_boxplot(threshold=15)
chart_plot(C,M[3])
```

constant_sum_norm

Normalisation to constant sum

Description

Each sample is normalised such that the total signal is equal to one (or a scaling factor if specified).

Usage

```
constant_sum_norm(scaling_factor = 1, ...)
```

Arguments

`scaling_factor` (numeric) The scaling factor applied after normalisation. The default is 1.
 ... Additional slots and values passed to `struct_class`.

Value

A `constant_sum_norm` object with the following output slots:

`normalised` (`DatasetExperiment`) A `DatasetExperiment` object containing the normalised data.
`coeff` (`data.frame`) The sum of each row, used to normalise the samples.

Examples

```
M = constant_sum_norm()
```

corr_coef

Correlation coefficient

Description

The correlation between features and a set of continuous factor are calculated. Multiple-test corrected p-values are used to indicate whether the computed coefficients may have occurred by chance.

Usage

```
corr_coef(alpha = 0.05, mtc = "fdr", factor_names, method = "spearman", ...)
```

Arguments

`alpha` (numeric) The p-value cutoff for determining significance. The default is 0.05.
`mtc` (character) Multiple test correction method. Allowed values are limited to the following:

- "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons.
- "fdr": Benjamini and Hochberg False Discovery Rate correction.
- "none": No correction.

The default is "fdr".

`factor_names` (character) The name of sample meta column(s) to use.

method (character) Type of correlation. Allowed values are limited to the following:

- "kendall": Kendall's tau is computed.
- "pearson": Pearson product moment correlation is computed.
- "spearman": Spearman's rho statistic is computed.

The default is "spearman".

... Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- stats

Value

A corr_coef object with the following output slots:

coeff (data.frame) The value of the calculate statistics which is converted to a p-value when compared to a t-distribution.

p_value (data.frame) The probability of observing the calculated statistic if the null hypothesis is true.

significant (data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

References

R Core Team (2021). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. <https://www.R-project.org/>.

Examples

```
D = MTBLS79_DatasetExperiment(filtered=TRUE)

# subset for this example
D = D[,1:10]

# convert to numeric for this example
D$sample_meta$sample_order=as.numeric(D$sample_meta$run_order)
D$sample_meta$sample_rep=as.numeric(D$sample_meta$Sample_Rep)

M = corr_coef(factor_names=c('sample_order', 'sample_rep'))
M = model_apply(M,D)
```

DatasetExperiment_boxplot

Feature distribution histogram

Description

A boxplot to visualise the distribution of values within a subset of features.

Usage

```
DatasetExperiment_boxplot(
  factor_name,
  by_sample = TRUE,
  per_class = TRUE,
  number = 50,
  ...
)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
by_sample	(logical) Plot by sample. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": The data is plotted across features for a subset of samples. • "FALSE": The data is plotted across samples for a subset of features. The default is TRUE.
per_class	(logical) Plot per class. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": The data is plotted for each class. • "FALSE": The data is plotted for all samples. The default is TRUE.
number	(numeric, integer) The number of features/samples plotted. The default is 50.
...	Additional slots and values passed to struct_class.

Value

A DatasetExperiment_boxplot object. This object has no output slots. See [chart_plot](#) in the struct package to plot this chart object.

struct object

Examples

```
D = MTBLS79_DatasetExperiment()
C = DatasetExperiment_boxplot(factor_name='Class', number=10, per_class=FALSE)
chart_plot(C,D)
```

DatasetExperiment_dist

Feature distribution histogram

Description

A histogram to visualise the distribution of values within features.

Usage

```
DatasetExperiment_dist(factor_name, per_class = TRUE, ...)
```

Arguments

`factor_name` (character) The name of a sample-meta column to use.

`per_class` (logical) Plot per class. Allowed values are limited to the following:

- "TRUE": The distributions are plotted for each class.
- "FALSE": The distribution is plotted for all samples.

The default is TRUE.

... Additional slots and values passed to `struct_class`.

Value

A `DatasetExperiment_dist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment()
C = DatasetExperiment_dist(factor_name='Class')
chart_plot(C,D)
```

DatasetExperiment_factor_boxplot
Factor boxplot

Description

Boxplot for a feature to visualise the distribution of values within each group

Usage

```
DatasetExperiment_factor_boxplot(feature_to_plot, factor_names, ...)
```

Arguments

`feature_to_plot` (character, numeric, integer) The name of the plotted feature.

`factor_names` (character) The name of sample meta column(s) to use.

... Additional slots and values passed to `struct_class`.

Value

A `DatasetExperiment_factor_boxplot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = iris_DatasetExperiment()
C = DatasetExperiment_factor_boxplot(factor_names='Species', feature_to_plot='Petal.Width')
chart_plot(C,D)
```

DatasetExperiment_heatmap
DatasetExperiment heatmap

Description

A heatmap to visualise the measured values in a data matrix.

Usage

```
DatasetExperiment_heatmap(na_colour = "#FF00E4", ...)
```

Arguments

`na_colour` (character) The hex colour code used to plot missing values. The default is "#FF00E4".

`...` Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `reshape2`

Value

A `DatasetExperiment_heatmap` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Wickham H (2007). "Reshaping Data with the reshape Package." *Journal of Statistical Software*, 21(12), 1–20. <http://www.jstatsoft.org/v21/i12/>.

Examples

```
D = iris_DatasetExperiment()
C = DatasetExperiment_heatmap()
chart_plot(C,D)
```

DFA

*Discriminant Factor Analysis***Description**

Discriminant Factor Analysis (DFA) is a supervised classification method. Using a linear combination of the input variables, DFA finds new orthogonal axes (canonical values) to minimize the variance within each given class and maximize variance between classes.

Usage

```
DFA(factor_name, number_components = 2, ...)
```

Arguments

`factor_name` (character) The name of a sample-meta column to use.
`number_components` (numeric, integer) The number of DFA components calculated. The default is 2.
`...` Additional slots and values passed to `struct_class`.

Value

A DFA object with the following output slots:

<code>scores</code>	(DatasetExperiment)
<code>loadings</code>	(data.frame)
<code>eigenvalues</code>	(data.frame)
<code>that</code>	(DatasetExperiment)

References

Manly B (1986). *Multivariate Statistical Methods: A Primer*. Chapman and Hall, Boca Raton.

Examples

```
D = iris_DatasetExperiment()
M = DFA(factor_name='Species')
M = model_apply(M,D)
```

dfa_scores_plot

*DFA scores plot***Description**

A scatter plot of the selected DFA components.

Usage

```
dfa_scores_plot(
  components = c(1, 2),
  points_to_label = "none",
  factor_name,
  ellipse = "all",
  label_filter = character(0),
  label_factor = "rownames",
  label_size = 3.88,
  ...
)
```

Arguments

<code>components</code>	(numeric) The components selected for plotting. The default is <code>c(1, 2)</code> .
<code>points_to_label</code>	(character) Points to label. Allowed values are limited to the following: <ul style="list-style-type: none"> "none": No samples labels are displayed. "all": The labels for all samples are displayed. "outliers": Labels for for potential outlier samples are displayed. The default is "none".
<code>factor_name</code>	(character) The name of a sample-meta column to use.
<code>ellipse</code>	(character) Plot ellipses. Allowed values are limited to the following: <ul style="list-style-type: none"> "all": Hotelling T2 95% ellipses are plotted for all groups and all samples. "group": Hotelling T2 95% ellipses are plotted for all groups. "none": Ellipses are not included on the plot. "sample": A Hotelling T2 95% ellipse is plotted for all samples (ignoring group). The default is "all".
<code>label_filter</code>	(character) Labels are only plotted for the named groups. If zero-length then all groups are included. The default is <code>character(0)</code> .
<code>label_factor</code>	(character) The column name of <code>sample_meta</code> to use for labelling samples on the plot. "rownames" will use the row names from <code>sample_meta</code> . The default is "rownames".
<code>label_size</code>	(numeric) The text size of labels. Note this is not in Font Units. The default is 3.88.
<code>...</code>	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- scales
- ggplot2

Value

A `dfa_scores_plot` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Wickham H, Seidel D (2020). *scales: Scale Functions for Visualization*. R package version 1.1.1, <https://CRAN.R-project.org/package=scales>.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre() + DFA(factor_name='Species')
M = model_apply(M,D)
C = dfa_scores_plot(factor_name = 'Species')
chart_plot(C,M[2])
```

dratio_filter

Dispersion ratio filter

Description

The dispersion ratio (d-ratio) compares the standard deviation (or non-parametric equivalent) of the Quality Control (QC) samples relative to the standard deviation (or non-parametric equivalent) of the samples for each feature. If the d-ratio is greater than a predefined threshold then the observed sample variance could be due to technical variance and the feature is removed.

Usage

```
dratio_filter(threshold = 20, qc_label = "QC", factor_name, ...)
```

Arguments

threshold	(numeric) The threshold below which features are removed. The default is 20.
qc_label	(character) The label used to identify QC samples. The default is "QC".
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to <code>struct_class</code> .

Value

A `dratio_filter` object with the following output slots:

filtered	(DatasetExperiment) A DatasetExperiment object containing the filtered data.
flags	(data.frame) Flag indicating whether the feature was rejected by the filter or not.
d_ratio	(data.frame)

References

Broadhurst D, Goodacre R, Reinke SN, Kuligowski J, Wilson ID, Lewis MR, Dunn WB (2018). “Guidelines and considerations for the use of system suitability and quality control samples in mass spectrometry assays applied in untargeted clinical metabolomic studies.” *Metabolomics*, **14**(6).

Examples

```
D = MTBLS79_DatasetExperiment()
M = dratio_filter(threshold=20, qc_label='QC', factor_name='Class')
M = model_apply(M,D)
```

feature_boxplot	<i>Feature boxplot</i>
-----------------	------------------------

Description

A boxplot to visualise the distribution of values within a feature.

Usage

```
feature_boxplot(
  label_outliers = TRUE,
  feature_to_plot,
  factor_name,
  show_counts = TRUE,
  style = "boxplot",
  jitter = FALSE,
  fill = FALSE,
  ...
)
```

Arguments

label_outliers (logical) Label outliers. Allowed values are limited to the following:

- "TRUE": The index for outlier samples is included on the plot.
- "FALSE": No labels are displayed.

The default is TRUE.

feature_to_plot

(character, numeric, integer) The column name of the plotted feature.

factor_name

(character) The name of a sample-meta column to use.

show_counts

(logical) Show counts. Allowed values are limited to the following:

- "TRUE": The number of samples for each box is displayed.
- "FALSE": The number of samples for each box is not displayed.

The default is TRUE.

style

(character) Plot style. Allowed values are limited to the following:

	<ul style="list-style-type: none"> • "boxplot": Boxplot style. • "violin": Violon plot style.
	The default is "boxplot".
jitter	(logical) Include points plotted with added jitter. The default is FALSE.
fill	(logical) Block fill the boxes or violins with the group colour. The default is FALSE.
...	Additional slots and values passed to struct_class.

Value

A `feature_boxplot` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment
C = feature_boxplot(factor_name='Species', feature_to_plot='Petal.Width')
chart_plot(C,D)
```

feature_profile	<i>Feature profile</i>
-----------------	------------------------

Description

A plot visualising the change in intensity of a feature with a continuous variable such as time, dose, or run order.

Usage

```
feature_profile(
  run_order,
  qc_label,
  qc_column,
  colour_by,
  feature_to_plot,
  plot_sd = FALSE,
  ...
)
```

Arguments

run_order	(character) The sample-meta column name containing run order.
qc_label	(character) The label used to identify QC samples.
qc_column	(character) The sample-meta column name containing the labels used to identify QC samples.
colour_by	(character) The sample-meta column name to used to colour the plot.

feature_to_plot	(numeric, character, integer) The name or column id of the plotted feature.
plot_sd	(logical) Plot standard deviation. Allowed values are limited to the following: <ul style="list-style-type: none">• "TRUE": Standard deviation of samples and QCs are included on the plot.• "FALSE": Standard deviation is not plotted. The default is FALSE.
...	Additional slots and values passed to struct_class.

Value

A `feature_profile` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment()
C = feature_profile(run_order='run_order',
  qc_label='QC',
  qc_column='Class',
  colour_by='Class',
  feature_to_plot=1)
chart_plot(C,D)
```

feature_profile_array *Feature profile*

Description

A plot visualising the change in intensity of a feature with a continuous variable such as time, dose, or run order.

Usage

```
feature_profile_array(
  run_order,
  qc_label,
  qc_column,
  colour_by,
  feature_to_plot,
  nrow = 5,
  log = TRUE,
  ...
)
```

Arguments

run_order	(character) The sample-meta column name containing run order.
qc_label	(character) The label used to identify QC samples.
qc_column	(character) The sample-meta column name containing the labels used to identify QC samples.
colour_by	(character) The sample-meta column name to used to colour the plot.
feature_to_plot	(numeric, character, integer) The name or column id of the plotted feature.
nrow	(numeric, integer) The number of rows in the plot. The default is 5.
log	(logical) Log transform. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": The data is log tranformed before plotting. • "FALSE": The data is not transformed before plotting. The default is TRUE.
...	Additional slots and values passed to struct_class.

Value

A `feature_profile_array` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment()
C = feature_profile_array(
  run_order='run_order',
  qc_label='QC',
  qc_column='Class',
  colour_by='Class',
  feature_to_plot=1:3,
  nrow=1,
  log=TRUE)
chart_plot(C,D)
```

filter_by_name	<i>Filter by name</i>
----------------	-----------------------

Description

A filter to subsample a `DatasetExperiment` object based on sample or feature name, id, row/column index or using a vector of TRUE/FALSE.

Usage

```
filter_by_name(mode = "exclude", dimension = "sample", names, ...)
```


Arguments

mode	"include" or ["exclude"] to subsample a DatasetExperiment by including or excluding samples/features based on the provided labels
dimension	["sample"] or "variable" to filter by sample or feature labels
names	the sample/feature identifiers to filter by. Can provide column names, column indices or logical.
...	additional slots and values passed to struct_class

Value

struct object

Examples

```
D = MTBLS79_DatasetExperiment()
M = filter_by_name(mode='exclude', dimension='variable', names=c(1,2,3))
M = model_apply(M,D)
```

filter_na_count	<i>Minimum number of measured values filter</i>
-----------------	---

Description

The number of measured values is counted for each feature, and any feature with less than a pre-defined minimum number of values in each group is removed. If there are several factors, then the threshold is applied so that the minimum number of samples is present for all combinations (interactions) of groups.

Usage

```
filter_na_count(threshold, factor_name, ...)
```

Arguments

threshold	(numeric) The minimum number of samples in each group/interaction.
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Value

A filter_na_count object with the following output slots:

filtered	(DatasetExperiment) A DatasetExperiment object containing the filtered data.
count	(data.frame) The number of measured values in each group/interaction.
na_count	(data.frame) The number of missing values in each group/interaction.
flags	(data.frame) Flags to indicate which features were removed.

Examples

```
D = MTBLS79_DatasetExperiment()
M = filter_na_count(threshold=3, factor_name='Class')
M = model_apply(M,D)
```

filter_smeta	<i>Filter by sample meta data</i>
--------------	-----------------------------------

Description

The data is filtered by so that the named levels of a factor are included/excluded from the dataset.

Usage

```
filter_smeta(mode = "include", levels, factor_name, ...)
```

Arguments

mode	(character) Mode of action. Allowed values are limited to the following: <ul style="list-style-type: none"> • "include": Samples in the specified levels are retained. • "exclude": Samples in the specified levels are excluded. The default is "include".
levels	(character) The level name(s) for filtering.
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Value

A filter_smeta object with the following output slots:

filtered (DatasetExperiment)

Examples

```
D = MTBLS79_DatasetExperiment()
M = filter_smeta(mode='exclude', levels='QC', factor_name='QC')
M = model_apply(M,D)
```

fisher_exact	<i>Fisher Exact Test</i>
--------------	--------------------------

Description

A fisher exact test is used to analyse contingency tables by comparing the number of correctly/incorrectly predicted group labels. A multiple test corrected p-value indicates whether the number of measured values is significantly different between groups.

Usage

```
fisher_exact(alpha = 0.05, mtc = "fdr", factor_name, factor_pred, ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
factor_name	(character) The name of a sample-meta column to use.
factor_pred	(data.frame) A data.frame, where each column is a factor of predicted group labels to compare with the true groups labels.
...	Additional slots and values passed to struct_class.

Value

A fisher_exact object with the following output slots:

p_value	(data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
significant	(data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

Examples

```
# load some data
D=MTBLS79_DatasetExperiment()

# prepare predictions based on NA
pred=as.data.frame(is.na(D$data))
pred=lapply(pred, factor, levels=c(TRUE,FALSE))
pred=as.data.frame(pred)

# apply method
M = fisher_exact(alpha=0.05,mtc='fdr',factor_name='Class',factor_pred=pred)
M=model_apply(M,D)
```

fold_change	<i>Fold change</i>
-------------	--------------------

Description

Fold change is the relative change in mean (or non-parametric equivalent) intensities of a feature between all pairs of levels in a factor.

Usage

```
fold_change(
  factor_name,
  paired = FALSE,
  sample_name = character(0),
  threshold = 2,
  control_group = character(0),
  method = "geometric",
  conf_level = 0.95,
  ...
)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
paired	(logical) Paired fold change. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": Fold change is calculated taking into account paired sampling. • "FALSE": Fold change is calculated assuming there is no paired sampling. The default is FALSE.
sample_name	(character) The name of a sample_meta column containing sample identifiers for paired sampling. The default is character(0).
threshold	(numeric) The fold change threshold for labelling features as significant. The default is 2.
control_group	(character) The level name of the group used in the denominator (where possible) when computing fold change. The default is character(0).
method	(character) Fold change method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "geometric": A log transform is applied before using group means to calculate fold change. In the non-transformed space this is equivalent to using geometric group means. Confidence intervals for independent and paired sampling are estimated using standard error of the mean in log transformed space before being transformed back to the original space. • "median": The group medians and the method described by Price and Bonett[1] is used to estimate confidence intervals. For paired data standard error of the median is used to estimate confidence intervals from the median fold change of all pairs.

- "mean": The group means and the method described by Price and Bonnet[1] is used to estimate confidence intervals. For paired data standard error of the mean is used to estimate confidence intervals from the mean fold change of all pairs.

The default is "geometric".

conf_level (numeric) The confidence level of the interval. The default is 0.95.
 ... Additional slots and values passed to struct_class.

Value

A fold_change object with the following output slots:

fold_change (data.frame) The fold change between groups.
 lower_ci (data.frame) Lower confidence interval for fold change.
 upper_ci (data.frame) Upper confidence interval for fold change.
 significant (data.frame) A logical indicator of whether the calculated fold change including the estimated confidence limit

References

Price Jr RM, Bonett DG (2020). "Confidence Intervals for Ratios of Means and Medians." *Journal of Educational and Behavioral Statistics*, **45**(6), 750-770.

Examples

```
D = MTBLS79_DatasetExperiment()
M = fold_change(factor_name='Class')
M = model_apply(M,D)
```

fold_change_int	<i>Fold change for interactions between factors</i>
-----------------	---

Description

For more than one factor the fold change calculation is extended to include all combinations of levels (interactions) of all factors. Paired fold changes are not possible for this computation.

Usage

```
fold_change_int(
  factor_name,
  threshold = 2,
  control_group = character(0),
  method = "geometric",
  conf_level = 0.95,
  ...
)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
threshold	(numeric) The fold change threshold for labelling features as significant. The default is 2.
control_group	(character) The level names of the groups used in the denominator (where possible) when computing fold change. One level for each factor, assumed to be in the same order as factor_name. The default is character(0).
method	(character) Fold change method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "geometric": A log transform is applied before using group means to calculate fold change. In the non-transformed space this is equivalent to using geometric group means. Confidence intervals for independent and paired sampling are estimated using standard error of the mean in log transformed space before being transformed back to the original space. • "median": The group medians and the method described by Price and Bonett[1] is used to estimate confidence intervals. For paired data standard error of the median is used to estimate confidence intervals from the median fold change of all pairs. • "mean": The group means and the method described by Price and Bonnet[1] is used to estimate confidence intervals. For paired data standard error of the mean is used to estimate confidence intervals from the mean fold change of all pairs. <p>The default is "geometric".</p>
conf_level	(numeric) The confidence level of the interval. The default is 0.95.
...	Additional slots and values passed to struct_class.

Value

A fold_change_int object with the following output slots:

fold_change	(data.frame) The fold change between groups.
lower_ci	(data.frame) Lower confidence interval for fold change.
upper_ci	(data.frame) Upper confidence interval for fold change.
significant	(data.frame) A logical indicator of whether the calculated fold change including the estimated confidence limit

References

Lloyd GR, Weber RJM (????). *struct: Statistics in R Using Class-based Templates*. R package version 1.5.2.

Examples

```
D = MTBLS79_DatasetExperiment()
D=D[,1:10,drop=FALSE]
M = filter_smeta(mode='exclude',levels='QC',factor_name='Class') +
  fold_change_int(factor_name=c('Class','Batch'))
```

```
M = model_apply(M,D)
```

fold_change_plot	<i>Fold change plot</i>
------------------	-------------------------

Description

A plot of fold changes calculated for a chosen subset of features. A predefined fold change threshold is indicated by shaded regions.

Usage

```
fold_change_plot(number_features = 20, orientation = "portrait", ...)
```

Arguments

`number_features` (numeric) The number randomly selected features to plot, or a list of column numbers. The default is 20.

`orientation` (character) Plot orientation. Allowed values are limited to the following:

- "landscape": Features are plotted on the y-axis.
- "portrait": Features are plotted on the x-axis.

The default is "portrait".

... Additional slots and values passed to `struct_class`.

Value

A `fold_change_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = fold_change_plot()
```

 forward_selection_by_rank

Forward selection by rank

Description

A model is trained and performance metric computed by including increasing numbers of features in the model. The features to be included in each step are defined by their rank, which is computed from another variable e.g. VIP score. An "optimal" subset of features is suggested by minimising the input performance metric.

Usage

```
forward_selection_by_rank(
  min_no_vars = 1,
  max_no_vars = 100,
  step_size = 1,
  factor_name,
  variable_rank,
  ...
)
```

Arguments

min_no_vars	(numeric) The minimum number of variables to include in the model. The default is 1.
max_no_vars	(numeric) The maximum number of variables to include in the model. The default is 100.
step_size	(numeric) The incremental change in number of features in the model. The default is 1.
factor_name	(character) The name of a sample-meta column to use.
variable_rank	(numeric, integer) The values used to rank the features.
...	Additional slots and values passed to struct_class.

Value

A forward_selection_by_rank object with the following output slots:

metric	(data.frame) The value of the computed metric for each model. For nested models the metric is averaged.
results	(data.frame) The predicted outputs from collated from all models computed during forward selection.
chosen_vars	(numeric, integer) The column number of the variables chosen for the best performing model.
smoothed	(numeric) The value of the performance metric for each evaluated model after smoothing.
searchlist	(numeric) The maximum rank of features included in each model.

Examples

```
# some data
D = MTBLS79_DatasetExperiment(filtered=TRUE)

# normalise, impute and scale then remove QCs
P = pqn_norm(qc_label='QC',factor_name='Class') +
  knn_impute(neighbours=5) +
  glog_transform(qc_label='QC',factor_name='Class') +
  filter_smeta(mode='exclude',levels='QC',factor_name='Class')
P = model_apply(P,D)
D = predicted(P)

# forward selection using a PLSDA model
M = forward_selection_by_rank(factor_name='Class',
                             min_no_vars=2,
                             max_no_vars=11,
                             variable_rank=1:2063) *
  (mean_centre() + PLSDA(number_components=1,
                        factor_name='Class'))
M = run(M,D,balanced_accuracy())
```

fs_line

Forward selection line plot

Description

A line plot for forward selection. The computed model performance metric is plotted against the number of features included in the model.

Usage

```
fs_line(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `fs_line` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
# some data
D = MTBLS79_DatasetExperiment(filtered=TRUE)

# normalise, impute and scale then remove QCs
```

```

P = pqn_norm(qc_label='QC', factor_name='Class') +
  knn_impute(neighbours=5) +
  glog_transform(qc_label='QC', factor_name='Class') +
  filter_smeta(mode='exclude', levels='QC', factor_name='Class')
P = model_apply(P,D)
D = predicted(P)

# forward selection using a PLSDA model
M = forward_selection_by_rank(factor_name='Class',
                             min_no_vars=2,
                             max_no_vars=11,
                             variable_rank=1:2063) *
  (mean_centre() + PLSDA(number_components=1,
                         factor_name='Class'))
M = run(M,D,balanced_accuracy())

# chart
C = fs_line()
chart_plot(C,M)

```

glog_opt_plot

Glog optimisation

Description

A plot of the sum of squares error (SSE) vs different values of lambda for the glog transform. The indicated optimum value for lambda minimises the SSE.

Usage

```
glog_opt_plot(plot_grid = 100, ...)
```

Arguments

plot_grid (numeric) The default is 100.
 ... Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A `glog_opt_plot` object. This object has no output slots. See [chart_plot](#) in the struct package to plot this chart object.

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
D = iris_DatasetExperiment()
M = glog_transform(qc_label='versicolor', factor_name='Species')
M = model_apply(M,D)
C = glog_opt_plot()
chart_plot(C,M,D)
```

glog_transform	<i>Generalised logarithmic transform</i>
----------------	--

Description

The generalised logarithm (glog) transformation applies a log transformation while applying an offset to account for technical variation.

Usage

```
glog_transform(qc_label = "QC", factor_name, lambda = NULL, ...)
```

Arguments

qc_label	(character) The label used to identify QC samples. The default is "QC".
factor_name	(character) The name of a sample-meta column to use.
lambda	(numeric, NULL) The value of lambda to use. If NULL then the pmp package will be used to determine an "optimal" value for lambda. The default is NULL.
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A glog_transform object with the following output slots:

transformed	(DatasetExperiment) A DatasetExperiment object containing the glog transformed data.
error_flag	(logical) A logical indicating whether the glog optimisation for lambda was successful. If not then PMP returns

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Durbin B, Hardin J, Hawkins D, Rocke D (2002). "A variance-stabilizing transformation for gene-expression microarray data." *Bioinformatics*, **18**(Suppl 1), S105-S110.

Parsons HM, Ludwig C, Gunther UL, Viant MR (2007). "Improved classification accuracy in 1- and 2-dimensional NMR metabolomics data using the variance stabilising generalised logarithm transformation." *Bioinformatics*, **8**(1), 234.

Examples

```
D = iris_DatasetExperiment()
M = glog_transform(qc_label='versicolor', factor_name='Species')
M = model_apply(M,D)
```

grid_search_1d	<i>One dimensional grid search</i>
----------------	------------------------------------

Description

A one dimensional grid search calculates a performance metric for a model at evenly spaced values for a model input parameter. The "optimum" value for the parameter is suggested as the one which maximises performance, or minimises error (whichever is appropriate for the chosen metric)

Usage

```
grid_search_1d(
  param_to_optimise,
  search_values,
  model_index,
  factor_name,
  max_min = "min",
  ...
)
```

Arguments

param_to_optimise	(character) The name of the model input parameter that is the focus of the search.
search_values	(ANY) The values of the input parameter being optimised.
model_index	(numeric, integer) The index of the model in the sequence that uses the parameter being optimised.
factor_name	(character) The name of a sample-meta column to use.
max_min	(character) Maximise or minimise. Allowed values are limited to the following:

- "max": The optimum parameter value is suggested based on maximising the performance metric.
- "min": The optimum parameter value is suggested based on minimising the performance metric.

The default is "min".

... Additional slots and values passed to struct_class.

Value

A grid_search_1d object with the following output slots:

results	(data.frame)
metric	(data.frame)
optimum_value	(numeric)

Examples

```
D = MTBLS79_DatasetExperiment()
# some preprocessing
M = pqn_norm(qc_label='QC', factor_name='Class') +
  knn_impute() +
  glog_transform(qc_label='QC', factor_name='Class') +
  filter_smeta(factor_name='Class', levels='QC', mode='exclude')
M=model_apply(M,D)
D=predicted(M)

# reduce number of features for this example
D=D[,1:10]

# optimise number of components for PLS model
I = grid_search_1d(param_to_optimise='number_components', search_values=1:5,
  model_index=2, factor_name='Class') *
  (mean_centre()+PLSDA(factor_name='Class'))
I = run(I,D,balanced_accuracy())
```

gs_line

Grid search line plot

Description

A plot of the calculated performance metric against the model input parameter values used to train the model. The optimum parameter value is indicated based on minimising (or maximising) the chosen metric.

Usage

```
gs_line(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `gs_line` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

Examples

```
C = gs_line()
```

HCA

Hierarchical Cluster Analysis

Description

Hierarchical Cluster Analysis is a numerical technique that uses agglomerative clustering to identify clusters or groupings of samples.

Usage

```
HCA(
  dist_method = "euclidean",
  cluster_method = "complete",
  minkowski_power = 2,
  factor_name,
  ...
)
```

Arguments

`dist_method` (character) Distance measure. Allowed values are limited to the following:

- "euclidean": The euclidean distance (2 norm).
- "maximum": The maximum distance.
- "manhattan": The absolute distance (1 norm).
- "canberra": A weighted version of the mahattan distance.
- "minkowski": A generalisation of manhattan and euclidean distance to nth norm.

The default is "euclidean".

`cluster_method` (character) Agglomeration method. Allowed values are limited to the following:

- "ward.D": Ward clustering.
- "ward.D2": Ward clustering using squared distances.
- "single": Single linkage.
- "complete": Complete linkage.

- "average": Average linkage (UPGMA).
- "mcquitty": McQuitty linkage (WPGMA).
- "median": Median linkage (WPGMC).
- "centroid": Centroid linkage (UPGMC).

The default is "complete".

minkowski_power (numeric) The default is 2.

factor_name (character) The name of a sample-meta column to use.

... Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- stats

Value

A HCA object with the following output slots:

dist_matrix (dist) An object containing pairwise distance information between samples.

hclust (hclust) An object of class hclust which describes the tree produced by the clustering process.

factor_df (data.frame)

References

R Core Team (2021). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. <https://www.R-project.org/>.

Examples

```
D = iris_DatasetExperiment()
M = HCA(factor_name='Species')
M = model_apply(M,D)
```

hca_dendrogram *HCA dendrogram*

Description

A dendrogram visualising the clustering by HCA.

Usage

```
hca_dendrogram(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `ggdendro`

Value

A `hca_dendrogram` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

de Vries A, Ripley BD (2020). *ggdendro: Create Dendrograms and Tree Diagrams Using 'ggplot2'*. R package version 0.1.22, <https://CRAN.R-project.org/package=ggdendro>.

Examples

```
C = hca_dendrogram()
```

HSD

Tukey's Honest Significant Difference

Description

Tukey's HSD post hoc test is a modified t-test applied for all features to all pairs of levels in a factor. It is used to determine which groups are different (if any). A multiple test corrected p-value is computed to indicate which groups are significantly different to the others for each feature.

Usage

```
HSD(alpha = 0.05, mtc = "fdr", formula, unbalanced = FALSE, ...)
```

Arguments

`alpha` (numeric) The p-value cutoff for determining significance. The default is `0.05`.

`mtc` (character) Multiple test correction method. Allowed values are limited to the following:

- `"bonferroni"`: Bonferroni correction in which the p-values are multiplied by the number of comparisons.
- `"fdr"`: Benjamini and Hochberg False Discovery Rate correction.
- `"none"`: No correction.

The default is `"fdr"`.

formula	(formula) A symbolic description of the model to be fitted.
unbalanced	(logical) Unbalanced model. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": A correction is applied for unbalanced designs. • "FALSE": No correction is applied for unbalanced designs. The default is FALSE.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- `agricolae`

Value

A HSD object with the following output slots:

difference	(data.frame)
UCL	(data.frame)
LCL	(data.frame)
p_value	(data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
significant	(data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

References

de Mendiburu F (2021). *agricolae: Statistical Procedures for Agricultural Research*. R package version 1.3-5, <https://CRAN.R-project.org/package=agricolae>.

Examples

```
D = iris_DatasetExperiment()
M = HSD(formula=y~Species)
M = model_apply(M,D)
```

HSDEM

Tukey's Honest Significant Difference using estimated marginal means

Description

Tukey's HSD post hoc test is a modified t-test applied for all features to all pairs of levels in a factor. It is used to determine which groups are different (if any). A multiple test corrected p-value is computed to indicate which groups are significantly different to the others for each feature. For mixed effects models estimated marginal means are used.

Usage

```
HSDEM(alpha = 0.05, mtc = "fdr", formula, ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
formula	(formula) A symbolic description of the model to be fitted.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- emmeans
- nlme

Value

A HSDem object with the following output slots:

p_value	(data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
significant	(data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

References

Lenth R (2021). *emmeans: Estimated Marginal Means, aka Least-Squares Means*. R package version 1.6.3, <https://CRAN.R-project.org/package=emmeans>.

Pinheiro J, Bates D, DebRoy S, Sarkar D, R Core Team (2021). *nlme: Linear and Nonlinear Mixed Effects Models*. R package version 3.1-153, <https://CRAN.R-project.org/package=nlme>.

Examples

```
D = iris_DatasetExperiment()
D$sample_meta$id=rownames(D) # dummy id column
M = HSDem(formula = y~Species+ Error(id/Species))
M = model_apply(M,D)
```

Description

A graphic for visualising the true class and the predicted class of samples in all groups for all cross-validation folds.

Usage

```
kfoldxcv_grid(factor_name, level, ...)
```

Arguments

`factor_name` (character) The name of a sample-meta column to use.
`level` (character) The level/group to plot.
`...` Additional slots and values passed to `struct_class`.

Value

A `kfoldxcv_grid` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = iris_DatasetExperiment()
I = kfold_xval(factor_name='Species') *
  (mean_centre() + PLSDA(factor_name='Species'))
I = run(I,D,balanced_accuracy())

C = kfoldxcv_grid(factor_name='Species',level='setosa')
chart_plot(C,I)
```

<code>kfoldxcv_metric</code>	<i>kfoldxcv metric plot</i>
------------------------------	-----------------------------

Description

A boxplot of the performance metric computed for each fold of a k-fold cross-validation.

Usage

```
kfoldxcv_metric(...)
```

Arguments

`...` Additional slots and values passed to `struct_class`.

Value

A `kfoldxcv_metric` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = kfoldxcv_metric()
```

kfold_xval	<i>k-fold cross-validation</i>
------------	--------------------------------

Description

k-fold cross-validation is an iterative approach applied to validate models. The samples are divided into k "folds", or subsets. Each subset is excluded from model training and used for model validation once, resulting in a single left-out prediction for each sample. Model performance metrics are then computed for the training and test sets across all folds.

Usage

```
kfold_xval(folds = 10, method = "venetian", factor_name, ...)
```

Arguments

folds	(numeric, integer) The number of cross-validation folds. The default is 10.
method	(character) Fold selection method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "venetian": Every nth sample is assigned to the same fold, where n is the number of folds. • "blocks": Blocks of adjacent samples are assigned to the same fold. • "random": Samples are randomly assigned to a fold. The default is "venetian".
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to <code>struct_class</code> .

Value

A `kfold_xval` object with the following output slots:

results	(data.frame)
metric	(data.frame)
metric.train	(numeric)
metric.test	(numeric)

Examples

```
D = iris_DatasetExperiment()
I = kfold_xval(factor_name='Species') *
  (mean_centre() + PLSDA(factor_name='Species'))
I = run(I,D,balanced_accuracy())
```

knn_impute	<i>kNN missing value imputation</i>
------------	-------------------------------------

Description

k-nearest neighbour missing value imputation replaces missing values in the data with the average of a predefined number of the most similar neighbours for which the value is present

Usage

```
knn_impute(  
  neighbours = 5,  
  sample_max = 50,  
  feature_max = 50,  
  by = "features",  
  ...  
)
```

Arguments

neighbours	(numeric) The number of neighbours (k) to use for imputation. The default is 5.
sample_max	(numeric) The maximum percent missing values per sample. The default is 50.
feature_max	(numeric) The maximum percent missing values per feature. The default is 50.
by	(character) Impute using similar "samples" or "features". Default features. The default is "features".
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A knn_impute object with the following output slots:

imputed (DatasetExperiment) A DatasetExperiment object containing the data where missing values have been imputed.

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
M = knn_impute()
```

kw_p_hist	<i>Histogram of p values</i>
-----------	------------------------------

Description

A histogram of the p-values computed by the kruskal-wallis method

Usage

```
kw_p_hist(...)
```

Arguments

... Additional slots and values passed to struct_class.

Value

A kw_p_hist object. This object has no output slots. See [chart_plot](#) in the struct package to plot this chart object.

Examples

```
C = kw_p_hist()
```

kw_rank_sum	<i>Kruskal-Wallis rank sum test</i>
-------------	-------------------------------------

Description

The Kruskal-Wallis test is a univariate hypothesis testing method that allows multiple ($n \geq 2$) groups to be compared without making the assumption that values are normally distributed. It is the non-parametric equivalent of a 1-way ANOVA. The test is applied to all variables/features individually, and multiple test corrected p-values are computed to indicate the significance of variables/features.

Usage

```
kw_rank_sum(alpha = 0.05, mtc = "fdr", factor_names, ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
factor_names	(character) The name of sample meta column(s) to use.
...	Additional slots and values passed to struct_class.

Value

A kw_rank_sum object with the following output slots:

test_statistic	(data.frame) The value of the calculated statistic which is converted to a p-value when compared to a chi2-
p_value	(data.frame) The probability of observing the calculated statistic.
dof	(numeric) The number of degrees of freedom used to calculate the test statistic.
significant	(data.frame) TRUE if the calculated p-value is less than the supplied threshold (alpha).
estimates	(data.frame)

Examples

```
D = iris_DatasetExperiment()
M = kw_rank_sum(factor_names='Species')
M = model_apply(M,D)
```

linear_model	<i>Linear model</i>
--------------	---------------------

Description

Linear models can be used to carry out regression, single stratum analysis of variance and analysis of covariance.

Usage

```
linear_model(formula, na_action = "na.omit", contrasts = list(), ...)
```

Arguments

formula	(formula) A symbolic description of the model to be fitted.
na_action	(character) NA action. Allowed values are limited to the following:

- "na.omit": Incomplete cases are removed.
- "na.fail": An error is thrown if NA are present.
- "na.exclude": Incomplete cases are removed, and the output result is padded to the correct size using NA.
- "na.pass": Does not apply a linear model if NA are present.

The default is "na.omit".

contrasts (list) The contrasts associated with a factor. The default is list.
 ... Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- stats

Value

A linear_model object with the following output slots:

lm	(lm) The lm object for this model_.
coefficients	(numeric) The coefficients for the fitted model_.
residuals	(numeric) The residuals for the fitted model_.
fitted_values	(numeric) The fitted values for the data used to train the model_.
predicted_values	(numeric) The predicted values for new data using the fitted model_.
r_squared	(numeric) The value of R Squared for the fitted model_.
adj_r_squared	(numeric) The value of Adjusted R Squared for the fitted model_.

References

R Core Team (2021). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. <https://www.R-project.org/>.

Examples

```
D = iris_DatasetExperiment()
M = linear_model(formula = y~Species)
```

log_transform

logarithm transform

Description

A logarithmic transform is applied to all values in the data matrix.

Usage

```
log_transform(base = 10, ...)
```

Arguments

base (numeric) The base of the logarithm used for the transform. The default is 10.
 ... Additional slots and values passed to `struct_class`.

Value

A `log_transform` object with the following output slots:

transformed (DatasetExperiment) A `DatasetExperiment` object containing the log transformed data.

struct object

Examples

```
M = log_transform()
```

mean_centre

Mean centre

Description

The mean sample is subtracted from all samples in the data matrix. The features in the centred matrix all have zero mean.

Usage

```
mean_centre(mode = "data", ...)
```

Arguments

mode (character) Mode of action. Allowed values are limited to the following:

- "data": Centring is applied to the data block.
- "sample_meta": Centring is applied to the sample_meta block.
- "both": Centring is applied to both the data and the sample_meta blocks.

The default is "data".

... Additional slots and values passed to `struct_class`.

Value

A `mean_centre` object with the following output slots:

centred	(DatasetExperiment)
mean_data	(numeric)
mean_sample_meta	(numeric)

Examples

```
M = mean_centre()
```

mean_of_medians	<i>Mean of medians</i>
-----------------	------------------------

Description

The data matrix is normalised by the mean of the median of each factor level.

Usage

```
mean_of_medians(factor_name, ...)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Value

A mean_of_medians object with the following output slots:

transformed	(DatasetExperiment) Data after the tranformation has been applied.
-------------	--

Examples

```
D = iris_DatasetExperiment()
M = mean_of_medians(factor_name='Species')
M = model_apply(M,D)
```

mixed_effect	<i>Mixed effects model</i>
--------------	----------------------------

Description

A mixed effects model is an extension of ANOVA where there are both fixed and random effects.

Usage

```
mixed_effect(alpha = 0.05, mtc = "fdr", formula, ss_type = "marginal", ...)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
formula	(formula) A symbolic description of the model to be fitted.
ss_type	(character) Sum of squares type. Allowed values are limited to the following: <ul style="list-style-type: none"> • "marginal": Type III sum of squares. • "sequential": Type II sum of squares. The default is "marginal".
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- nlme
- emmeans

Value

A `mixed_effect` object with the following output slots:

f_statistic	(data.frame) The value of the calculated statistic.
p_value	(data.frame) The probability of observing the calculated statistic if the null hypothesis is true.
significant	(data.frame) True/False indicating whether the p-value computed for each variable is less than the threshold.

References

Pinheiro J, Bates D, DebRoy S, Sarkar D, R Core Team (2021). *nlme: Linear and Nonlinear Mixed Effects Models*. R package version 3.1-153, <https://CRAN.R-project.org/package=nlme>.

Lenth R (2021). *emmeans: Estimated Marginal Means, aka Least-Squares Means*. R package version 1.6.3, <https://CRAN.R-project.org/package=emmeans>.

Fox J, Weisberg S (2019). *An R Companion to Applied Regression*, Third edition. Sage, Thousand Oaks CA. <https://socialsciences.mcmaster.ca/jfox/Books/Companion/>.

Examples

```
D = iris_DatasetExperiment()
D$sample_meta$id=rownames(D) # dummy id column
M = mixed_effect(formula = y~Species+ Error(id/Species))
M = model_apply(M,D)
```

model_apply,ANOVA,DatasetExperiment-method
Apply method

Description

Applies method to the input DatasetExperiment

Usage

```
## S4 method for signature 'ANOVA,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'HSD,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'mixed_effect,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'HSDEM,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'classical_lsq,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'confounders_clsq,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'constant_sum_norm,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'corr_coef,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'filter_smeta,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'fisher_exact,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'fold_change,DatasetExperiment'
```

```
model_apply(M, D)

## S4 method for signature 'fold_change_int,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'HCA,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'knn_impute,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'kw_rank_sum,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'log_transform,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'mean_of_medians,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'nroot_transform,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'pairs_filter,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'prop_na,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'rsd_filter,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'sb_corr,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'split_data,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'stratified_split,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'tSNE,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'ttest,DatasetExperiment'
model_apply(M, D)

## S4 method for signature 'vec_norm,DatasetExperiment'
```

```
model_apply(M, D)
```

```
## S4 method for signature 'wilcox_test,DatasetExperiment'
model_apply(M, D)
```

Arguments

M	a method object
D	another object used by the first

Value

Returns a modified method object

Examples

```
M=model()
model_apply(M,DatasetExperiment())
```

```
model_predict,DFA,DatasetExperiment-method
```

Model prediction

Description

Apply a model using the input DatasetExperiment. Assumes the model is trained first.

Usage

```
## S4 method for signature 'DFA,DatasetExperiment'
model_predict(M, D)

## S4 method for signature 'PCA,DatasetExperiment'
model_predict(M, D)

## S4 method for signature 'PLSDA,DatasetExperiment'
model_predict(M, D)

## S4 method for signature 'PLSR,DatasetExperiment'
model_predict(M, D)

## S4 method for signature 'autoscale,DatasetExperiment'
model_predict(M, D)

## S4 method for signature 'blank_filter,DatasetExperiment'
model_predict(M, D)
```

```
## S4 method for signature 'constant_sum_norm,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'dratio_filter,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'filter_by_name,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'filter_na_count,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'filter_smeta,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'glog_transform,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'linear_model,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'mean_centre,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'mv_feature_filter,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'mv_sample_filter,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'pareto_scale,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'pqn_norm,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'SVM,DatasetExperiment'  
model_predict(M, D)  
  
## S4 method for signature 'vec_norm,DatasetExperiment'  
model_predict(M, D)
```

Arguments

M	a model object
D	a DatasetExperiment object

Value

Returns a modified model object

Examples

```
M = example_model()
M = model_predict(M, iris_DatasetExperiment())
```

model_reverse, autoscale, DatasetExperiment-method
Reverse preprocessing

Description

Reverse the effect of a preprocessing step on a DatasetExperiment.

Usage

```
## S4 method for signature 'autoscale, DatasetExperiment'
model_reverse(M, D)

## S4 method for signature 'mean_centre, DatasetExperiment'
model_reverse(M, D)
```

Arguments

M a model object
D a DatasetExperiment object

Value

Returns a modified DatasetExperiment object

Examples

```
M = example_model()
D = model_reverse(M, iris_DatasetExperiment())
```

model_train,DFA,DataSetExperiment-method
Train a model

Description

Trains a model using the input DataSetExperiment

Usage

```
## S4 method for signature 'DFA,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'PCA,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'PLSDA,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'PLSR,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'autoscale,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'blank_filter,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'constant_sum_norm,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'dratio_filter,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'filter_by_name,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'filter_na_count,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'filter_smeta,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'glog_transform,DataSetExperiment'  
model_train(M, D)  
  
## S4 method for signature 'linear_model,DataSetExperiment'
```

```
model_train(M, D)

## S4 method for signature 'mean_centre,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'mv_feature_filter,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'mv_sample_filter,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'pareto_scale,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'pqn_norm,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'SVM,DatasetExperiment'
model_train(M, D)

## S4 method for signature 'vec_norm,DatasetExperiment'
model_train(M, D)
```

Arguments

M	a model object
D	a DatasetExperiment object

Value

Returns a modified model object

Examples

```
M = example_model()
M = model_train(M, iris_DatasetExperiment())
```

MTBLS79_DatasetExperiment

*MTBLS79: Direct infusion mass spectrometry metabolomics dataset:
a benchmark for data processing and quality control*

Description

Direct-infusion mass spectrometry (DIMS) metabolomics is an important approach for characterising molecular responses of organisms to disease, drugs and the environment. Increasingly

large-scale metabolomics studies are being conducted, necessitating improvements in both bio-analytical and computational workflows to maintain data quality. This dataset represents a systematic evaluation of the reproducibility of a multi-batch DIMS metabolomics study of cardiac tissue extracts. It comprises of twenty biological samples (cow vs. sheep) that were analysed repeatedly, in 8 batches across 7 days, together with a concurrent set of quality control (QC) samples. Data are presented from each step of the workflow and are available in MetaboLights (<https://www.ebi.ac.uk/metabolights/MTBLS79>)

Usage

```
MTBLS79_DatasetExperiment(filtered = FALSE)
```

Arguments

`filtered` TRUE to load data with quality control filters already applied, or FALSE to load the unfiltered data. Default is FALSE. The raw data is available from (<https://www.ebi.ac.uk/metabolights/MTBLS79>) and as an R dataset in the `pmp` package, available on Bioconductor.

Value

DatasetExperiment object

Examples

```
D = MTBLS79_DatasetExperiment()
summary(D)
```

mv_boxplot

Missing value boxplots

Description

Boxplots of the number of missing values per sample/feature.

Usage

```
mv_boxplot(
  label_outliers = TRUE,
  by_sample = TRUE,
  factor_name,
  show_counts = TRUE,
  ...
)
```

Arguments

- `label_outliers` (logical) Label outliers. Allowed values are limited to the following:
- "TRUE": Sample labels for potential outliers are displayed on the plot.
 - "FALSE": Sample labels are not included on the plot.
- The default is TRUE.
- `by_sample` (logical) Plot by sample or by feature. Allowed values are limited to the following:
- "TRUE": Missing values are plotted per sample.
 - "FALSE": Missing values are plotted per feature.
- The default is TRUE.
- `factor_name` (character) The name of a sample-meta column to use.
- `show_counts` (logical) Show counts. Allowed values are limited to the following:
- "TRUE": The number of samples for each box is displayed.
 - "FALSE": The number of samples for each box is not displayed.
- The default is TRUE.
- ... Additional slots and values passed to `struct_class`.

Value

A `mv_boxplot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = MTBLS79_DatasetExperiment()
C = mv_boxplot(factor_name='Class')
chart_plot(C,D)
```

`mv_feature_filter` *Filter by fraction missing values*

Description

Filters features where the percent number of missing values exceeds a predefined threshold.

Usage

```
mv_feature_filter(
  threshold = 20,
  qc_label = "QC",
  method = "QC",
  factor_name,
  ...
)
```

Arguments

threshold	(numeric) The threshold for excluding features. The default is 20.
qc_label	(character) The label used to identify QC samples. The default is "QC".
method	(character) Filtering method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "within_all": The filter is applied within classes. • "within_one": The filter is applied within any one class. • "QC": The filter is applied within QC samples. • "across": The filter is applied across all samples. The default is "QC".
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A mv_feature_filter object with the following output slots:

filtered	(DatasetExperiment) A DatasetExperiment object containing the filtered data.
flags	(data.frame)

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
D = iris_DatasetExperiment()
M = mv_feature_filter(factor_name='Species', qc_label='versicolor')
M = model_apply(M,D)
```

mv_feature_filter_hist

Histogram of missing values per feature

Description

A histogram of the proportion of missing values per feature.

Usage

```
mv_feature_filter_hist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `mv_feature_filter_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = mv_feature_filter_hist()
```

mv_histogram	<i>Missing value histogram</i>
--------------	--------------------------------

Description

A histogram of the numbers of missing values per sample/feature

Usage

```
mv_histogram(label_outliers = TRUE, by_sample = TRUE, ...)
```

Arguments

`label_outliers` (logical) Label outliers. Allowed values are limited to the following:

- "TRUE": Sample labels for potential outliers are displayed on the plot.
- "FALSE": Sample labels are not included on the plot.

The default is TRUE.

`by_sample` (logical) Plot by sample or by feature. Allowed values are limited to the following:

- "TRUE": Missing values are plotted per sample.
- "FALSE": Missing values are plotted per feature.

The default is TRUE.

... additional slots and values passed to `struct_class`

Value

A `mv_histogram` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

struct object

Examples

```
D = MTBLS79_DatasetExperiment()
C = mv_histogram(label_outliers=FALSE,by_sample=FALSE)
chart_plot(C,D)
```

mv_sample_filter	<i>Missing value sample filter</i>
------------------	------------------------------------

Description

Filters samples by removing those where the percent number of missing values exceeds a predefined threshold.

Usage

```
mv_sample_filter(mv_threshold = 20, ...)
```

Arguments

`mv_threshold` (numeric) The threshold for excluding samples. The default is 20.
`...` Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `pmp`

Value

A `mv_sample_filter` object with the following output slots:

<code>filtered</code>	(DatasetExperiment) A DatasetExperiment object containing the filtered data.
<code>flags</code>	(data.frame) A flag indicating whether the sample was rejected. 0 = rejected.
<code>percent_missing</code>	(data.frame)

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
C = mv_sample_filter()
```

`mv_sample_filter_hist` *Histogram of missing values per sample*

Description

A histogram of the the proportion of missing values per sample

Usage

```
mv_sample_filter_hist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `mv_sample_filter_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = mv_sample_filter_hist()
```

`nroot_transform` *nth root transform*

Description

All values in the data matrix are transformed by raising them to the power of $1/n$.

Usage

```
nroot_transform(root = 2, ...)
```

Arguments

`root` (numeric) The n th root used for the transform. The default is 2.

... Additional slots and values passed to `struct_class`.

Value

A `nroot_transform` object with the following output slots:

`transformed` (DatasetExperiment) A `DatasetExperiment` object containing the n th root transformed data.

Examples

```
M = nroot_transform()
```

ontology_cache	<i>ontology cache</i>
----------------	-----------------------

Description

A cached list of ontology terms obtained from the ontology lookup service (OLS) for ontology terms specified for objects in `structToolbox`.

Usage

```
ontology_cache()
```

Value

list of cached ontology terms

See Also

ontology

Examples

```
cache = ontology_cache()
```

pairs_filter	<i>Pairs filter</i>
--------------	---------------------

Description

This filter is used for study designs with paired sampling to ensure that measurements from the same source (e.g. patient) are represented in all factor levels and interactions.

Usage

```
pairs_filter(factor_name, sample_id, ...)
```

Arguments

<code>factor_name</code>	(character) The name of a sample-meta column to use.
<code>sample_id</code>	(character) Name of sample meta column containing sample identifiers.
<code>...</code>	Additional slots and values passed to <code>struct_class</code> .

Value

A `pairs_filter` object with the following output slots:

`filtered` (DatasetExperiment) A DatasetExperiment object after the filter has been applied.
`flags` (data.frame) A data.frame indicating whether features were filtered from the DatasetExperiment.

struct object

Examples

```
M=pairs_filter(factor_name='Class',sample_id='ids')
```

<code>pareto_scale</code>	<i>Pareto scaling</i>
---------------------------	-----------------------

Description

The mean sample is subtracted from all samples and then scaled by the square root of the standard deviation. The transformed data has zero mean.

Usage

```
pareto_scale(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `pareto_scale` object with the following output slots:

<code>scaled</code>	(DatasetExperiment)
<code>mean</code>	(numeric)
<code>sd</code>	(numeric)

Examples

```
D = iris_DatasetExperiment()
M = pareto_scale()
M = model_train(M,D)
M = model_predict(M,D)
```

PCA	<i>Principal Component Analysis (PCA)</i>
-----	---

Description

PCA is a multivariate data reduction technique. It summarises the data in a smaller number of Principal Components that maximise variance.

Usage

```
PCA(number_components = 2, ...)
```

Arguments

`number_components` (numeric, integer) The number of Principal Components calculated. The default is 2.

`...` Additional slots and values passed to `struct_class`.

Value

A PCA object with the following output slots:

<code>scores</code>	(DatasetExperiment)	A matrix of PCA scores where each column corresponds to a Principal Component.
<code>loadings</code>	(data.frame)	
<code>eigenvalues</code>	(data.frame)	
<code>ssx</code>	(numeric)	
<code>correlation</code>	(data.frame)	
<code>that</code>	(DatasetExperiment)	

Examples

```
M = PCA()
```

pca_biplot

PCA biplot

Description

A scatter plot of the selected principal component scores overlaid with the corresponding principal component loadings.

Usage

```
pca_biplot(
  components = c(1, 2),
  points_to_label = "none",
  factor_name,
  scale_factor = 0.95,
  style = "points",
```

```

    label_features = FALSE,
    ...
  )

```

Arguments

components (numeric) The principal components used to generate the plot. The default is `c(1,2)`.

points_to_label (character) `points_to_label`. Allowed values are limited to the following:

- "none": No samples are labelled on the plot.
- "all": All samples are labelled on the plot.
- "outliers": Potential outliers are labelled on the plot.

The default is "none".

factor_name (character) The name of a sample-meta column to use.

scale_factor (numeric) The scaling factor applied to the loadings. The default is `0.95`.

style (character) Plot style. Allowed values are limited to the following:

- "points": Loadings and scores are plotted as a scatter plot.
- "arrows": The loadings are plotted as arrow vectors.

The default is "points".

label_features (logical) Add feature labels. Allowed values are limited to the following:

- "TRUE": Features are labelled.
- "FALSE": Features are not labelled.

The default is `FALSE`.

... Additional slots and values passed to `struct_class`.

Value

A `pca_biplot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = pca_biplot(factor_name='Species')
```

pca_correlation_plot *PCA correlation plot*

Description

A plot of the correlation between the variables/features and the selected principal component scores. Features with high correlation are well represented by the selected component(s)

Usage

```
pca_correlation_plot(components = c(1, 2), ...)
```

Arguments

components (numeric) The Principal Components used to generate the plot. The default is c(1,2).
 ... Additional slots and values passed to struct_class.

Value

A pca_correlation_plot object. This object has no output slots. See [chart_plot](#) in the struct package to plot this chart object.

Examples

```
C = pca_correlation_plot()
```

pca_dstat_plot *d-statistic plot*

Description

A bar chart of the d-statistics for samples in the input PCA model. Samples above the indicated threshold are considered to be outlying.

Usage

```
pca_dstat_plot(number_components = 2, alpha = 0.05, ...)
```

Arguments

number_components (numeric) The number of principal components to use. The default is 2.
 alpha (numeric) A confidence threshold for rejecting samples based on the d-statistic. The default is 0.05.
 ... Additional slots and values passed to struct_class.

Value

A `pca_dstat_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = pca_dstat_plot()
```

`pca_loadings_plot` *PCA loadings plot*

Description

A barchart (one component) or scatter plot (two components) of the selected principal component loadings.

Usage

```
pca_loadings_plot(
  components = c(1, 2),
  style = "points",
  label_features = NULL,
  ...
)
```

Arguments

<code>components</code>	(numeric) The principal components used to generate the plot. The default is <code>c(1,2)</code> .
<code>style</code>	(character) Plot style. Allowed values are limited to the following: <ul style="list-style-type: none"> • <code>"points"</code>: Loadings and scores are plotted as a scatter plot. • <code>"arrows"</code>: The loadings are plotted as arrow vectors. The default is <code>"points"</code> .
<code>label_features</code>	(character, NULL) Feature labels. Allowed values are limited to the following: <ul style="list-style-type: none"> • <code>"character()"</code>: A vector of labels for the features. • <code>"NULL"</code>: No labels. • <code>"row.names"</code>: Labels will be extracted from the column names of the data matrix. The default is <code>NULL</code> .
<code>...</code>	Additional slots and values passed to <code>struct_class</code> .

Value

A `pca_loadings_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = pca_loadings_plot()
```

pca_scores_plot *PCA scores plot*

Description

Plots a 2d scatter plot of the selected components

Usage

```
pca_scores_plot(
  components = c(1, 2),
  points_to_label = "none",
  factor_name,
  ellipse = "all",
  ellipse_type = "norm",
  ellipse_confidence = 0.95,
  label_filter = character(0),
  label_factor = "rownames",
  label_size = 3.88,
  ...
)
```

Arguments

components (numeric) The components selected for plotting. The default is `c(1, 2)`.

points_to_label (character) Points to label. Allowed values are limited to the following:

- "none": No samples labels are displayed.
- "all": The labels for all samples are displayed.
- "outliers": Labels for for potential outlier samples are displayed.

The default is "none".

factor_name (character) The name of a sample-meta column to use.

ellipse (character) Plot ellipses. Allowed values are limited to the following:

- "all": Ellipses are plotted for all groups and all samples.
- "group": Ellipses are plotted for all groups.
- "none": Ellipses are not included on the plot.
- "sample": An ellipse is plotted for all samples (ignoring group).

The default is "all".

ellipse_type (character) Type of ellipse. Allowed values are limited to the following:

- "norm": Multivariate normal ($p = 0.95$).

- "t": Multivariate t ($p = 0.95$).
The default is "norm".
- ellipse_confidence (numeric) The confidence level for plotting ellipses. The default is 0.95.
- label_filter (character) Labels are only plotted for the named groups. If zero-length then all groups are included. The default is character(0).
- label_factor (character) The column name of sample_meta to use for labelling samples on the plot. "rownames" will use the row names from sample_meta. The default is "rownames".
- label_size (numeric) The text size of labels. Note this is not in Font Units. The default is 3.88.
- ... Additional slots and values passed to struct_class.

Value

A `pca_scores_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre() + PCA()
M = model_apply(M,D)
C = pca_scores_plot(factor_name = 'Species')
chart_plot(C,M[2])
```

<code>pca_scee_plot</code>	<i>Scree plot</i>
----------------------------	-------------------

Description

A plot of the percent variance and cumulative percent variance for the components of a PCA model.

Usage

```
pca_scee_plot(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `pca_scee_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

struct object

Examples

```
C = pca_scree_plot()
```

permutation_test	<i>Permutation test</i>
------------------	-------------------------

Description

A permutation test generates a "null" model by randomising the response (for regression models) or group labels (for classification models). This is repeated many times to generate a distribution of performance metrics for the null model. This distribution can then be compared to the performance of the true model. If there is overlap between the true and null model performances then the model is overfitted.

Usage

```
permutation_test(number_of_permutations = 50, factor_name, ...)
```

Arguments

number_of_permutations	(numeric, integer) The number of permutations. The default is 50.
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to struct_class.

Value

A permutation_test object with the following output slots:

results.permuted	(data.frame)
results.unpermuted	(data.frame)
metric	(data.frame)

Examples

```
I=permutation_test(factor_name='Species')
```

permutation_test_plot	<i>permutation_test_plot class</i>
-----------------------	------------------------------------

Description

Plots the results of a permutation test.

Usage

```
permutation_test_plot(style = "boxplot", binwidth = 0.05, ...)
```

Arguments

style	The plot style. One of 'boxplot', 'violin', 'histogram', 'density' or 'scatter'.
binwidth	Binwidth for the "histogram" style. Ignored for all other styles.
...	additional slots and values passed to struct_class

Value

struct object

Examples

```
C = permutation_test_plot(style='boxplot')
```

permute_sample_order *Permute Sample Order*

Description

The order of samples in the data matrix is randomly permuted. The relationship between the samples and the sample meta data is maintained.

Usage

```
permute_sample_order(number_of_permutations = 10, ...)
```

Arguments

number_of_permutations	(numeric, integer) The number of times the sample order is permuted. The default is 10.
...	Additional slots and values passed to struct_class.

Value

A permute_sample_order object with the following output slots:

results	(data.frame)
metric	(data.frame)
metric.train	(numeric)

Examples

```
C = permute_sample_order()
```

PLSDA

Partial least squares discriminant analysis

Description

PLS is a multivariate regression technique that extracts latent variables maximising covariance between the input data and the response. The Discriminant Analysis variant uses group labels in the response variable and applies a threshold to the predicted values in order to predict group membership for new samples.

Usage

```
PLSDA(number_components = 2, factor_name, ...)
```

Arguments

`number_components` (numeric, integer) The number of PLS components. The default is 2.

`factor_name` (character) The name of a sample-meta column to use.

`...` Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `pls`

Value

A PLSDA object with the following output slots:

<code>scores</code>	(data.frame)
<code>loadings</code>	(data.frame)
<code>yhat</code>	(data.frame)
<code>design_matrix</code>	(data.frame)
<code>y</code>	(data.frame)
<code>reg_coeff</code>	(data.frame)
<code>probability</code>	(data.frame)
<code>vip</code>	(data.frame)
<code>pls_model</code>	(list)
<code>pred</code>	(data.frame)
<code>threshold</code>	(numeric)

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.

Perez NF, Ferre J, Boque R (2009). "Calculation of the reliability of classification in discriminant partial least-squares binary classification." *Chemometrics and Intelligent Laboratory Systems*, **95**(2), 122-128.

Barker M, Rayens W (2003). "Partial least squares for discrimination." *Journal of Chemometrics*, **17**(3), 166-173.

Examples

```
M = PLSDA('number_components'=2, factor_name='Species')
```

```
plsda_predicted_plot  PLSDA predicted plot
```

Description

A plot of the regression coefficients from a PLSDA model.

Usage

```
plsda_predicted_plot(factor_name, style = "boxplot", ...)
```

Arguments

<code>factor_name</code>	(character) The name of a sample-meta column to use.
<code>style</code>	(character) Plot style. Allowed values are limited to the following: <ul style="list-style-type: none"> "boxplot": A boxplot. "violin": A violin plot. "density": A density plot. The default is "boxplot".
<code>...</code>	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- `pls`
- `ggplot2`

Value

A `plsda_predicted_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_predicted_plot(factor_name='Species')
chart_plot(C,M[2])
```

plsda_regcoeff_plot *plsda_regcoeff_plot class*

Description

Plots the regression coefficients of a PLSDA model.

Usage

```
plsda_regcoeff_plot(level, ...)
```

Arguments

level	the group label to plot regression coefficients for
...	additional slots and values passed to struct_class

Value

struct object

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_regcoeff_plot(level='setosa')
chart_plot(C,M[2])
```

plsda_roc_plot	<i>PLSDA ROC plot</i>
----------------	-----------------------

Description

A Receiver Operator Characteristic (ROC) plot for PLSDA models computed by adjusting the threshold for assigning group labels from PLS predictions.

Usage

```
plsda_roc_plot(factor_name, ...)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- `pls`
- `ggplot2`

Value

A `plsda_roc_plot` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_roc_plot(factor_name='Species')
chart_plot(C,M[2])
```

plsda_scores_plot *PLSDA scores plot*

Description

A scatter plot of the selected PLSDA scores.

Usage

```
plsda_scores_plot(  
  components = c(1, 2),  
  points_to_label = "none",  
  factor_name,  
  ...  
)
```

Arguments

`components` (numeric) The components selected for plotting. The default is `c(1, 2)`.
`points_to_label` (character) Points to label. Allowed values are limited to the following:

- "none": No samples labels are displayed.
- "all": The labels for all samples are displayed.
- "outliers": Labels for for potential outlier samples are displayed.

The default is "none".
`factor_name` (character) The name of a sample-meta column to use.
... Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `pls`
- `ggplot2`

Value

A `plsda_scores_plot` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.
Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_scores_plot(factor_name='Species')
chart_plot(C,M[2])
```

plsda_vip_plot

PLSDA VIP plot

Description

A plot of the Variable Importance for Projection (VIP) scores for a PLSDA model.

Usage

```
plsda_vip_plot(threshold = 1, level, ...)
```

Arguments

threshold	(numeric, integer) The threshold for indicating significant features. The default is 1.
level	(character) The factor level (group) to plot.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- pls
- ggplot2

Value

A `plsda_vip_plot` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_vip_plot(level='setosa')
chart_plot(C,M[2])
```

plsda_vip_summary_plot

PLSDA VIP summary plot

Description

A plot of the Variable Importance for Projection (VIP) scores for a PLSDA model for the top selected features.

Usage

```
plsda_vip_summary_plot(n_features = 50, ...)
```

Arguments

n_features	(numeric, integer) The number of features to include in the summary. The default is 50.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- pls
- ggplot2
- reshape2
- cowplot

Value

A `plsda_vip_summary_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

References

- Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.
- Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. ISBN 978-3-319-24277-4, <https://ggplot2.tidyverse.org>.
- Wickham H (2007). “Reshaping Data with the reshape Package.” *Journal of Statistical Software*, **21**(12), 1–20. <http://www.jstatsoft.org/v21/i12/>.
- Wilke C (2020). *cowplot: Streamlined Plot Theme and Plot Annotations for 'ggplot2'*. R package version 1.1.1, <https://CRAN.R-project.org/package=cowplot>.

Examples

```
D = iris_DatasetExperiment()
M = mean_centre()+PLSDA(factor_name='Species')
M = model_apply(M,D)

C = plsda_vip_summary_plot(n_features=30)
chart_plot(C,M[2])
```

PLSR

Partial least squares regression

Description

PLS is a multivariate regression technique that extracts latent variables maximising covariance between the input data and the response. For regression the response is a continuous variable.

Usage

```
PLSR(number_components = 2, factor_name, ...)
```

Arguments

number_components	(numeric, integer) The number of PLS components. The default is 2.
factor_name	(character) The name of a sample-meta column to use.
...	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- `pls`

Value

A PLSR object with the following output slots:

scores	(data.frame)
loadings	(data.frame)
y	(data.frame)
yhat	(data.frame)
reg_coeff	(data.frame)
vip	(data.frame)
pls_model	(list)
pred	(data.frame)

References

Liland K, Mevik B, Wehrens R (2021). *pls: Partial Least Squares and Principal Component Regression*. R package version 2.8-0, <https://CRAN.R-project.org/package=pls>.

Examples

```
M = PLSR(factor_name='run_order')
```

plsr_cook_dist	<i>Cook's distance barchart</i>
----------------	---------------------------------

Description

A barchart of Cook's distance for each sample used to train a PLSR model. Cook's distance is used to estimate the influence of a sample on the model and can be used to identify potential outliers.

Usage

```
plsr_cook_dist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `plsr_cook_dist` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

Examples

```
C = plsr_cook_dist()
```

plsr_prediction_plot *PLSR prediction plot*

Description

A scatter plot of the true response values against the predicted values for a PLSR model.

Usage

```
plsr_prediction_plot(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `plsr_prediction_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = plsr_prediction_plot()
```

plsr_qq_plot *PLSR QQ plot*

Description

A plot of the quantiles of the residuals from a PLSR model against the quantiles of a normal distribution.

Usage

```
plsr_qq_plot(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `plsr_qq_plot` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = plsr_qq_plot()
```

plsr_residual_hist *PLSR residuals histogram*

Description

A histogram of the residuals for a PLSR model.

Usage

```
plsr_residual_hist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `plsr_residual_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = plsr_residual_hist()
```

pqn_norm *Probabilistic Quotient Normalisation (PQN)*

Description

PQN is used to normalise for differences in concentration between samples. It makes use of Quality Control (QC) samples as a reference. PQN scales by the median change relative to the reference in order to be more robust against changes caused by response to perturbation.

Usage

```
pqn_norm(  
  qc_label = "QC",  
  factor_name,  
  qc_frac = 0,  
  sample_frac = 0,  
  ref_method = "mean",  
  ref_mean = NULL,  
  ...  
)
```

Arguments

qc_label	(character) The label used to identify QC samples. The default is "QC".
factor_name	(character) The name of a sample-meta column to use.
qc_frac	(numeric) A value between 0 and 1 to indicate the minimum proportion of QC samples a feature must be present in for it to be included when computing the reference. Default qc_frac = 0. . The default is 0.
sample_frac	(numeric) A value between 0 and 1 to indicate the minimum proportion of samples a feature must be present in for it to be considered when computing the normalisation coefficients. . The default is 0.
ref_method	(character) Reference computation method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "mean": The reference is computed as the mean of the samples matching the qc_label input. • "median": The reference is computed as the median of the samples matching the qc_label_input. The default is "mean".
ref_mean	(numeric, NULL) A single sample to use as the reference for normalisation. If set to NULL then the reference will be computed based on the other input parameters (ref_mean, qc_label etc). . The default is NULL.
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A pqn_norm object with the following output slots:

normalised	(DatasetExperiment) A DatasetExperiment object containing the normalised data.
coeff	(data.frame) The normalisation coefficients calculated by PQN.

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
D = iris_DatasetExperiment()
M = pqn_norm(factor_name='Species',qc_label='all')
M = model_apply(M,D)
```

pqn_norm_hist	<i>PQN coefficient histogram</i>
---------------	----------------------------------

Description

A histogram of the PQN coefficients for all features

Usage

```
pqn_norm_hist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `pqn_norm_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = pqn_norm_hist()
```

prop_na	<i>Fisher's exact test for missing values</i>
---------	---

Description

A Fisher's exact test is used to compare the number of missing values in each group. Multiple test corrected p-values are computed to indicate whether there is a significant difference in the number of missing values across groups for each feature.

Usage

```
prop_na(alpha = 0.05, mtc = "fdr", factor_name, ...)
```

Arguments

`alpha` (numeric) The p-value cutoff for determining significance. The default is `0.05`.

`mtc` (character) Multiple test correction method. Allowed values are limited to the following:

- "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons.
- "fdr": Benjamini and Hochberg False Discovery Rate correction.

- "none": No correction.
The default is "fdr".
- factor_name (character) The name of a sample-meta column to use.
... Additional slots and values passed to struct_class.

Value

A prop_na object with the following output slots:

- p_value (data.frame) The probability of observing the calculated statistic.
significant (data.frame) TRUE if the calculated p-value is less than the supplied threshold (alpha).
na_count (data.frame) The number of NA values per group of the chosen factor.

struct object

Examples

```
M = prop_na(factor_name='Species')
```

rsd_filter

RSD filter

Description

An RSD filter calculates the relative standard deviation (the ratio of the standard deviation to the mean) for all features. Any feature with an RSD greater than a predefined threshold is excluded.

Usage

```
rsd_filter(rsd_threshold = 20, qc_label = "QC", factor_name, ...)
```

Arguments

- rsd_threshold (numeric) The RSD threshold above which features are removed. The default is 20.
qc_label (character) The label used to identify QC samples. The default is "QC".
factor_name (character) The name of a sample-meta column to use.
... Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A `rsd_filter` object with the following output slots:

`filtered` (DatasetExperiment) A DatasetExperiment object containing the filtered data.
`flags` (data.frame) RSD and a flag indicating whether the feature was rejected by the filter or not.
`rsd_qc` (data.frame) The calculated RSD of the QC class.

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Examples

```
M = rsd_filter(factor_name='Class')
```

<code>rsd_filter_hist</code>	<i>RSD histogram</i>
------------------------------	----------------------

Description

A histogram of the calculated RSD values.

Usage

```
rsd_filter_hist(...)
```

Arguments

... Additional slots and values passed to `struct_class`.

Value

A `rsd_filter_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
C = rsd_filter_hist()
```

run,bootstrap,DataSetExperiment,metric-method

Runs an iterator, applying the chosen model multiple times.

Description

Running an iterator will apply the iterator a number of times to a DataSetExperiment. For example, in cross-validation the same model is applied multiple times to the same data, splitting it into training and test sets. The input metric object can be calculated and collected for each iteration as an output.

Usage

```
## S4 method for signature 'bootstrap,DataSetExperiment,metric'  
run(I, D, MET = NULL)  
  
## S4 method for signature 'forward_selection_by_rank,DataSetExperiment,metric'  
run(I, D, MET)  
  
## S4 method for signature 'grid_search_1d,DataSetExperiment,metric'  
run(I, D, MET)  
  
## S4 method for signature 'kfold_xval,DataSetExperiment,metric'  
run(I, D, MET = NULL)  
  
## S4 method for signature 'permutation_test,DataSetExperiment,metric'  
run(I, D, MET = NULL)  
  
## S4 method for signature 'permute_sample_order,DataSetExperiment,metric'  
run(I, D, MET)
```

Arguments

I	an iterator object
D	a DataSetExperiment object
MET	a metric object

Value

Modified iterator object

Examples

```
D = iris_DataSetExperiment() # get some data  
MET = metric() # use a metric  
I = example_iterator() # initialise iterator  
models(I) = example_model() # set the model  
I = run(I,D,MET) # run
```

r_squared	<i>Coefficient of determination (R-squared)</i>
-----------	---

Description

R-squared is a metric used to assess the goodness of fit for regression models. It measures how much variance of one variable can be explained by another variable.

Usage

```
r_squared(...)
```

Arguments

```
... Additional slots and values passed to struct_class.
```

Value

A `r_squared` object. This object has no output slots.

Examples

```
MET = r_squared()
```

sb_corr	<i>Signal/batch correction for mass spectrometry data</i>
---------	---

Description

Applies Quality Control Robust Spline (QC-RSC) method to correct for signal drift and batch differences in mass spectrometry data.

Usage

```
sb_corr(  
  order_col,  
  batch_col,  
  qc_col,  
  smooth = 0,  
  use_log = TRUE,  
  min_qc = 4,  
  qc_label = "QC",  
  spar_lim = c(-1.5, 1.5),  
  ...  
)
```

Arguments

order_col	(character) The column name of sample_meta indicating the run order of the samples.
batch_col	(character) The column name of sample_meta indicating the batch each sample was measured in.
qc_col	(character) The column name of sample_meta indicating the group each sample is a member of.
smooth	(numeric) The amount of smoothing applied (0 to 1). If set to 0 the smoothing parameter will be estimated using leave-one-out cross-validation. The default is 0.
use_log	(logical) Log transformation. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": The data is log transformed prior to performing signal correction. • "FALSE": Signal correction is applied to the input data. The default is TRUE.
min_qc	(numeric) The minimum number of QC samples required for signal correction. The default is 4.
qc_label	(character) The label used to identify QC samples. The default is "QC".
spar_lim	(numeric) A two element vector specifying the upper and lower limits when 'spar = 0'. Allows the value of 'spar' to be constrained within these limits to prevent overfitting. The default is c(-1.5, 1.5).
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- pmp

Value

A sb_corr object with the following output slots:

corrected	(DatasetExperiment) The DatasetExperiment after signal/batch correction has been applied.
fitted	(data.frame) The fitted splines for each feature.

struct object

References

Jankevics A, Lloyd GR, Weber RJM (2021). *pmp: Peak Matrix Processing and signal batch correction for metabolomics datasets*. R package version 1.5.0.

Kirwan JA, Broadhurst DI, Davidson RL, Viant MR (2013). "Characterising and correcting batch variation in an automated direct infusion mass spectrometry (DIMS) metabolomics workflow." *Analytical and Bioanalytical Chemistry*, **405**(15), 5147-5157.

Examples

```
M = sb_corr(order_col='run_order', batch_col='batch_no', qc_col='class')
```

split_data	<i>Split data</i>
------------	-------------------

Description

The data matrix is divided into two subsets. A predefined proportion of the samples are randomly selected for a training set, and the remaining samples are used for the test set.

Usage

```
split_data(p_train, ...)
```

Arguments

`p_train` (numeric) The proportion of samples selected for the training set.
`...` Additional slots and values passed to `struct_class`.

Value

A `split_data` object with the following output slots:

`training` (DatasetExperiment) A DatasetExperiment object containing samples selected for the training set.
`testing` (DatasetExperiment) A DatasetExperiment object containing samples selected for the testing set.

Examples

```
M = split_data(p_train=0.75)
```

stratified_split	<i>Stratified sampling</i>
------------------	----------------------------

Description

The dataset is divided into two subsets. A predefined proportion of samples from each level of a factor is selected for the training set, and the remaining samples are used for the test set. The stratification by factor level means that the relative number of samples per level is approximately equal to the original dataset.

Usage

```
stratified_split(p_train, factor_name, ...)
```

Arguments

`p_train` (numeric) The proportion of samples selected for the training set.
`factor_name` (character) The name of a sample-meta column to use.
`...` Additional slots and values passed to `struct_class`.

Value

A `stratified_split` object with the following output slots:

`training` (DatasetExperiment) A `DatasetExperiment` object containing samples selected for the training set.
`testing` (DatasetExperiment) A `DatasetExperiment` object containing samples selected for the testing set.

Examples

```
D = iris_DatasetExperiment()
M = stratified_split(p_train=0.75, factor_name='Species')
M = model_apply(M,D)
```

<code>structToolbox</code>	<i>structToolbox: Examples of tools built using the Statistics in R Using Class Templates (struct) package</i>
----------------------------	--

Description

This package extends the classes defined in the `struct` package

SVM	<i>Support Vector Machine Classifier</i>
-----	--

Description

Support Vector Machines (SVM) are a machine learning algorithm for classification. They can make use of kernel functions to generate highly non-linear boundaries between groups.

Usage

```
SVM(
  factor_name,
  kernel = "linear",
  degree = 3,
  gamma = 1,
  coef0 = 0,
  cost = 1,
  class_weights = NULL,
  ...
)
```

Arguments

factor_name	(character) The name of a sample-meta column to use.
kernel	(character) Kernel type. Allowed values are limited to the following: <ul style="list-style-type: none"> • "linear": . • "polynomial": . • "radial": . • "sigmoid": . The default is "linear".
degree	(numeric) The polynomial degree. The default is 3.
gamma	(numeric) The gamma parameter. The default is 1.
coef0	(numeric) The offset coefficient. The default is 0.
cost	(numeric) The cost of violating the constraints. The default is 1.
class_weights	(numeric, character, NULL) A named vector of weights for the different classes. Specifying "inverse" will choose the weights inversely proportional to the class distribution. The default is NULL.
...	Additional slots and values passed to struct_class.

Details

This object makes use of functionality from the following packages:

- e1071

Value

A SVM object with the following output slots:

SV	(matrix)
index	(numeric)
coefs	(matrix)
pred	(data.frame)
decision_values	(data.frame)

struct object

References

Meyer D, Dimitriadou E, Hornik K, Weingessel A, Leisch F (2021). *e1071: Misc Functions of the Department of Statistics, Probability Theory Group (Formerly: E1071), TU Wien*. R package version 1.7-8, <https://CRAN.R-project.org/package=e1071>.

Brereton RG, Lloyd GR (2010). "Support Vector Machines for classification and regression." *The Analyst*, **135**(2), 230-267.

Examples

```
M = SVM(factor_name='Species',gamma=1)
```

```
svm_plot_2d
```

```
SVM scatter plot
```

Description

A scatter plot of the input data by group and the calculated boundary of a SVM model.

Usage

```
svm_plot_2d(factor_name, npoints = 100, ...)
```

Arguments

`factor_name` (character) The name of a sample-meta column to use.
`npoints` (numeric) The number of grid points used to plot the boundary. The default is 100.
`...` Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- `e1071`

Value

A `svm_plot_2d` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

Meyer D, Dimitriadou E, Hornik K, Weingessel A, Leisch F (2021). *e1071: Misc Functions of the Department of Statistics, Probability Theory Group (Formerly: E1071), TU Wien*. R package version 1.7-8, <https://CRAN.R-project.org/package=e1071>.

Examples

```
D = iris_DatasetExperiment()
M = filter_smeta(mode='exclude',levels='setosa',factor_name='Species') +
  mean_centre()+PCA(number_components=2)+
  SVM(factor_name='Species',kernel='linear')
M = model_apply(M,D)

C = svm_plot_2d(factor_name='Species')
chart_plot(C,M[4],predicted(M[3]))
```

tic_chart	<i>Total Ion Count chart.</i>
-----------	-------------------------------

Description

A scatter plot of Total Ion Count (sum of each sample) versus run order.

Usage

```
tic_chart(run_order, factor_name, connected = FALSE, ...)
```

Arguments

run_order	(character) The column name of sample_meta indicating the run order of the samples.
factor_name	(character) The name of a sample-meta column to use.
connected	(logical) Plot samples connected by a grey line. The default is FALSE.
...	Additional slots and values passed to struct_class.

Value

A `tic_chart` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
D = iris_DatasetExperiment()
D$sample_meta$run_order=1:nrow(D)
C = tic_chart(factor_name='Species',run_order='run_order')
chart_plot(C,D)
```

tSNE	<i>tSNE</i>
------	-------------

Description

t-Distributed Stochastic Neighbor Embedding.

Usage

```
tSNE(
  dims = 2,
  perplexity = 30,
  max_iter = 100,
  theta = 0.5,
  check_duplicates = FALSE,
  init = NULL,
  eta = 200,
  ...
)
```

Arguments

<code>dims</code>	(numeric) The number of tSNE dimensions computed. The default is 2.
<code>perplexity</code>	(numeric) Perplexity parameter. The default is 30.
<code>max_iter</code>	(numeric) The maximum number of tSNE iterations. The default is 100.
<code>theta</code>	(numeric) Speed/accuracy trade-off. A value of 0 gives an exact tSNE. The default is 0.5.
<code>check_duplicates</code>	(logical) Check for duplicates. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": Checks for the presence of exact duplicate samples. • "FALSE": Does not check for exact duplicate samples. The default is FALSE.
<code>init</code>	(NULL, data.frame, DatasetExperiment) A set of coordinates for initialising the tSNE algorithm. NULL uses random initialisation. The default is NULL.
<code>eta</code>	(numeric) The learning rate parameter. The default is 200.
<code>...</code>	Additional slots and values passed to <code>struct_class</code> .

Details

This object makes use of functionality from the following packages:

- Rtsne

Value

A tSNE object with the following output slots:

Y (DatasetExperiment)

References

van der Maaten L, Hinton G (2008). "Visualizing High-Dimensional Data Using t-SNE." *Journal of Machine Learning Research*, **9**, 2579-2605.

van der Maaten L (2014). “Accelerating t-SNE using Tree-Based Algorithms.” *Journal of Machine Learning Research*, **15**, 3221-3245.

Krijthe JH (2015). *Rtsne: T-Distributed Stochastic Neighbor Embedding using Barnes-Hut Implementation*. R package version 0.15, <https://github.com/jkrijthe/Rtsne>.

Examples

```
M = tSNE()
```

tSNE_scatter	<i>Feature boxplot</i>
--------------	------------------------

Description

plots the new representation of data after applying tSNE.

Usage

```
tSNE_scatter(factor_name, ...)
```

Arguments

`factor_name` (character) The name of a sample-meta column to use.
`...` Additional slots and values passed to `struct_class`.

Details

This object makes use of functionality from the following packages:

- Rtsne

Value

A `tSNE_scatter` object. This object has no output slots. See `chart_plot` in the `struct` package to plot this chart object.

References

van der Maaten L, Hinton G (2008). “Visualizing High-Dimensional Data Using t-SNE.” *Journal of Machine Learning Research*, **9**, 2579-2605.

van der Maaten L (2014). “Accelerating t-SNE using Tree-Based Algorithms.” *Journal of Machine Learning Research*, **15**, 3221-3245.

Krijthe JH (2015). *Rtsne: T-Distributed Stochastic Neighbor Embedding using Barnes-Hut Implementation*. R package version 0.15, <https://github.com/jkrijthe/Rtsne>.

Examples

```
M = tSNE_scatter(factor_name='Species')
```

ttest

t-test

Description

A t-test compares the means of two factor levels. Multiple-test corrected p-values are used to indicate the significance of the computed difference for all features.

Usage

```
ttest(
  alpha = 0.05,
  mtc = "fdr",
  factor_names,
  paired = FALSE,
  paired_factor = character(0),
  equal_variance = FALSE,
  conf_level = 0.95,
  ...
)
```

Arguments

- | | |
|----------------|--|
| alpha | (numeric) The p-value cutoff for determining significance. The default is 0.05. |
| mtc | (character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr". |
| factor_names | (character) The name of sample meta column(s) to use. |
| paired | (logical) Apply a paired t-test. The default is FALSE. |
| paired_factor | (character) The factor name that encodes the sample id for pairing. The default is character(0). |
| equal_variance | (logical) Equal variance. Allowed values are limited to the following: <ul style="list-style-type: none"> • "TRUE": The variance of each group is treated as being equal using the pooled variance to estimate the variance. • "FALSE": The variance of each group is not assumed to be equal and the Welch (or Satterthwaite) approximation is used. |

The default is FALSE.
 conf_level (numeric) The confidence level of the interval. The default is 0.95.
 ... Additional slots and values passed to struct_class.

Value

A ttest object with the following output slots:

t_statistic (data.frame) The value of the calculate statistics which is converted to a p-value when compared to a t-distribution.
 p_value (data.frame) The probability of observing the calculated t-statistic.
 dof (numeric) The number of degrees of freedom used to calculate the test statistic.
 significant (data.frame) TRUE if the calculated p-value is less than the supplied threshold (alpha).
 conf_int (data.frame) Confidence interval for t statistic.
 estimates (data.frame) The group means estimated when computing the t-statistic.

Examples

```
M = ttest(factor_name='Class')
```

vec_norm *Vector normalisation*

Description

The samples in the data matrix are normalised to account for differences in concentration by scaling each sample such that the sum of squares is equal to 1.

Usage

```
vec_norm(...)
```

Arguments

... Additional slots and values passed to struct_class.

Value

A vec_norm object with the following output slots:

normalised (DatasetExperiment) A DatasetExperiment object containing the normalised data.
 coeff (data.frame) The normalisation coefficients calculated by PQN.

struct object

Examples

```
M = vec_norm()
```

wilcox_p_hist	<i>Histogram of p values</i>
---------------	------------------------------

Description

A histogram of p values for the wilcoxon signed rank test

Usage

```
wilcox_p_hist(...)
```

Arguments

... Additional slots and values passed to struct_class.

Value

A `wilcox_p_hist` object. This object has no output slots. See [chart_plot](#) in the `struct` package to plot this chart object.

Examples

```
M = wilcox_p_hist()
```

wilcox_test	<i>wilcoxon signed rank test</i>
-------------	----------------------------------

Description

A Mann-Whitney-Wilcoxon signed rank test compares the ranks of values in two groups. It is the non-parametric equivalent of a t-test. Multiple test corrected p-values are computed as indicators of significance for each variable/feature.

Usage

```
wilcox_test(
  alpha = 0.05,
  mtc = "fdr",
  factor_names,
  paired = FALSE,
  paired_factor = character(0),
  conf_level = 0.95,
  ...
)
```

Arguments

alpha	(numeric) The p-value cutoff for determining significance. The default is 0.05.
mtc	(character) Multiple test correction method. Allowed values are limited to the following: <ul style="list-style-type: none"> • "bonferroni": Bonferroni correction in which the p-values are multiplied by the number of comparisons. • "fdr": Benjamini and Hochberg False Discovery Rate correction. • "none": No correction. The default is "fdr".
factor_names	(character) The name of a sample-meta column to use.
paired	(logical) Apply a paired test. The default is FALSE.
paired_factor	(character) The factor name containing sample ids for paired data. The default is character(0).
conf_level	(numeric) The confidence level of the interval. The default is 0.95.
...	Additional slots and values passed to struct_class.

Value

A wilcox_test object with the following output slots:

statistic	(data.frame) The value of the calculated statistic which is converted to a p-value.
p_value	(data.frame) The probability of observing the calculated t-statistic.
dof	(numeric) The number of degrees of freedom used to calculate the test statistic.
significant	(data.frame) TRUE if the calculated p-value is less than the supplied threshold (alpha).
conf_int	(data.frame) Confidence interval for t statistic.
estimates	(data.frame) The group estimates used when computing the statistic.

struct object

Examples

```
M = wilcox_test(factor_name='Class')
```

Index

ANOVA, [5](#)
as_data_frame, [6](#)
as_data_frame, filter_na_count-method
 (as_data_frame), [6](#)
as_data_frame, ttest-method
 (as_data_frame), [6](#)
as_data_frame, wilcox_test-method
 (as_data_frame), [6](#)
AUC, [7](#)
autoscale, [7](#)

balanced_accuracy, [8](#)
blank_filter, [9](#)
blank_filter_hist, [10](#)
bootstrap, [11](#)

calculate (calculate, AUC-method), [11](#)
calculate, AUC-method, [11](#)
calculate, balanced_accuracy-method
 (calculate, AUC-method), [11](#)
calculate, r_squared-method
 (calculate, AUC-method), [11](#)
chart_plot, [10](#), [17](#), [19](#), [20](#), [23–25](#), [28](#), [30–32](#),
 [39](#), [41](#), [42](#), [46](#), [48](#), [51](#), [54](#), [68](#), [70](#), [72](#),
 [76–78](#), [80](#), [84](#), [86–89](#), [91–93](#), [95](#), [97](#),
 [104](#), [105](#), [107](#), [110](#)
chart_plot
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, blank_filter_hist, blank_filter-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, compare_dist, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, confounders_lsq_barchart, confounders_clsq-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, confounders_lsq_boxplot, confounders_clsq-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, DatasetExperiment_boxplot, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, DatasetExperiment_dist, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, DatasetExperiment_factor_boxplot, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, DatasetExperiment_heatmap, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, dfa_scores_plot, DFA-method, [12](#)
chart_plot, feature_boxplot, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, feature_profile, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, feature_profile, sb_corr-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, feature_profile_array, DatasetExperiment-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, fold_change_plot, fold_change-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, fs_line, forward_selection_by_rank-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, glog_opt_plot, glog_transform-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)
chart_plot, gs_line, grid_search_1d-method
 (chart_plot, dfa_scores_plot, DFA-method), [12](#)

chart_plot,hca_dendrogram,HCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,plsda_regcoeff_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,kfoldxcv_grid,kfold_xval-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,plsda_roc_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,kfoldxcv_metric,kfold_xval-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,plsda_scores_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,kw_p_hist,kw_rank_sum-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,plsda_vip_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,mv_boxplot,DatasetExperiment-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,plsda_vip_summary_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,mv_feature_filter_hist,mv_feature_filter-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,pls_r_cook_dist,PLSR-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,mv_histogram,DatasetExperiment-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,pls_r_prediction_plot,PLSR-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,mv_sample_filter_hist,mv_sample_filter-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,pls_r_qq_plot,PLSR-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_biplot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,pls_r_residual_hist,PLSR-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_correlation_plot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,pqn_norm_hist,pqn_norm-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_dstat_plot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,rsd_filter_hist,rsd_filter-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_loadings_plot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,svm_plot_2d,SVM-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_scores_plot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,tic_chart,DatasetExperiment-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,pca_scree_plot,PCA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,tSNE_scatter,tSNE-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,permutation_test_plot,permutation_test-method (chart_plot,dfa_scores_plot,DFA-method),
 12 chart_plot,wilcox_p_hist,wilcox_test-method (chart_plot,dfa_scores_plot,DFA-method),
 12
 chart_plot,plsda_predicted_plot,PLSDA-method (chart_plot,dfa_scores_plot,DFA-method),
 12 classical_ls, 16
 compare_dist, 17
 confounders_cls, 17

- confounders_lsq_barchart, 19
- confounders_lsq_boxplot, 20
- constant_sum_norm, 20
- corr_coef, 21

- DatasetExperiment_boxplot, 22
- DatasetExperiment_dist, 23
- DatasetExperiment_factor_boxplot, 24
- DatasetExperiment_heatmap, 25
- DFA, 26
- dfa_scores_plot, 26
- dratio_filter, 28

- feature_boxplot, 29
- feature_profile, 30
- feature_profile_array, 31
- filter_by_name, 32
- filter_na_count, 33
- filter_smeta, 34
- fisher_exact, 34
- fold_change, 36
- fold_change_int, 37
- fold_change_plot, 39
- forward_selection_by_rank, 40
- fs_line, 41

- glog_opt_plot, 42
- glog_transform, 43
- grid_search_1d, 44
- gs_line, 45

- HCA, 46
- hca_dendrogram, 47
- HSD, 48
- HSDEM, 49

- kfold_xval, 52
- kfoldxcv_grid, 50
- kfoldxcv_metric, 51
- knn_impute, 53
- kw_p_hist, 54
- kw_rank_sum, 54

- linear_model, 55
- log_transform, 56

- mean_centre, 57
- mean_of_medians, 58
- mixed_effect, 58

- model_apply
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, ANOVA, DatasetExperiment-method, 60
- model_apply, classical_lsq, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, confounders_clsq, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, constant_sum_norm, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, corr_coef, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, filter_smeta, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, fisher_exact, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, fold_change, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, fold_change_int, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, HCA, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, HSD, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, HSDEM, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, knn_impute, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, kw_rank_sum, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, log_transform, DatasetExperiment-method
 - (model_apply, ANOVA, DatasetExperiment-method), 60
- model_apply, mean_of_medians, DatasetExperiment-method

(model_apply,ANOVA,DatasetExperiment-method), 60
 (model_predict,DFA,DatasetExperiment-method), 62
 model_apply,mixed_effect,DatasetExperiment-method (model_apply,ANOVA,DatasetExperiment-method), 60
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,nroot_transform,DatasetExperiment-method (model_predict,dratio_filter,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,pairs_filter,DatasetExperiment-method (model_predict,filter_by_name,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,prop_na,DatasetExperiment-method (model_predict,filter_na_count,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,rsd_filter,DatasetExperiment-method (model_predict,filter_smeta,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,sb_corr,DatasetExperiment-method (model_predict,glog_transform,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,split_data,DatasetExperiment-method (model_predict,linear_model,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,stratified_split,DatasetExperiment-method (model_predict,mean_centre,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,tSNE,DatasetExperiment-method (model_predict,mv_feature_filter,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,ttest,DatasetExperiment-method (model_predict,mv_sample_filter,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,vec_norm,DatasetExperiment-method (model_predict,pareto_scale,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_apply,wilcox_test,DatasetExperiment-method (model_predict,PCA,DatasetExperiment-method) (model_apply,ANOVA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_predict (model_predict,DFA,DatasetExperiment-method), 62
 model_predict,autoscale,DatasetExperiment-method (model_predict,PLSDA,DatasetExperiment-method) (model_predict,DFA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_predict,blank_filter,DatasetExperiment-method (model_predict,PLSR,DatasetExperiment-method) (model_predict,DFA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_predict,constant_sum_norm,DatasetExperiment-method (model_predict,pqn_norm,DatasetExperiment-method) (model_predict,DFA,DatasetExperiment-method), 62
 model_predict,DFA,DatasetExperiment-method, 62
 model_predict,SVM,DatasetExperiment-method (model_predict,DFA,DatasetExperiment-method), 62

62 (model_train,DFA,DatasetExperiment-method),
 model_predict,vec_norm,DatasetExperiment-method 65
 (model_predict,DFA,DatasetExperiment-method),
 62 (model_train,DFA,DatasetExperiment-method),
 model_reverse 65
 (model_reverse,autoscale,DatasetExperiment-method),
 64 (model_train,DFA,DatasetExperiment-method),
 model_reverse,autoscale,DatasetExperiment-method, 65
 64 model_train,PCA,DatasetExperiment-method
 model_reverse,mean_centre,DatasetExperiment-method (model_train,DFA,DatasetExperiment-method),
 (model_reverse,autoscale,DatasetExperiment-method), 65
 64 model_train,PLSDA,DatasetExperiment-method
 model_train (model_train,DFA,DatasetExperiment-method),
 (model_train,DFA,DatasetExperiment-method), 65
 65 model_train,PLSR,DatasetExperiment-method
 model_train,autoscale,DatasetExperiment-method (model_train,DFA,DatasetExperiment-method),
 (model_train,DFA,DatasetExperiment-method), 65
 65 model_train,pqn_norm,DatasetExperiment-method
 model_train,blank_filter,DatasetExperiment-method (model_train,DFA,DatasetExperiment-method),
 (model_train,DFA,DatasetExperiment-method), 65
 65 model_train,SVM,DatasetExperiment-method
 model_train,constant_sum_norm,DatasetExperiment-method (model_train,DFA,DatasetExperiment-method),
 (model_train,DFA,DatasetExperiment-method), 65
 65 model_train,vec_norm,DatasetExperiment-method
 model_train,DFA,DatasetExperiment-method, (model_train,DFA,DatasetExperiment-method),
 65
 model_train,dratio_filter,DatasetExperiment-method MTBLS79_DatasetExperiment, 66
 (model_train,DFA,DatasetExperiment-method), mv_boxplot, 67
 65 mv_feature_filter, 68
 model_train,filter_by_name,DatasetExperiment-method mv_feature_filter_hist, 69
 (model_train,DFA,DatasetExperiment-method), mv_histogram, 70
 65 mv_sample_filter, 71
 model_train,filter_na_count,DatasetExperiment-method mv_sample_filter_hist, 72
 (model_train,DFA,DatasetExperiment-method),
 65 hroot_transform, 72
 model_train,filter_smeta,DatasetExperiment-method ontology_cache, 73
 (model_train,DFA,DatasetExperiment-method),
 65 pairs_filter, 73
 model_train,glog_transform,DatasetExperiment-method paruto_scale, 74
 (model_train,DFA,DatasetExperiment-method),
 65 plog, 74
 model_train,linear_model,DatasetExperiment-method pca_biplot, 75
 (model_train,DFA,DatasetExperiment-method),
 65 pcorrelation_plot, 77
 model_train,mean_centre,DatasetExperiment-method pchiststat_plot, 77
 (model_train,DFA,DatasetExperiment-method),
 65 pca_loadings_plot, 78
 model_train,mv_feature_filter,DatasetExperiment-method pcd_scores_plot, 79
 (model_train,DFA,DatasetExperiment-method),
 65 pcdscreen_plot, 80
 permutation_test, 81
 permutation_test_plot, 81

permute_sample_order, 82
PLSDA, 83
plsda_predicted_plot, 84
plsda_regcoeff_plot, 85
plsda_roc_plot, 86
plsda_scores_plot, 87
plsda_vip_plot, 88
plsda_vip_summary_plot, 89
PLSR, 90
plsr_cook_dist, 91
plsr_prediction_plot, 92
plsr_qq_plot, 92
plsr_residual_hist, 93
pqn_norm, 93
pqn_norm_hist, 95
prop_na, 95

r_squared, 99
rsd_filter, 96
rsd_filter_hist, 97
run
 (run,bootstrap,DatasetExperiment,metric-method),
 98
run,bootstrap,DatasetExperiment,metric-method,
 98
run,forward_selection_by_rank,DatasetExperiment,metric-method
 (run,bootstrap,DatasetExperiment,metric-method),
 98
run,grid_search_1d,DatasetExperiment,metric-method
 (run,bootstrap,DatasetExperiment,metric-method),
 98
run,kfold_xval,DatasetExperiment,metric-method
 (run,bootstrap,DatasetExperiment,metric-method),
 98
run,permutation_test,DatasetExperiment,metric-method
 (run,bootstrap,DatasetExperiment,metric-method),
 98
run,permute_sample_order,DatasetExperiment,metric-method
 (run,bootstrap,DatasetExperiment,metric-method),
 98

sb_corr, 99
split_data, 101
stratified_split, 101
structToolbox, 102
SVM, 102
svm_plot_2d, 104

tic_chart, 105
tsNE, 105
tsNE_scatter, 107
ttest, 108

vec_norm, 109

wilcox_p_hist, 110
wilcox_test, 110