

Package ‘ChIC.data’

April 11, 2023

Title ChIC package data

Version 1.18.0

Maintainer Carmen Maria Livi <carmen.livi@ifom.eu>

Description This package contains annotation and metagene profile data for the ChIC package.

Depends R (>= 3.5), genomeIntervals, randomForest

Imports caret (>= 6.0-78)

biocViews ExperimentData, ENCODE

License GPL-2

Encoding UTF-8

LazyData true

LazyDataCompression bzip2

RoxygenNote 7.1.1

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/ChIC.data>

git_branch RELEASE_3_16

git_last_commit a6b23fe

git_last_commit_date 2022-11-01

Date/Publication 2023-04-11

Author Carmen Maria Livi [aut, cre, dtc],
Endre Sebestyen [aut]

R topics documented:

chipSubset	2
classesDefList	3
compendium_db	3
compendium_db_tf	4
compendium_profiles	4
compendium_profiles_TF	6

dm3_chrom_info	10
dm3_refseq_genes_filtered_granges	10
EM_Results	11
hg19_chrom_info	11
hg19_refseq_genes_filtered_granges	12
hg38_chrom_info	12
hg38_refseq_genes_filtered_granges	13
inputSubset	13
mm10_chrom_info	14
mm10_refseq_genes_filtered_granges	14
mm9_chrom_info	15
mm9_refseq_genes_filtered_granges	15
rf_models	16
Index	17

chipSubset	<i>ChIP-seq bam file stored as spp tag-list for a subset of chromosomes for the chip</i>
------------	--

Description

Example data for manual and vignette. tag-list created with the read.bam.tags() function from spp package. The original bam file has been downloaded from ENCODE (ID: ENCFF000BFX).

Usage

```
data(chipSubset)
```

Format

list of 2 elements containing the reads and the read quality of the ChIP.

- tags : list containing the start coordinates of each read aligned (ChIP) (3'end)
- quality: list containing the read quality of each read

classesDefList	<i>List with definitions</i>
----------------	------------------------------

Description

List containing information about chromatin marks, transcription factors, definitions for broad and sharp class.

Usage

```
data(classesDefList)
```

Format

A list of 5, containing a vector with chromatin mark names, TF names, the members of sharp binding marks, broad binding marks and RNAPol2

- Hlist: vector with chromatin marks
- allSharp: vector with sharp binding marks
- allBroad: vector with broad binding marks
- RNAPol2 : RNAPol2
- TF: vector with TF names

compendium_db	<i>Histone mark compendium</i>
---------------	--------------------------------

Description

Histone mark ChIP-seq compendium for the ChIC package. The compendium contains quality control metrics and metadata for 2204 histone mark samples analysed from ENCODE and Roadmap Epigenomics.

Usage

```
data(compendium_db)
```

Format

Data frame with 251 variables (quality control metrics, metadata) for each analysed sample.

Source

XX

compendium_db_tf	<i>Transcription factor compendium</i>
------------------	--

Description

Transcription factor ChIP-seq compendium for the ChIC package. The compendium contains quality control metrics and metadata for 1350 transcription factors analysed from ENCODE.

Usage

```
data(compendium_db_tf)
```

Format

Data frame with 251 variables (quality control metrics, metadata) for each analysed sample.

Source

XX

compendium_profiles	<i>Metagene profile data for chromatin marks</i>
---------------------	--

Description

Compendium of averaged metagene profiles for the ChIC package. Contains averaged metagene profiles for following ChIP-seq datasets from ENCODE and Roadmap Epigenomics.

Usage

```
data(compendium_profiles)
```

Format

A list of data frames with the coordinates of the metagene profile of the respective chromatin mark.

x : genomic coordinates mean : the mean of the signal intensity in the compendium sd : the standard deviation of the signal intensity in the compendium q1..q5 : being the respective quantile of the value distribution sderr : standard error setSize : setsize analysed

Details

- H2A.Z
- H2AFZ
- H2AK5ac
- H2AK9ac
- H2BK120ac
- H2BK12ac
- H2BK15ac
- H2BK20ac
- H2BK5ac
- H3K14ac
- H3K18ac
- H3K23ac
- H3K23me2
- H3K27ac
- H3K27me3
- H3K36me3
- H3K4ac
- H3K4me1
- H3K4me2
- H3K4me3
- H3K56ac
- H3K79me1
- H3K79me2
- H3K9ac
- H3K9me1
- H3K9me3
- H3T11ph
- H4K12ac
- H4K20me1
- H4K5ac
- H4K8ac
- H4K91ac
- POLR2A
- POLR2AphosphoS2
- POLR2AphosphoS5

Source

XX

compendium_profiles_TF

Metagene profile data for transcription factors

Description

Compendium of averaged metagene profiles for the ChIC package. Contains averaged metagene profiles for following ChIP-seq datasets from ENCODE.

Usage

```
data(compendium_profiles_TF)
```

Format

A list of data frames with the coordinates of the metagene profile of the respective transcription factor.

x : genomic coordinates mean : the mean of the signal intensity in the compendium sd : the standard deviation of the signal intensity in the compendium q1..q5 : being the respective quantile of the value distribution sderr : standard error setSize : setsize analysed

Details

- ARID3A
- ATF2
- ATF3
- BACH1
- BATF
- BCL11A
- BCL3
- BCLAF1
- BHLHE40
- BRCA1
- CBX2
- CBX3
- CEBPB
- CEBPD
- CEBPZ
- CHD1
- CHD2
- CHD4

- CREB1
- CREBBP
- CTCF
- CUX1
- E2F4
- E2F6
- EBF1
- EGR1
- ELF1
- ELK1
- EP300
- ESRRA
- ETS1
- EZH2
- FOSL1
- FOSL2
- FOS
- FOXA1
- FOXA2
- FOXM1
- GABPA
- GATA2
- GATA3
- GTF2F1
- HA
- HDAC2
- HDAC6
- HNF4A
- HNF4G
- IRF3
- IRF4
- JUND
- JUN
- KAT2A
- KAT2B
- KDM1A
- KDM4A

- KDM5A
- KDM5B
- MAFF
- MAFK
- MAX
- MAZ
- MBD4
- MEF2A
- MEF2C
- MTA3
- MXI1
- MYBL2
- MYC
- NANOG
- NCOR1
- NFATC1
- NFIC
- NR2F2
- NR3C1
- NRF1
- PAX5
- PBX3
- PHF8
- PML
- POU2F2
- PRDM1
- RAD21
- RBBP5
- RCOR1
- REST
- RFX5
- RNF2
- RUNX3
- RXRA
- SAP30
- SETDB1
- SIN3A

- SIRT6
- SIX5
- SMC3
- SP1
- SP2
- SP4
- SPI1
- SREBF1
- SREBF2
- SRF
- STAT3
- STAT5A
- SUPT20H
- SUZ12
- TAF1
- TAF7
- TAL1
- TBP
- TCF12
- TCF3
- TEAD4
- USF1
- USF2
- WRNIP1
- YY1
- ZBTB33
- ZBTB7A
- ZC3H11A
- ZEB1
- ZMIZ1
- ZNF143
- ZNF274
- ZNF384

Source

XX

dm3_chrom_info *dm3 chromosome information*

Description

dm3 chromosome information for the ChIC package.

Usage

```
data(dm3_chrom_info)
```

Format

A named list of int vectors with 2 elements, the start and end position of all dm3 chromosomes.

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/dm3/database/chromInfo.txt.gz>

dm3_refseq_genes_filtered_granges
Filtered RefSeq gene annotation as GRanges for dm3

Description

RefSeq gene annotation data for the ChIC package in GRanges format, filtered by the gene length and by overlaps.

Usage

```
data(dm3_refseq_genes_filtered_granges)
```

Format

A GRanges object.

EM_Results	<i>Example results from the qualityScores_EM() function based on the example ChIP-seq data for the Vignette for ChIC package</i>
------------	--

Description

Example data to be used in the vignette for ChIC package

Usage

```
data(EM_Results)
```

Format

list containing EM scores and filtered reads

hg19_chrom_info	<i>hg19 chromosome information</i>
-----------------	------------------------------------

Description

hg19 chromosome information for the ChIC package.

Usage

```
data(hg19_chrom_info)
```

Format

A named list of int vectors with 2 elements, the start and end position of all hg19 chromosomes.

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/hg19/bigZips/hg19.chrom.sizes>

hg19_refseq_genes_filtered_granges

Filtered RefSeq gene annotation as GRanges

Description

RefSeq gene annotation data for the ChIC package in GRanges format, filtered by the gene length and by overlaps.

Usage

```
data(hg19_refseq_genes_filtered_granges)
```

Format

A GRanges object.

hg38_chrom_info

hg38 chromosome information

Description

hg38 chromosome information for the ChIC package.

Usage

```
data(hg38_chrom_info)
```

Format

A named list of int vectors with 2 elements, the start and end position of all hg38 chromosomes.

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/hg38/bigZips/hg38.chrom.sizes>

hg38_refseq_genes_filtered_granges
Filtered RefSeq gene annotation as GRanges

Description

RefSeq gene annotation data for the ChIC package in GRanges format, filtered by the gene length and by overlaps.

Usage

```
data(hg38_refseq_genes_filtered_granges)
```

Format

A GRanges object.

inputSubset	<i>ChIP-seq bam file stored as spp tag-list for a subset of chromosomes for the input</i>
-------------	---

Description

Example data for manual and vignette. Tag-list created with the read.bam.tags() function from spp package for the input data. The original bam file has been downloaded from ENCODE (ID: ENCFF000BDQ).

Usage

```
data(inputSubset)
```

Format

list of 2 elements containing the reads and the read quality of the input.

- tags : list containing the start coordinates of each read aligned (input) (3'end)
- quality: list containing the read quality of each read

mm10_chrom_info *mm10 chromosome information*

Description

mm10 chromosome information for the ChIC package.

Usage

```
data(mm10_chrom_info)
```

Format

A named list of int vectors with 2 elements, the start and end position of all mm10 chromosomes.

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/mm10/bigZips/mm10.chrom.sizes>

mm10_refseq_genes_filtered_granges
Filtered RefSeq gene annotation as GRanges for mm10

Description

RefSeq gene annotation data for the ChIC package in GRanges format, filtered by the gene length and by overlaps.

Usage

```
data(mm10_refseq_genes_filtered_granges)
```

Format

A GRanges object.

mm9_chrom_info	<i>mm9 chromosome information</i>
----------------	-----------------------------------

Description

mm9 chromosome information for the ChIC package.

Usage

```
data(mm9_chrom_info)
```

Format

A named list of int vectors with 2 elements, the start and end position of all mm9 chromosomes.

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/mm9/bigZips/mm9.chrom.sizes>

mm9_refseq_genes_filtered_granges	<i>Filtered RefSeq gene annotation as GRanges for mm9</i>
-----------------------------------	---

Description

RefSeq gene annotation data for the ChIC package in GRanges format, filtered by the gene length and by overlaps.

Usage

```
data(mm9_refseq_genes_filtered_granges)
```

Format

A GRanges object.

rf_models	<i>Random forest models for chromatin marks ChIP-seq experiment classification</i>
-----------	--

Description

Random forest models based on ENCODE and Roadmap data for ChIP-seq experiment classification using the ChIC package.

Usage

```
data(rf_models)
```

Format

A list of 7 random forest models for the different chromatin marks and transcription factors:

- Broad : model for broad binding marks
- H3K9me3 : model for H3K9me3
- H3K27me3 : model for H3K27me3
- H3K36me3 : model for H3K36me3
- RNAPol2 : model for RNAPol2
- Sharp : model for sharp binding marks
- TF : model for transcription factors

Index

- * **EM_Results**
 - EM_Results, 11
- * **Transcription**
 - compendium_profiles_TF, 6
- * **annotation**
 - dm3_refseq_genes_filtered_granges, 10
 - hg19_refseq_genes_filtered_granges, 12
 - hg38_refseq_genes_filtered_granges, 13
 - mm10_refseq_genes_filtered_granges, 14
 - mm9_refseq_genes_filtered_granges, 15
- * **bamfile**
 - chipSubset, 2
 - inputSubset, 13
- * **chromatin**
 - compendium_profiles, 4
- * **classification**
 - rf_models, 16
- * **compendium**
 - compendium_db, 3
 - compendium_db_tf, 4
 - compendium_profiles, 4
 - compendium_profiles_TF, 6
- * **control**
 - compendium_db, 3
 - compendium_db_tf, 4
- * **definitions**
 - classesDefList, 3
- * **dm3**
 - dm3_chrom_info, 10
- * **factors**
 - compendium_profiles_TF, 6
- * **hg19**
 - hg19_chrom_info, 11
- * **hg38**
 - hg38_chrom_info, 12
- * **histone**
 - compendium_db, 3
- * **marks**
 - compendium_db, 3
 - compendium_profiles, 4
- * **metagene**
 - compendium_profiles, 4
 - compendium_profiles_TF, 6
- * **metrics**
 - compendium_db, 3
 - compendium_db_tf, 4
- * **mm10**
 - mm10_chrom_info, 14
- * **mm9**
 - mm9_chrom_info, 15
- * **profiles**
 - compendium_profiles, 4
 - compendium_profiles_TF, 6
- * **quality**
 - compendium_db, 3
 - compendium_db_tf, 4
- * **tf**
 - compendium_db_tf, 4
- chipSubset, 2
- classesDefList, 3
- compendium_db, 3
- compendium_db_tf, 4
- compendium_profiles, 4
- compendium_profiles_TF, 6
- dm3_chrom_info, 10
- dm3_refseq_genes_filtered_granges, 10
- EM_Results, 11
- hg19_chrom_info, 11
- hg19_refseq_genes_filtered_granges, 12
- hg38_chrom_info, 12

hg38_refseq_genes_filtered_granges, [13](#)

inputSubset, [13](#)

mm10_chrom_info, [14](#)

mm10_refseq_genes_filtered_granges, [14](#)

mm9_chrom_info, [15](#)

mm9_refseq_genes_filtered_granges, [15](#)

rf_models, [16](#)