

# Package ‘rRDPData’

April 11, 2023

**Title** Database for the Default RDP Classifier  
**Description** Database used by the default RDP Classifier  
**Version** 1.18.0  
**Date** 2014-08-19  
**Author** Michael Hahsler, Anurag Nagar  
**Maintainer** Michael Hahsler <mhahsler@lyle.smu.edu>  
**biocViews** SequencingData, MicrobiomeData  
**Depends** rRDP  
**SystemRequirements** Java  
**License** GPL-2  
**git\_url** <https://git.bioconductor.org/packages/rRDPData>  
**git\_branch** RELEASE\_3\_16  
**git\_last\_commit** af8b9df  
**git\_last\_commit\_date** 2022-11-01  
**Date/Publication** 2023-04-11

## R topics documented:

16SrRNA . . . . .	1
<b>Index</b>	<b>3</b>

---

16SrRNA	<i>RDP Classifier Model for RDP 16S rRNA Trainingset No 9</i>
---------	---

---

### Description

Model data for the RDP classifier trained with the RDP 16S rRNA Trainingset No 9. This is the default model data used by RDP.

## Details

`rdp()` creates a default classifier using this data set.

The model data is stored in `system.file("16srrna", package="rRDPData")` and consists of several files in proprietary format used by the RDP software. Since RDP is a naive Bayes classifier the data mainly contain conditional word (8-mer) probabilities.

## References

RDP Classifier <http://sourceforge.net/projects/rdp-classifier/>

## Examples

```
### Use the RDP with the default classifier model data
seq <- readRNAStringSet(system.file("examples/RNA_example.fasta",
package="rRDP"))

## shorten names
names(seq) <- sapply(strsplit(names(seq), " "), "[", 1)
seq

## use RDP for classification
pred <- predict(rdp(), seq)
pred

attr(pred, "confidence")
```

# Index

\* **model**

16SrRNA, [1](#)  
16S (16SrRNA), [1](#)  
16SrRNA, [1](#)