

Measurement error model for correlation coefficient estimation

Beiyong Ding
Robert Gentleman

April 25, 2023

Introduction

The `MeasurementError.cor` package fits a two-stage measurement error model for estimating correlation between two random variables under bivariate normality. It's application is perhaps most relevant for the gene expression data where both point and standard estimates are available. We have shown that the proposed measurement error corrected correlation estimate has lower bias compared with the usual sample pearson correlation. For details, refer to Ding and Gentleman (2003) as well as R help pages associated with each function.

The `cor.me.vector` and `cor.me.matrix` functions

The `cor.me.vector` calculates the measurement error model estimate of correlation between two observed vectors whereas `cor.me.matrix` calculates all pairwise measurement error model estimate of correlation in the matrix.

```
> library(MeasurementError.cor)
> exp <- matrix(abs(rnorm(100,1000,20)),ncol=10)
> se <- matrix(abs(rnorm(100,50,5)),ncol=10)
> cor.me.vector(exp[1,],se[1,],exp[2,],se[2,])

$estimate
      corr.me   corr.true      mu1      mu2      s1      s2
0.9786091 -0.8705384 992.3851243 991.0991818 2.6351104 14.5215152
```

```

$counts
function gradient
      104      100

$convergence
[1] 1

> cor.me.matrix(exp,se)

$corr.true
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]
[1,] 1.0000000 -0.8705384 -0.6734336  0.8122606 -0.8854614 -0.7788074
[2,] -0.8705384  1.0000000 -0.6438400  0.7935012  0.9113707  0.8656959
[3,] -0.6734336 -0.6438400  1.0000000 -0.8125620  0.3085164  0.2061967
[4,]  0.8122606  0.7935012 -0.8125620  1.0000000 -0.8171256  0.5790860
[5,] -0.8854614  0.9113707  0.3085164 -0.8171256  1.0000000 -0.8035459
[6,] -0.7788074  0.8656959  0.2061967  0.5790860 -0.8035459  1.0000000
[7,] -0.7172073 -0.7732703  0.6022574  0.7850281  0.5953330  0.7947176
[8,] -0.7872399  0.6852461  0.8877072 -0.7909519  0.8152235  0.7807547
[9,]  0.7719502  0.8196399 -0.5447638  0.8847991  0.9302696 -0.7993205
[10,] -0.7974766 -0.8045137  0.7325499  0.7626254 -0.6990547  0.7765247
      [,7]      [,8]      [,9]      [,10]
[1,] -0.7172073 -0.7872399  0.7719502 -0.7974766
[2,] -0.7732703  0.6852461  0.8196399 -0.8045137
[3,]  0.6022574  0.8877072 -0.5447638  0.7325499
[4,]  0.7850281 -0.7909519  0.8847991  0.7626254
[5,]  0.5953330  0.8152235  0.9302696 -0.6990547
[6,]  0.7947176  0.7807547 -0.7993205  0.7765247
[7,]  1.0000000  0.5331547 -0.7720564  0.8054266
[8,]  0.5331547  1.0000000  0.3823405  0.7148907
[9,] -0.7720564  0.3823405  1.0000000 -0.7946079
[10,]  0.8054266  0.7148907 -0.7946079  1.0000000

>

```

the quantity of interest, i.e. the model estimate of the correlation between the true value of two random variables whereas `cor.me` is the model estimate of correlation between the measurement errors of the two random variables. The second quantity may not be of interest. `mu1,mu2` and `s1, s2` are the estimated mean and standard deviation of the two random variables.

`cor.me.matrix` only returns the estimated correlation matrix.

References

Beiying Ding and Robert Gentleman. Measurement error model for correlation coefficient estimation and its application in microarray analysis. 2003.