

# Package ‘webbioc’

August 26, 2024

**Version** 1.76.0

**Date** 2009-02-05

**Title** Bioconductor Web Interface

**Author** Colin A. Smith <colin@colinsmith.org>

**Maintainer** Colin A. Smith <colin@colinsmith.org>

**Depends** R (>= 1.8.0), Biobase, affy, multtest, annaffy, vsn, gcrma, qvalue

**Imports** multtest, qvalue, stats, utils, BiocManager

**SystemRequirements** Unix, Perl (>= 5.6.0), Netpbm

**Description** An integrated web interface for doing microarray analysis using several of the Bioconductor packages. It is intended to be deployed as a centralized bioinformatics resource for use by many users. (Currently only Affymetrix oligonucleotide analysis is supported.)

**License** GPL (>= 2)

**URL** <http://www.bioconductor.org/>

**LazyLoad** yes

**biocViews** Infrastructure, Microarray, OneChannel, DifferentialExpression

**git\_url** <https://git.bioconductor.org/packages/webbioc>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 0dc07a7

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-08-25

## Contents

installReps . . . . .	2
mt.wrapper . . . . .	2

---

installReps	<i>Install all repository packages</i>
-------------	--

---

**Description**

Using reposTools, install/update all packages from given repositories.

**Usage**

```
installReps(repNames = "aData", lib = .libPaths()[1],
            type = getOption("pkgType"))
```

**Arguments**

repNames	A character vector containing repository names. A listing of known repository names can be found with the getReposOption() function.
lib	A path to install/update the packages. If this directory does not exist, it will be created (if possible).
type	type of package do download

**Author(s)**

Colin A. Smith <webbioc@colinsmith.org>

---

mt.wrapper	<i>Multiple Testing Wrapper Function</i>
------------	--

---

**Description**

A wrapper for some of the functionality for the multtest package. It also includes hooks to calculate q-values with John D. Storey's 'q-value.R' code.

**Usage**

```
mt.wrapper(proc, X, classlabel, test="t", rawpcalc="Parametric", side="abs", ...)
```

**Arguments**

proc	A character string containing the name of the multiple testing procedure for which adjusted $p$ -values are to be computed. This vector should include any of the following: "Bonferroni", "Holm", "Hochberg", "SidakSS", "SidakSD", "BH", "BY", "maxT", "minP", "q".
X	A data frame or matrix, with $m$ rows corresponding to variables (hypotheses) and $n$ columns to observations. In the case of gene expression data, rows correspond to genes and columns to mRNA samples. The data can be read using <a href="#">read.table</a> .
classlabel	A vector of integers corresponding to observation (column) class labels. For $k$ classes, the labels must be integers between 0 and $k - 1$ . For the blockf test option, observations may be divided into $n/k$ blocks of $k$ observations each. The observations are ordered by block, and within each block, they are labeled using the integers 0 to $k - 1$ .
test	A character string specifying the statistic to be used to test the null hypothesis of no association between the variables and the class labels. If test="t", the tests are based on two-sample Welch t-statistics (unequal variances). If test="t.equalvar", the tests are based on two-sample t-statistics with equal variance for the two samples. The square of the t-statistic is equal to an F-statistic for $k = 2$ . If test="wilcoxon", the tests are based on standardized rank sum Wilcoxon statistics. If test="f", the tests are based on F-statistics. If test="pairt", the tests are based on paired t-statistics. The square of the paired t-statistic is equal to a block F-statistic for $k = 2$ . If test="blockf", the tests are based on F-statistics which adjust for block differences (cf. two-way analysis of variance).
rawpvalc	A character string specifying how to calculate nominal/raw p-values. The possible choices are "Parametric" or "Permutation".
side	A character string specifying the type of rejection region. If side="abs", two-tailed tests, the null hypothesis is rejected for large absolute values of the test statistic. If side="upper", one-tailed tests, the null hypothesis is rejected for large values of the test statistic. If side="lower", one-tailed tests, the null hypothesis is rejected for small values of the test statistic.
...	Further arguments for mt.maxT, mt.minP, qvalue.

**Value**

A data frame with components

index	Vector of row indices, between 1 and nrow(X), where rows are sorted first according to their adjusted $p$ -values, next their unadjusted $p$ -values, and finally their test statistics.
-------	--

<code>teststat</code>	Vector of test statistics, ordered according to <code>index</code> . To get the test statistics in the original data order, use <code>teststat[order(index)]</code> .
<code>rawp</code>	Vector of raw (unadjusted) $p$ -values, ordered according to <code>index</code> .
<code>adjp</code>	Vector of adjusted $p$ -values, ordered according to <code>index</code> .
<code>plower</code>	For <code>mt.minP</code> function only, vector of "adjusted $p$ -values", where ties in the permutation distribution of the successive minima of raw $p$ -values with the observed $p$ -values are counted only once. Note that procedures based on <code>plower</code> do not control the FWER. Comparison of <code>plower</code> and <code>adjp</code> gives an idea of the discreteness of the permutation distribution. Values in <code>plower</code> are ordered according to <code>index</code> .

**Author(s)**

Colin A. Smith <webbioc@colinsmith.org>

# Index

\* **file**

installReps, 2

mt.wrapper, 2

installReps, 2

mt.minP, 4

mt.wrapper, 2

read.table, 3