

Basic GO Usage

R. Gentleman

October 13, 2015

Introduction

In this vignette we describe some of the basic characteristics of the data available from the Gene Ontology (GO), (The Gene Ontology Consortium, 2000) and how these data have been incorporated into Bioconductor. We assume that readers are familiar with the basic DAG structure of GO and with the mappings of genes to GO terms that are provide by GOA (Camon et al., 2004). We consider these basic structures and properties quite briefly.

GO, itself, is a structured terminology. The ontology describes genes and gene products and is divided into three separate ontologies. One for cellular component (CC), one for molecular function (MF) and one for biological process (BP). We maintain those same distinctions were appropriate. The relationship between terms is a parent-child one, where the parents of any term are less specific than the child. The mapping in either direction can be one to many (so a child may have many parents and a parent may have many children). There is a single root node for all ontologies as well as separate root nodes for each of the three ontologies named above. These terms are structured as a directed acyclic graph (or a DAG).

GO itself is only the collection of terms; the descriptions of genes, gene products, what they do, where they do it and so on. But there is no direct association of genes to terms. The assignment of genes to terms is carried out by others, in particular the GOA project (Camon et al., 2004). It is this assignment that makes GO useful for data analysis and hence it is the combined relationship between the structure of the terms and the assignment of genes to terms that is the concern of the *GO.db* package.

The basis for child-parent relationships in GO can be either an *is-a* relationship, where the child term is a more specific version of the parent. Or, it can be a *has-a*, or *part-of* relationship where the child is a part of the parent. For example a telomere is a part-of a chromosome.

Genes are assigned to terms on the basis of their LocusLink ID. For this reason we make most of our mappings and functions work for LocusLink identifiers. Users of specific chips, or data with other gene identifiers should first map their identifiers to LocusLink before using *GOstats*.

A gene is mapped only to the most specific terms that are applicable to it (in each ontology). Then, all less specific terms are also applicable and they are easily obtained by traversing the set of parent relationships down to the root node. In practice many of these mappings are precomputed and easily obtained from the different hash tables provided by the *GO.db* package.

Mapping of a gene to a term can be based on many different things. GO and GOA provide an extensive set of evidence codes, some of which are given in Table 1, but readers are referred to the GO web site and the documentation for the *GO.db* package for a more comprehensive listing. Clearly for some investigations one will want to exclude genes that were mapped according to some of the evidence codes.

IMP	inferred from mutant phenotype
IGI	inferred from genetic interaction
IPI	inferred from physical interaction
ISS	inferred from sequence similarity
IDA	inferred from direct assay
IEP	inferred from expression pattern
IEA	inferred from electronic annotation
TAS	traceable author statement
NAS	non-traceable author statement
ND	no biological data available
IC	inferred by curator

Table 1: GO Evidence Codes

In some sense TAS is probably the most reliable of the mappings. IEA is a weak association and is based on electronic information, no human curator has examined or confirmed this association. As we shall see later, IEA is also the most common evidence code.

The sets of mappings of interest are roughly divided into three parts. First there is the basic description of the terms etc., these are provided in the **GOTERMS** hash table. Each element of this hash table is named using its GO identifier (these are all of the form **GO:** followed by seven digits). Each element is an instance of the **GOTerms** class. A complete description of this class can be obtained from the appropriate manual page (use `class?GOTerms`). From these data we can find the text string describing the term, which ontology it is in as well as some other basic information.

There are also a set of hash tables that contain the information about parents and children. They are provided as hash tables (the **XX** in the names below should be substituted for one of **BP**, **MF**, or **CC**).

- **GOXXPARENTS**: the parents of the term
- **GOXXANCESTOR**: the parents, and all their parents and so on.

- GOXXCHILDREN: the children of the term
- GOXXOFFSPRING: the children, their children and so on out to the leaves of the GO graph.

For the GOXXPARENTS mappings (only) information about the nature of the relationship is included.

```
> GOTERM$"GO:0003700"
```

```
GOID: GO:0003700
```

```
Term: transcription factor activity, sequence-specific DNA binding
```

```
Ontology: MF
```

```
Definition: Interacting selectively and non-covalently with a specific
             DNA sequence in order to modulate transcription. The transcription
             factor may or may not also interact selectively with a protein or
             macromolecular complex.
```

```
Synonym: sequence-specific DNA binding transcription factor activity
```

```
Synonym: transcription factor activity
```

```
Synonym: GO:0000130
```

```
Secondary: GO:0000130
```

```
> GOMFPARENTS$"GO:0003700"
```

```
is_a
"GO:0001071"
```

```
> GOMFCHILDREN$"GO:0003700"
```

```
is_a      is_a      is_a      is_a      is_a      is_a
"GO:0000981" "GO:0001010" "GO:0001011" "GO:0001034" "GO:0001073" "GO:0001130"
is_a      is_a      is_a      is_a
"GO:0001142" "GO:0001167" "GO:0001199" "GO:0098531"
```

```
>
```

Here we see that the term GO:0003700 has two parents, that the relationships are `is-a` and that it has one child. One can then follow this chains of relationships or use the `ANCESTOR` and `OFFSPRING` hash tables to get more information.

The mappings of genes to GO terms is not contained in the `GO` package. Rather these mappings are held in each of the chip and organism specific data packages, such as `hgu95av2GO` and `org.Hs.egGO` are contained within packages `hgu95av2.db` and `org.Hs.eg.db` respectively. These mappings are from a Entrez Gene ID to the most specific applicable GO terms. Each such entry is a list of lists where the innermost list has these names:

- **GOID:** the GO identifier
- **Evidence:** the evidence code for the assignment
- **Ontology:** the ontology the GO identifier belongs to (one of BP, MF, or CC).

Some genes are mapped to a GO identifier based on two or more evidence codes. Currently these appear as separate entries. So you may want to remove duplicate entries if you are not interested in evidence codes. However, as more sophisticated use is made of these data it will be important to be able to separate out mappings according to specific evidence codes.

In this next example we consider the gene with Entrez Gene ID 4121, this corresponds to Affymetrix ID 39613_at.

```
> l11 = hgu95av2GO[["39613_at"]]
> length(l11)

[1] 16

> sapply(l11, function(x) x$Ontology)

GO:0006491 GO:0018279 GO:0043687 GO:0044267 GO:0000139 GO:0000139 GO:0005737
      "BP"      "BP"      "BP"      "BP"      "CC"      "CC"      "CC"
GO:0005783 GO:0005793 GO:0005794 GO:0016020 GO:0016021 GO:0070062 GO:0004571
      "CC"      "CC"      "CC"      "CC"      "CC"      "CC"      "MF"
GO:0005509 GO:0015923
      "MF"      "MF"

>
```

We see that there are 16 different mappings. We can get only those mappings for the BP ontology by using `getOntology`. We can get the evidence codes using `getEvidence` and we can drop those codes we do not wish to use by using `dropECode`.

```
> getOntology(l11, "BP")

[1] "GO:0006491" "GO:0018279" "GO:0043687" "GO:0044267"

> getEvidence(l11)

GO:0006491 GO:0018279 GO:0043687 GO:0044267 GO:0000139 GO:0000139 GO:0005737
      "IBA"      "TAS"      "TAS"      "TAS"      "IBA"      "TAS"      "IDA"
GO:0005783 GO:0005793 GO:0005794 GO:0016020 GO:0016021 GO:0070062 GO:0004571
      "TAS"      "IDA"      "IDA"      "IDA"      "IEA"      "IDA"      "IEA"
GO:0005509 GO:0015923
      "IEA"      "TAS"
```

```

> zz = dropECode(111)
> getEvidence(zz)

GO:0006491 GO:0018279 GO:0043687 GO:0044267 GO:0000139 GO:0000139 GO:0005737
      "IBA"      "TAS"      "TAS"      "TAS"      "IBA"      "TAS"      "IDA"
GO:0005783 GO:0005793 GO:0005794 GO:0016020 GO:0070062 GO:0015923
      "TAS"      "IDA"      "IDA"      "IDA"      "IDA"      "TAS"

>

```

A Basic Description of GO

We now characterize GO and some of its properties. First we list some of the specific GO IDs that might be of interest (please feel free to propose even more).

- GO:0003673 is the GO root.
- GO:0003674 is the MF root.
- GO:0005575 is the CC root.
- GO:0008150 is the BP root.
- GO:0000004 is biological process unknown
- GO:0005554 is molecular function unknown
- GO:0008372 is cellular component unknown

We can find out how many terms are in each of the different ontologies by:

```

> zz = Ontology(GOTERM)
> table(unlist(zz))

      BP      CC      MF universal
28007    3827    9955           1

>

```

Or we can ask about the number of is-a and partof relationships in each of the three different ontologies.

```

> BPisa = eapply(GOBPPARENTS, function(x) names(x))
> table(unlist(BPisa))

```

	is_a negatively_regulates	part_of
	53959	2600
positively_regulates	regulates	5733
	2587	3024

```
> MFisa = eapply(GOMFPARENTS, function(x) names(x))
> table(unlist(MFisa))
```

is_a	part_of
12142	11

```
> CCisa = eapply(GOCCPARENTS, function(x) names(x))
> table(unlist(CCisa))
```

is_a	part_of
5518	1678

```
>
```

Working with GO

Finding terms that have specific character strings in them is easily accomplished using `grep`. In the next example we first convert the data from `GOTERM` into a character vector to make it easier to do multiple searches.

```
> goterms = unlist(Term(GOTERM))
> whmf = grep("fertilization", goterms)
```

So we see that there are 11 terms with the string “fertilization” in them in the ontology. They can be accessed by subsetting the `goterms` object.

```
> goterms[whmf]
```

	GO:0007338
"single fertilization"	
	GO:0009566
"fertilization"	
	GO:0009567
"double fertilization forming a zygote and endosperm"	
	GO:0009677
"double fertilization forming two zygotes"	
	GO:0035042
"fertilization, exchange of chromosomal proteins"	

```

GO:0045729
"respiratory burst at fertilization"
GO:0060387
"fertilization envelope"
GO:0060467
"negative regulation of fertilization"
GO:0080154
"regulation of fertilization"
GO:0080155
"regulation of double fertilization forming a zygote and endosperm"
GO:0080173
"male-female gamete recognition during double fertilization"
>

```

Working with chip specific meta-data

In some cases users will want to restrict their attention to the set of terms etc that map to genes that were assayed in the experiments that they are working with. To do this you should first get the appropriate chip specific meta-data file. Here we demonstrate some of the examples on the Affymetrix HGu95av2 chips and so use the package *hgu95av2.db*. Each of these packages has a data environment whose name is the base-name of the package with a **GO** suffix, so in this case **hgu95av2GO**. Note that if there are many manufacturer ids that map to the same Entrez Gene identifier then these will be duplicate entries (with different keys).

We can get all the MF terms for our Affymetrix data.

```

> affyGO = eapply(hgu95av2GO, getOntology)
> table(sapply(affyGO, length))

```

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1852	1411	1856	1993	1463	1150	829	596	388	286	224	133	115	87	59	29
16	17	18	19	20	21	22	23	26	28	32	33				
35	38	28	12	7	4	9	4	3	9	2	3				

```

>

```

How many of these probes have multiple GO terms associated with them? What do we do if we want to compare two genes that have multiple GO terms associated with them?

What about evidence codes? To find these we apply a similar function to the **affyGO** terms.

```

> affyEv = eapply(hgu95av2GO, getEvidence)
> table(unlist(affyEv, use.names=FALSE))

  EXP   IBA    IC   IDA   IEA   IEP   IGI   IMP   IPI   ISS   NAS    ND   TAS
247 12683  1244 56108 69437  1165  1052 14542 12052 18603  6603   793 54091

>

> test1 = eapply(hgu95av2GO, dropECode, c("IEA", "NR"))
> table(unlist(sapply(test1, getEvidence),
+             use.names=FALSE))

  EXP   IBA    IC   IDA   IEP   IGI   IMP   IPI   ISS   NAS    ND   TAS
247 12683  1244 56108  1165  1052 14542 12052 18603  6603   793 54091

```

These functions make is somewhat straightforward to select subsets of the GO terms that are specific to different evidence codes.

References

E. Camon, M. Magrane, D. Barrell, V. Lee, E. Dimmer, D. Binns J. Maslen, N. Harte, R. Lopez, and R. Apweiler. The Gene Ontology annotation (GOA) database: sharing knowledge in Uniprot with Gene Ontology. *Nucleic Acids Research*, 32:D262–D266, 2004.

The Gene Ontology Consortium. Gene Ontology: tool for the unification of biology. *Nature Genetics*, 25:25–29, 2000.