

Package ‘spikeLI’

November 22, 2024

Type Package

Title Affymetrix Spike-in Langmuir Isotherm Data Analysis Tool

Version 2.67.0

Date 2009-04-03

Author Delphine Baillon, Paul Leclercq <paulleclercq@hotmail.com>, Sarah Ternisien,
Thomas Heim, Enrico Carlon <enrico.carlon@fys.kuleuven.be>

Maintainer Enrico Carlon <enrico.carlon@fys.kuleuven.be>

Description SpikeLI is a package that performs the analysis of the Affymetrix spike-in data using the Langmuir Isotherm. The aim of this package is to show the advantages of a physical-chemistry based analysis of the Affymetrix microarray data compared to the traditional methods. The spike-in (or Latin square) data for the HGU95 and HGU133 chipsets have been downloaded from the Affymetrix web site. The model used in the spikeLI package is described in details in E. Carlon and T. Heim, Physica A 362, 433 (2006).

Imports graphics, grDevices, stats, utils

License GPL-2

biocViews Microarray, QualityControl

git_url <https://git.bioconductor.org/packages/spikeLI>

git_branch devel

git_last_commit 443a12f

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-11-21

Contents

| | |
|---------------------------|---|
| spikeLI-package | 2 |
| collapse | 3 |
| conc133 | 4 |
| conc95 | 4 |
| hgu | 5 |
| Ivsc | 6 |

| | |
|----------------------|----|
| IvsDG | 7 |
| SPIKE_IN | 8 |
| SPIKE_IN95 | 9 |
| SPIKE_INA | 10 |
| SPIKE_INB | 11 |
| SPIKE_INH | 12 |

| | |
|--------------|-----------|
| Index | 13 |
|--------------|-----------|

| | |
|-----------------|--|
| spikeLI-package | <i>Analysis of Affymetrix spike-in data (HGU95 and HGU133 Latin square) using the Langmuir Isotherm.</i> |
|-----------------|--|

Description

spikeLI performs a series of analysis of Affymetrix spike-in data using inputs from physical-chemistry. It illustrates the advantages of such approach in determining expression levels and in identifying outliers compared to other methods. The analysis so far is restricted to spike-in genes. It will be extended to a generic CEL file. spikeLI does not require affy (and it is independent of any other bioconductor packages) as it reads spike-in data from a data frame variable hgu which is contained in the package.

Details

| | |
|----------|--------------------|
| Package: | spikeLI |
| Type: | Package |
| Version: | 1.0 |
| Date: | 2006-05-05 |
| License: | GNU Public License |

The package contains three basic functions: - IvsC plot intensities as function of spike-in concentration for a fixed probe. - IvsDG plot intensities as function of affinity for a given probe set at fixed concentration. - collapse plot of intensities both as a function of concentration and affinities.

Author(s)

Delphine Baillon, Paul Leclercq, Sarah Ternisien, Thomas Heim and Enrico Carlon
 Maintainer: Enrico Carlon <enrico.carlon@polytech-lille.fr>

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[collapse](#), [IvsC](#), [IvsDG](#), [hgu](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#), [SPIKE_IN95](#)

collapse

Data collapse of all concentrations into a single graph

Description

This function takes as input one or more (up to four) probe sets of the Latin square spike-in data and produces collapse plots. A collapse plot contains data of different concentrations into a single graph. The user can compare in how far the data follows the predicted Langmuir behavior which is also given in the plot. Two models are compared: the basic Langmuir Isotherm and the Langmuir Isotherm with hybridization in solution.

Usage

```
collapse(probe_set, param = "NULL", probes = "NULL", output = "NULL", filename = "NULL")
```

Arguments

| | |
|-----------|--|
| probe_set | This has to take the value of a probe set |
| param | In input one or more probe sets can be given |
| probes | A vector containing the probes |
| output | "PS" output on a postscript file |
| filename | the file in which collapses are given |

Author(s)

Delphine Baillon, Paul Leclercq, Sarah Ternisien, Thomas Heim and Enrico Carlon

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [hgu](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
## You may display the matched intensities of a Probe-Set according to the Delta-G value
collapse("1091_at")

## You may restrict the value to the Perfect match or mis-matches
collapse("1091_at", "PM")

## You may restrict the values displayed for only a number of probes
collapse("1091_at", probes=c(1,9))

## You may output the graphs to a postscript file
```

```
collapse("1091_at",output="PS",filename="outfile.ps")

## You may display up to 4 probe-sets in the same window
collapse(c("1091_at","37777_at",SPIKE_INA[1:2]))

## You can also use the values of the probe-sets contained in one of the Vectors of Human, Bacteria,
## or Artificial Probe-sets
collapse(SPIKE_INH)
```

conc133

Concentration 95

Description

This datasets contains the values of the latine square matrix for the hgu133 Affymetrix Microarrays

Usage

```
data(conc133)
```

Format

The format is: num [1:14] 0 0.125 0.25 0.5 1 2 4 8 16 32 ...

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
data(conc133)
```

conc95

Concentration 95

Description

This datasets contains the values of the latine square matrix for the hgu95 Affymetrix Microarrays

Usage

```
data(conc95)
```

Format

The format is: num [1:14] 0 0.25 0.5 1 2 4 8 16 32 64 ...

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
data(conc95)
```

| | |
|-----|--------------------------------|
| hgu | <i>Selected Probe Set data</i> |
|-----|--------------------------------|

Description

This selected probe sets information contains the sequence of the selected probe sets, as well as the match and mismatch information and Delta G value required for the langmuir analysis

Usage

```
data(hgu)
```

Format

A data frame with 11452 observations on the following 9 variables.

Probe.Set.Name Name of probe set

conc a numeric vector

Ipm a numeric vector

Imm a numeric vector

Seq DNA Sequence of the probe

DGpm DG value of perfect match of the probe

DGmm Delta G value of the mismatch of the probe

DGRNA Delta G value of the RNA

FILE a factor with levels HGU133 HGU95

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
data(hgu)
## maybe str(hgu) ; plot(hgu) ...
```

Ivsc

Plot of intensity vs. concentration for given probes

Description

The function Ivsc plots intensity as a function of a concentration for a given probe in the spike-in Latin square experiments. It also performs a non-linear data fit (using the package nls in the R-package stats) of the experimental data using the Langmuir Isotherm: $I = I_0 + Ac/(K+c)$ Solid and dashed lines are best fits according to this formula. Imax in the plot are given by $I_{max}=I_0+A$, ie the asymptotic intensity in the limit of c to infinity.

Usage

```
Ivsc(probe_set, probe = "NULL", outfile = "NULL")
```

Arguments

| | |
|-----------|---|
| probe_set | Probe set number of the probe set analyzed |
| probe | Integer giving the probe number (if not give the probe 1 is selected) |
| outfile | output the plotted data to a postscript file |

Warning

Some probes have an irregular behavior and the non-linear square fit does not converge.

Author(s)

Delphine Baillon, Paul Leclercq, Sarah Ternisien, Thomas Heim and Enrico Carlon
Maintainer: Enrico Carlon <enrico.carlon@iemn.univ-lille1.fr>

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[collapse](#), [IvsDG](#), [hgu](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
Ivsc("3777_at",4)
```

| | |
|-------|---|
| IvsDG | <i>Plot Intensity as function of the affinity for a given probe set at fixed concentration.</i> |
|-------|---|

Description

IvsDG plots intensity vs affinity (or free energy) for a probe set at a given concentration. The outcome is compared with the prediction from the Langmuir isotherm at that concentration. Two graphs are shown: on the left intensity vs. probe number for PM (blue) and MM (red); on the right the same value plotted as function of the affinities. The black line is the Langmuir Isotherm at the given concentration. The two green lines correspond to concentrations fourfold higher and lower compared to the given one.

Usage

```
IvsDG(probe_set, conc, outfile = "NULL")
```

Arguments

| | |
|-----------|--|
| probe_set | Probe set number of the probe set analyzed |
| conc | Concentration value |
| outfile | "PS" output on a postscript file |

Author(s)

Delphine Baillon, Paul Leclercq, Sarah Ternisien, Thomas Heim and Enrico Carlon

Maintainer: Enrico Carlon <enrico.carlon@iemn.univ-lille1.fr>

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [collapse](#), [hgu](#), [SPIKE_IN](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
data(hgu)
IvsDG("1024_at", 64)
```

SPIKE_IN

Spike-in Probe-Set Names

Description

This dataset contains the names of the Probe-Sets contained in the HGU dataset

Usage

```
data(SPIKE_IN)
```

Format

A string containing the name of the genes

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [hgu](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#), [SPIKE_IN95](#)

Examples

```
## you can first check if the data matches the predicted hybridisation value according to the langmuir
## value, from the intensity versus the concentration value
Ivsc(SPIKE_IN[3])

## you can then plot the value of the Intensity of the probe with the predicted value of the hybridisation
## according to the Delta G, value
IvsDG(SPIKE_IN[5],64)

## The collapse function will finally plot all the values of the probe set according to
## the langmuir absorption theory

collapse(SPIKE_IN[2])

## By comparing the matched value and the mismatches, you will be able to identify errors which
## could have done while sampling the data, or if the error happens repeatedly this will show errors
## which will have happened while sequencing old data.
```

SPIKE_IN95

set of spike-in genes contained in the HGU95 dataset

Description

This dataset contains a set of gene names contained in the HGU95 dataset

Usage

```
data(SPIKE_IN95)
```

Format

The set of spike-in gene names contained in the HGU dataset

Source

This data is experimental data extracted from the publicly available HGU dataset

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [hgu](#), [SPIKE_INA](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
## you can first check if the data matches the predicted hybridisation value according to the langmuir
## value, from the intensity versus the concentration value
Ivsc(SPIKE_IN95[1])

## you can then plot the value of the Intensity of the probe with the predicted value of the hybridisation
## according to the Delta G, value
IvsDG(SPIKE_IN95[4],128)

## The collapse function will finally plot all the values of the probe set according to
## the langmuir absorption theory

collapse(SPIKE_IN95[2])

## By comparing the matched value and the mismatches, you will be able to identify errors which
## could have done while sampling the data, or if the error happens repeatedly this will show errors
## which will have happened while sequencing old data.
```

SPIKE_INA

Artificial Spike-in probesets

Description

This dataset contains the names of the probesets contained in the hgu dataset

Usage

```
data(SPIKE_INA)
```

Format

This dataset contains a set of String containing the names of the Artificial genes contained in the HGU dataset

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [hgu](#), [SPIKE_INB](#), [SPIKE_INH](#)

Examples

```
## you can first check if the data matches the predicted hybridisation value according to the langmuir
## value, from the intensity versus the concentration value
Ivsc(SPIKE_INA[1])

## you can then plot the value of the Intensity of the probe with the predicted value of the hybridisation
## according to the Delta G, value
IvsDG(SPIKE_INA[4],128)

## The collapse function will finally plot all the values of the probe set according to
## the langmuir absorption theory

collapse(SPIKE_INA[2])

## By comparing the matched value and the mismatches, you will be able to identify errors which
## could have done while sampling the data, or if the error happens repeatedly this will show errors
## which will have happened while sequencing old data.
```

SPIKE_INB

Bacteria Spike-in probeset names

Description

This dataset contains the names of the Bacteria probe-sets contained in the HGU dataset

Usage

```
data(SPIKE_INB)
```

Format

names of the Bacteria probe-sets contained in the HGU dataset

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [hgu](#), [SPIKE_INA](#), [SPIKE_INH](#)

Examples

```
## you can first check if the data matches the predicted hybridisation value according to the langmuir
## value, from the intensity versus the concentration value
Ivsc(SPIKE_INB[3])

## you can then plot the value of the Intensity of the probe with the predicted value of the hybridisation
## according to the Delta G, value
IvsDG(SPIKE_INB[4],64)

## The collapse function will finally plot all the values of the probe set according to
## the langmuir absorption theory

collapse(SPIKE_INB[2])

## By comparing the matched value and the mismatches, you will be able to identify errors which
## could have done while sampling the data, or if the error happens repeatedly this will show errors
## which will have happened while sequencing old data.
```

SPIKE_INH

Human Spike-in probe-set names

Description

This dataset contains the names of the Human probe-sets contained in the HGU dataset

Usage

```
data(SPIKE_INH)
```

Format

names of the human probe-sets contained in the HGU dataset

References

E. Carlon and T. Heim, Physica A 362, 433 (2006).

See Also

[Ivsc](#), [IvsDG](#), [collapse](#), [SPIKE_IN](#), [hgu](#), [SPIKE_INA](#), [SPIKE_INB](#)

Examples

```
## you can first check if the data matches the predicted hybridisation value according to the langmuir
## value, from the intensity versus the concentration value
Ivsc(SPIKE_INH[3])

## you can then plot the value of the Intensity of the probe with the predicted value of the hybridisation
## according to the Delta G, value
IvsDG(SPIKE_INH[5],256)

## The collapse function will finally plot all the values of the probe set according to
## the langmuir absorption theory

collapse(SPIKE_INH[2])

## By comparing the matched value and the mismatches, you will be able to identify errors which
## could have done while sampling the data, or if the error happens repeatedly this will show errors
## which will have happened while sequencing old data.
```

Index

* datasets

- conc133, 4
- conc95, 4
- hgu, 5
- SPIKE_IN, 8
- SPIKE_IN95, 9
- SPIKE_INA, 10
- SPIKE_INB, 11
- SPIKE_INH, 12

* data

- collapse, 3
- Ivsc, 6
- IvsDG, 7

* models

- collapse, 3
- Ivsc, 6
- IvsDG, 7
- spikeLI-package, 2

* package

- spikeLI-package, 2

collapse, 2, 3, 4–12

conc133, 4

conc95, 4

hgu, 2, 3, 5, 6–12

Ivsc, 2–5, 6, 7–12

IvsDG, 2–6, 7, 8–12

SPIKE_IN, 2–7, 8, 9–12

SPIKE_IN95, 2, 8, 9

SPIKE_INA, 2–9, 10, 11, 12

SPIKE_INB, 2–10, 11, 12

SPIKE_INH, 2–11, 12

spikeLI (spikeLI-package), 2

spikeLI-package, 2