

# Comprehensive Pipeline for Analyzing and Visualizing Array-Based CGH Data

Frederic Commo \*

Inserm U981, Bioinformatics Group, Gustave Roussy, France

May 15, 2016

## 1 Introduction

---

Genomic profiling using array-based comparative genomic hybridization (aCGH) is widely used within precision medicine programs, in combination with DNA sequencing, to match specific molecular alterations (amplifications or deletions) with therapeutic orientations.

We present *rCGH*, a comprehensive array-based CGH analysis workflow, integrating functionalities specifically designed for precision medicine. *rCGH* ensures a full traceability by saving all the process parameters, and facilitates genomic profiles interpretation and decision-making through interactive visualizations.

*rCGH* supports commercial arrays : Agilent (from 44K to 400K arrays), and Affymetrix SNP6.0 and cytoScanHD. Custom arrays can also be supported, provided a suitable data format is passed. See [subsection 4.1](#) for details.

## 2 Quick start

---

A typical workflow is of the form:

```
> cgh <- readAffyCytoScan("path/to/cytoScan.CNCHP.txt")
> cgh <- adjustSignal(cgh)
> cgh <- EMnormalize(cgh)
> cgh <- segmentCGH(cgh)
```

Then, the genomic profile can be visualized or stored as any R object. The segmentation table can be extracted, then transformed into a by-gene table, or used for any further analysis. All these functions and features are detailed in the next sections.

---

\*frederic.commo@gustaveroussy.fr

### 3 rCGH object structure

---

In order to store (or update) data, sample information, and the workflow parameters all along a genomic profile analysis process, rCGH objects are structured as follow:

- info: the sample information.
- cnSet: the full by-probe dataset.
- param: the workflow parameters, for traceability.
- segTable: the segmentation data.

All these slots are accessible through specific functions, as described in the next sections.

Notice that *rCGH* is a superclass designed for calling common methods. Depending on the type of array and the *read* functions used, the resulting objects will be assigned to classes *rCGH-Agilent*, *rCGH-SNP6*, *rCGH-cytoScan*, or *rCGH-generic*. These classes inherit from the superclass, and allow array-specific pre-parametrizations.

*rCGH-generic* is a particular class, not dedicated to a specific platform. The associated `readGeneric` read function allows the creation of a *rCGH* object from custom arrays, provided the data contains mandatory columns, as described in the next section.

### 4 rCGH functions

---

*rCGH* provides functions for each of the analysis steps, from reading files to visualizing genomic profiles. Several *get* functions allow the user to get access to specific results and workflow parameters, saved and stored at each step.

#### 4.1 Reading files

##### 4.1.1 Commercial arrays

Agilent Feature Extraction files (from 44K to 400K arrays), and Affymetrix SNP6.0 and cytoScanHD data are supported.

To keep more flexibility, Affymetrix CEL files have to be first read using ChAS or Affymetrix Power Tools (APT) [1], and then exported as *cychp.txt* or *cnchp.txt* files. Notice that *cnchp.txt* files contain Allelic differences, that allow the loss of heterozygosity (LOH) to be estimated, while *cychp.txt* files do not.

Due to specific files structures, and since preambles may be missing (depending on ChAS and APT versions), *rCGH* provides specific read/build-object functions:

- `readAgilent()`: 44K to 400K FE (.txt) files.
- `readAffySNP6()`: *cychp*, *cnchp* and *probeset* (.txt) files, exported from SNP6.0 CEL, through ChAS or APT.

- `readAffyCytoScan()`: `cychp`, `cnchp` and `probeset (.txt)` files, exported from CytoScanHD CEL, through ChAS or APT.

Notice that these read functions have a *genome*, which allow the user to specify what genome build to use with the current array. The supported genome builds are hg18, hg19 (default) and hg38. This value is stored, then used in the plot functions.

#### 4.1.2 Custom arrays

Custom arrays can be read using `readGeneric()`, which leads to construct an object of class *rCGH-generic*. Data as to be provided as a text file, with the following mandatory information.

Mandatory columns for custom arrays:

- `ProbeName`: Character strings. Typically the probe ids.
- `ChrNum`: numeric. The chromosome numbers. In case Chr X and Y are used and named as "X" and "Y", these notations will be converted into "23" and "24", respectively.
- `ChrStart`: numeric. The chromosomal probe locations.
- `Log2Ratio`: numeric. The corresponding Log2Ratios.

Each of the read functions take the file's path as the unique mandatory argument. Other optional arguments allow the user to save supplementary information: *sampleName*, *labName*:

```
> library(rCGH)
> filePath <- system.file("extdata", "Affy_cytoScan.cyhd.CN5.CNCHP.txt.bz2",
+   package = "rCGH")
> cgh <- readAffyCytoScan(filePath, sampleName = "CSc-Example",
+   labName = "myLab")
```

```
> cgh

                               info
fileName      Affy_cytoScan.cyhd.CN5.CNCHP.txt.bz2
sampleName    CSc-Example
labName       myLab
usedProbes    snp
genome        hg19
platform      CytoScanHD_Array
barCode       @52082500958167113016424803602715
gridName      CytoScanHD_Array.na33.annot.db
scanDate      2015-01-22
programVersion 5.0.0
gridGenomicBuild hg19/GRCh37
reference      CytoScanHD_Array.na33.r1.REF_MODEL
analyseDate    2016-05-15
```

```
rCGH_version 1.2.2
```

In complement, any kind of useful annotation (logical, string or numeric) can be added, with `setInfo()`:

```
> setInfo(cgh, "item1") <- 35
> setInfo(cgh, "item2") <- TRUE
> setInfo(cgh, "item3") <- "someComment"
```

At any time, the full (or specific) annotations stored can be accessed:

```
> getInfo(cgh)

                               info
fileName      Affy_cytoScan.cyhd.CN5.CNCHP.txt.bz2
sampleName    CSc-Example
labName       myLab
usedProbes    snp
genome        hg19
platform      CytoScanHD_Array
barCode       @52082500958167113016424803602715
gridName      CytoScanHD_Array.na33.annot.db
scanDate      2015-01-22
programVersion 5.0.0
gridGenomicBuild hg19/GRCh37
reference      CytoScanHD_Array.na33.r1.REF_MODEL
analyseDate    2016-05-15
rCGH_version  1.2.2
item1         35
item2         TRUE
item3         someComment

> getInfo(cgh, c("item1", "item3"))

      item1      item3
      "35"  "someComment"
```

## 4.2 Adjusting signals

When Agilent dual-color hybridization are used, GC content and the cy3/cy5 bias are necessary adjustments. `adjustSignal()` handle these steps before computing the  $\log_2(\text{RelativeRatios})$  (LRR). In both cases, a local regression (`loessFit`, R package *limma*) is used [2].

Note that by default, the cyanine3 signal is used as the reference. Use `Ref=cy5` if cyanine5 signal has to be used as the reference.

In case of Affymetrix cychp or cnchp files, these steps have already been processed, and `adjustSignal()`

simply rescale the LRR, when `Scale=TRUE` (default). As for Agilent data, some useful quality scores: the derivative Log Ratio Spread (dLRs) and the LRR Median Absolute Deviation (MAD), are stored in the object.

```
> cgh <- adjustSignal(cgh, nCores=1)
```

*Log2Ratios QCs:*

*dLRs: 0.188*

*MAD: 0.24*

*Scaling...*

*Signal filtering...*

*Modeling allelic Difference...*

### 4.3 Centering LRR

Centering LRR is a key step in the genomic analysis process since it defines the base line (the expected 2-copies level) from where gains and losses are estimated. To do so, LRRs are considered as a mixture of several gaussian populations, and an expectation-maximization (EM) algorithm is used to estimate their parameters.

The centralization value is chosen according to the user specification: the mean of the sub-population with a density peak higher than a given proportion of the highest density peak [3]. The default value is 0.5. Setting `peakThresh = 1` leads to choose the highest density peak.

The `plotDensity()` function gives access to a graphical check on how the centralization step worked, and what LRR population has been chosen for centering the profile:

```
> # Restricted to 3 groups for the purpose of that demo.
```

```
> cgh <- EMnormalize(cgh, G = 3)
```

*Smoothing param: 73*

*Analyzing mixture...*

*Merging peaks closer than 0.1 ...*

*Gaussian mixture estimation:*

*n.peaks = 3*

*Group parameters:*

*Grp 1:*

*prop: 0.382, mean: 0.037, Sd: 0.077, peak height: 1.992*

```
Grp 2:
prop: 0.042, mean: 0.468, Sd: 0.347, peak height: 0.049
Grp 3:
prop: 0.576, mean: 1.343, Sd: 0.086, peak height: 2.66

Correction value: 0.037

Use plotDensity() to visualize the LRR densities.
```

```
> plotDensity(cgh)
```




Figure 1: **plotDensity**. `plotDensity()` shows how *EM* models the *LRR* distribution, and what peak is chosen for centralizing the profile (in bold).

## 4.4 Segmenting

One possible strategy for segmenting the genome profile consists in identifying breakpoints all along the genome, when exist. These breakpoints define the DNA segments start and end positions. To do so, *rCGH* uses the Circular Binary Segmentation algorithm (*CBS*) [4] from the *DNACopy* package [5]. All the steps are wrapped into one unique easy-to-use function, `segmentCGH()`. In order to facilitate its use, all the parameters but one are predefined: `UndoSD` is kept free. When this parameter is set to `NULL` (default), its optimal value is estimated directly from the values. However, the user can specify

its own value, generally from 0.5 to 1.5.

The resulting segmentation table is of the form of a standard *DNAcopy* output, plus additional columns:

- ID : sample Id.
- chrom : chromosome number.
- loc.start : segment start position.
- loc.end : segment end position.
- num.mark : number of markers within each segment.
- seg.mean : the mean LRR along each segment.
- seg.med : the median LRR along each segment.
- probes.Sd : the LRR standard deviation along each segment.

```
> cgh <- segmentCGH(cgh, nCores=1)
```

*Computing LRR segmentation using UnodSD: 0.245*

*Merging segments shorter than 10Kb.*

*Number of segments: 26*

```
> segTable <- getSegTable(cgh)
```

```
> head(segTable)
```

	ID	chrom	loc.start	loc.end	num.mark	seg.mean	seg.med	probes.Sd
1	CSc.Example	1	882803	120345101	617	0.0841	-0.03480	0.6932669
2	CSc.Example	1	121155528	249198692	591	1.1789	1.27150	0.6836284
3	CSc.Example	2	15703	242775910	1316	1.3088	1.32065	0.4807931
4	CSc.Example	3	62614	197851260	1099	-0.0060	-0.03480	0.5034378
5	CSc.Example	4	46691	190921709	1041	1.2993	1.32065	0.4823672
6	CSc.Example	5	113577	180692833	985	1.3239	1.32065	0.5121162

Note that such data format allows GISTIC-compatible inputs to be exported [6].

## 4.5 Parallelization

*rCGH* allows parallelization within `EMnormalise()` and `segmentCGH()`, through `mclapply()` from R package *parallel*.

By default, `nCores` will be set to half of the available cores, but any value, from 1 to `detectCores()`, is allowed. However, this feature is currently only available on Linux and OSX: `nCores` will be automatically set to 1 when a Windows system is detected.

## 4.6 Getting the by-gene table

This step converts a segmentation table into a by-genes table. `byGeneTable()` extracts the list of genes included in each segment, and constructs a dataset, easy to export and to manipulate outside R. The final genes' list reports the corresponding segmentation values (expressed in Log2Ratio), and

the official positions and annotations, with respect to the genome build specified by the user. As for the read functions, the supported genome builds are hg18, hg19 (default) and hg38. For hg19, locations and annotations are exported from [TxDb.Hsapiens.UCSC.hg19.knownGene](#) and [org.Hs.eg.db](#). The corresponding TxDb is used in case another genome build is specified with the *genome* argument.

```
> geneTable <- byGeneTable(segTable)
Creating byGene table...
> head(geneTable, n=3)
```

	entrezid	symbol	fullName	cytoband	chr	chrStart
1	1	A1BG	alpha-1-B glycoprotein	19q13.4	19	58858172
2	503538	A1BG-AS1	A1BG antisense RNA 1	19q13.4	19	58859117
3	29974	A1CF APOBEC1	complementation factor	10q11.23	10	52559169

	chrEnd	width	strand	Log2Ratio	num.mark	segNum	segLength(kb)	relativeLog
1	58874214	16043	-	1.32065	230	22	58836.84	0
2	58866549	7433	+	1.32065	230	22	58836.84	0
3	52645435	86267	-	1.27150	750	11	135330.87	0

	genomeStart
1	2718302494
2	2718303439
3	1732932312

Notice that the `byGeneTable()` function takes a segmentation table as its first argument, and not a rCGH object. This means that this function can be used to extract genes from any other segmentation table, provided this table is of the same format, and the genome build to use is specified (the default setting is "hg19").

```
> byGeneTable(segTable, "erbb2", genome = "hg19")[,1:6]
```

	symbol	entrezid	fullName	cytoband	chr	chrStart
1	ERBB2	2064	erb-b2 receptor tyrosine kinase 2	17q12	17	37844393

```
> byGeneTable(segTable, "erbb2", genome = "hg18")[,1:6]
```

	symbol	entrezid	fullName	cytoband	chr	chrStart
1	ERBB2	2064	erb-b2 receptor tyrosine kinase 2	17q12	17	35097919

## 4.7 Accessing the analysis parameters

For traceability and reproducibility, it may be useful to keep track to a profile analysis parameters. At each step, the workflow parameters, defined by default or specified by the user, are stored in a `params` slot. They are accessible at any time using `getParam()`.



```
> getParam(cgh)[1:3]
$ksmooth
[1] 73

$Kmax
[1] 20

$Nmin
[1] 160
```

## 4.8 Visualizing the genomic profile

In a context of Precision Medicine, visualizing and manipulating a genomic profile is crucial to interpret imbalances, to identify targetable genes, and to make decisions regarding a potential therapeutic orientation. In many situations, considering LOH can also help to better interpret imbalances.

*rCGH* provides 2 ways for visualizing a genomic profile: `plotProfile()`, `plotLOH()` and `multiplot()` are simple static ways to visualize a profile, possibly with some tagged gene, while `view()` is a more sophisticated and interactive visualization method, build on top of shiny. A control panel allows the user to interact with the profile, and to export the results.

Notice that `plotLOH()` and `multiplot()` are relevant only in case the allelic difference is available, namely when Affymetrix `cnchp.txt` files are used.

### 4.8.1 Static profile visualizations

`plotProfile()` allows the genomic profile visualization. Any gene(s) of interest can be added to the plot by passing a valid HUGO symbol. Other arguments can be used to color the segments according to specified gain/loss thresholds, or to change the plot title.

Two other static functions can be useful for reporting alterations: `plotLOH()` to visualize LOH, and `multiplot()` to build a full report, including both the genomic profile and LOH plot.

*comment: Notice that genes will be located with respect to the genome build version stored in the *rCGH* object. See [subsection 4.1](#) for details.*

```
> multiplot(cgh, c("egfr", "erbb2"))
```




Figure 2: **Static views.** `multiplot()` provides static visualisations combining the genomic profile and the LOH.

#### 4.8.2 Recentering

When the profile centering doesn't seem appropriate, `recenter()` allows the user to choose another centralization value. The new choice has to be specified as the peak index to use: peaks are indexed, from 1 to k (from left to right) as they appear on the density plot.

```
> # Recentering on peak #3
> recenter(cgh) <- 3

Profile recentered on: 1.34
```

```
> plotProfile(cgh, "erbb2")
```




Figure 3: **Recentering.** By default, the EM-based normalization choose a possibly optimal peak to center the profile, but any other peak can be chosen, using `recenter()`.

### 4.8.3 Interactive visualization

The `view()` function provides a more flexible way for interpreting genomic profile, individually. This application allows interactive manipulations through a command panel: defining the gain/loss thresholds, displaying a gene, resizing the y-axis, selecting one unique chromosome, and recentering the entire profile. Note that the *Genes table* is updated whenever changes are made through that command panel, e.g. selecting one unique chromosome on the graph filters the *Genes table* on that chromosome, simultaneously.

The Download buttons, *Plot*, *LOH* and *Table*, allow plots and gene table to be exported, as they have been modified.

*comment: Notice that genes will be located according to the genome build value stored in the rCGH object. This value has to be specified when a file is read. See [subsection 4.1](#) for details.*

The `view()` control panel:

- Gene Symbol : display any existing gene, providing its official HUGO symbol.
- Show chromosome : display the entire profile (default is 'All'), or one specific chromosome.
- Gain/Loss colors : choose blue/red or red/blue.
- Recenter profile : recenter the profile on-the-fly. Gene values are updated in the 'Genes table'.
- Merge segments... : merge segments shorter than the specified value, in Kb. Gene values are updated in the 'Genes table'.
- Recenter profile : recenter the profile on-the-fly. Gene values are updated in the 'Genes table'.
- Rescale max(y) : adjust the top y-axis ( $y_1$ ) using a proportion of the maximum value.
- Rescale min(y) : adjust the bottom y-axis ( $y_0$ ) using a proportion of the minimum value.
- Gain threshold (Log2ratio) : define the gain threshold. Segments higher than this value are colored according to the chosen color code, and the 'Genes table' is filtered, consequently.
- Loss threshold (Log2ratio) : same as 'Gain threshold' but for losses.
- Download - Profile : download the profile as it is displayed on the screen, including modifications.
- Download - LOH : download the LOH plot as it is displayed on the screen, including modifications.
- Download - Table : download the 'Genes table', including modifications.

```
> view(cgh)
```




Figure 4: **Interactive profile.** The genomic profile is displayed in the first *CGH profile* tab (left). Several changes can be applied using the control panel (in blue). The list of genes is accessible through the *Genes table* tab (right). Both are updated simultaneously and can be exported, after modifications are applied.

## 5 Notes regarding the example files

In order to reduce the computation time, we provide subsets of real data for the 3 supported platforms:

```
> list.files(system.file("extdata", package = "rCGH"))
[1] "Affy_cytoScan.cyhd.CN5.CNCHP.txt.bz2"
[2] "Affy_snp6_cnchp.txt.bz2"
[3] "Agilent4x180K.txt.bz2"
[4] "Illumina.txt.bz2"
[5] "generic.txt.bz2"
```

*comment:*

*In order to speed up demos, the provided example files contain only a subset of the original probes. Affymetrix example files (cytoScan and SNP6) only contain SNP probes. Setting useProbes = "cn" in readAffy functions should return an error.*

## 6 Server version

A web browser version of the interactive visualization is available at

[https://fredcommo.shinyapps.io/aCGH\\_viewer](https://fredcommo.shinyapps.io/aCGH_viewer)

As inputs, this application support the *rCGH* segmentation tables, or any segmentation table in the same format as the *CBS* outputs.

For more details about this application, or to install it on your own server, please visit

[https://github.com/fredcommo/aCGH\\_viewer](https://github.com/fredcommo/aCGH_viewer).

## 7 Session information

---

```
> toLatex(sessionInfo())
```

```
\begin{itemize}\raggedright
```

```
\item R version 3.3.0 (2016-05-03), \verb|x86_64-w64-mingw32|
```

```
\item Locale: \verb|LC_COLLATE=C|, \verb|LC_CTYPE=English_United States.1252|, \verb|LC_
```

```
\item Base packages: base, datasets, grDevices, graphics, methods,  
stats, utils
```

```
\item Other packages: knitr~1.13, rCGH~1.2.2
```

```
\item Loaded via a namespace (and not attached):
```

```
AnnotationDbi~1.34.2, Biobase~2.32.0, BiocGenerics~0.18.0,
```

```
BiocInstaller~1.22.2, BiocParallel~1.6.2, BiocStyle~2.0.2,
```

```
Biostrings~2.40.0, DBI~0.4-1, DNACopy~1.46.0, GenomeInfoDb~1.8.2,
```

```
GenomicAlignments~1.8.0, GenomicFeatures~1.24.2,
```

```
GenomicRanges~1.24.0, IRanges~2.6.0, MASS~7.3-45, Matrix~1.2-6,
```

```
R6~2.1.2, RCurl~1.95-4.8, RSQLite~1.0.0, Rcpp~0.12.5,
```

```
Rsamtools~1.24.0, S4Vectors~0.10.0, SummarizedExperiment~1.2.2,
```

```
TxDb.Hsapiens.UCSC.hg18.knownGene~3.2.2,
```

```
TxDb.Hsapiens.UCSC.hg19.knownGene~3.2.2,
```

```
TxDb.Hsapiens.UCSC.hg38.knownGene~3.1.3, XML~3.98-1.4,
```

```
XVector~0.12.0, aCGH~1.50.0, affy~1.50.0, affyio~1.42.0,
```

```
biomaRt~2.28.0, bitops~1.0-6, cluster~2.0.4, colorspace~1.2-6,
```

```
digest~0.6.9, evaluate~0.9, formatR~1.4, ggplot2~2.1.0, grid~3.3.0,
```

```
gtable~0.2.0, highr~0.6, htmltools~0.3.5, httpuv~1.3.3,
```

```
labeling~0.3, lattice~0.20-33, limma~3.28.4, magrittr~1.5,
```

```
mclust~5.2, mime~0.4, multtest~2.28.0, munsell~0.4.3,
```

```
org.Hs.eg.db~3.3.0, parallel~3.3.0, plyr~1.8.3,
```

```
preprocessCore~1.34.0, rtracklayer~1.32.0, scales~0.4.0,
```

```
shiny~0.13.2, splines~3.3.0, stats4~3.3.0, stringi~1.0-1,
```

```
stringr~1.0.0, survival~2.39-4, tools~3.3.0, xtable~1.8-2,
```

```
zlibbioc~1.18.0
```

```
\end{itemize}
```

## References

---

- [1] URL: [http://www.affymetrix.com/estore/partners\\_programs/programs/developer/tools/powerertools.affx](http://www.affymetrix.com/estore/partners_programs/programs/developer/tools/powerertools.affx).
- [2] Smyth GK and Speed TP. Normalization of cDNA microarray data. *Methods*, 31:265–273, 2003. URL: <http://www.statsci.org/smyth/pubs/normalize.pdf>.
- [3] Commo F, Ferte C, Soria JC, Friend SH, Andre F, and Guinney J. Impact of centralization on acgh-based genomic profiles for precision medicine in oncology. *Ann Oncol.*, 2014.

- [4] Venkatraman ES and Olshen AB. A faster circular binary segmentation algorithm for the analysis of array cgh data. *Bioinformatics*, 15(23):657–663, 2007.
- [5] Venkatraman E. Seshan and Adam Olshen. *DNACopy: DNA copy number data analysis*. R package version 1.40.0.
- [6] Mermel CH, Schumacher SE, Hill B, Meyerson ML, Beroukheim R, and Getz G. Gistic2.0 facilitates sensitive and confident localization of the targets of focal somatic copy-number alteration in human cancers. *Genome Biology*, 12(4):R41, 2011.