

Package ‘CopyNumberPlots’

October 16, 2019

Type Package

Title Create Copy-Number Plots using karyoploteR functionality

Version 1.0.1

Author Bernat Gel <bgel@igtp.cat> and Miriam Magallon <mmagallon@igtp.cat>

Maintainer Bernat Gel <bgel@igtp.cat>

Description CopyNumberPlots have a set of functions extending karyoploteRs functionality to create beautiful, customizable and flexible plots of copy-number related data.

Depends R (>= 3.6), karyoploteR

Imports regioneR, IRanges, Rsamtools, SummarizedExperiment, VariantAnnotation, methods, stats, GenomeInfoDb, GenomicRanges, cn.mops, utils

Suggests BiocStyle, knitr, panelcn.mops, BSgenome.Hsapiens.UCSC.hg19.masked, DNACopy

License Artistic-2.0

URL <https://github.com/bernatgel/CopyNumberPlots>

BugReports <https://github.com/bernatgel/CopyNumberPlots/issues>

Encoding UTF-8

VignetteBuilder knitr

biocViews Visualization, CopyNumberVariation, Coverage, OneChannel, DataImport, Sequencing, DNASEq

LazyData false

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/CopyNumberPlots>

git_branch RELEASE_3_9

git_last_commit 37bfc71

git_last_commit_date 2019-05-22

Date/Publication 2019-10-15

R topics documented:

colByCopyNumber	2
EnsemblStyle	3
getBAFColumn	4
getChrColumn	5
getColumn	6
getCopyNumberColors	7
getCopyNumberColumn	8
getEndColumn	9
getIDColumn	10
getLOHColumn	11
getLRRColumn	12
getPosColumn	13
getSegmentValueColumn	14
getStartColumn	15
loadCopyNumberCalls	16
loadCopyNumberCallsCnmops	17
loadCopyNumberCallsCNVkit	18
loadCopyNumberCallsDECoN	19
loadCopyNumberCallsDNAcopy	20
loadCopyNumberCallsPanelcnmops	21
loadCopyNumberCallspennCNV	22
loadCopyNumberCallsSeg	23
loadSNPData	24
loadSNPDataDNAcopy	25
loadSNPDataFromVCF	26
plotBAF	27
plotCopyNumberCalls	29
plotCopyNumberCallsAsLines	31
plotCopyNumberSummary	33
plotLRR	35
prepareLabels	37
removeNAs	37
transformChr	38
UCSCStyle	39
Index	41

colByCopyNumber	<i>colByCopyNumber</i>
-----------------	------------------------

Description

Assign a color to each data element according to the copy number status of the its genomic location

Usage

```
colByCopyNumber(data, cn.calls, cn.column="cn", cn.colors=NULL)
```

Arguments

<code>data</code>	The data elements. Can be a GRanges or anything accepted by toGRanges
<code>cn.calls</code>	The CN calls to use to select the color for the data elements
<code>cn.column</code>	The name of the column with the copy number information. (defaults to "cn")
<code>cn.colors</code>	The specification of the colors. Internally, it used to call the function getCopyNumberColors . Detailed documentation on color specification can be found there. (defaults to NULL)

Details

Given a set of data elements positioned on the genome (either a GRanges or any other format accepted by `regioneR`'s [toGRanges](#)) and a set of copy number calls, assign a color to each element depending on the copy number status of the genomic region where it's located. The colors can be customized using the `cn.colors` parameter as documented in [getCopyNumberColors](#).

Value

Return a vector of colors with the same length as the number of elements in data

See Also

[toGRanges](#), [getCopyNumberColors](#), [plotBAF](#)

Examples

```
pos <- sort(floor(runif(1000, 1, 10000)))
baf.data <- toGRanges("chr1", pos, pos)
baf.data$baf <- rnorm(1000, mean = 0.5, sd = 0.05)
baf.data$baf[1:400] <- baf.data$baf[1:400] + c(0.2, -0.2)

breakpoint <- start(baf.data)[400]
cn.calls <- toGRanges(data.frame(chr=c("chr1", "chr1"), start=c(1, breakpoint+1), end=c(breakpoint, 10000)), c

kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotBAF(kp, baf.data, points.col = colByCopyNumber(baf.data, cn.calls))
```

EnsemblStyle

EnsemblStyle

Description

Set the style of the chromosome names to Ensembl ("chr1" instead of "1")

Usage

```
EnsemblStyle(x)
```

Arguments

`x` (GRanges, GRangesList or list of GRanges) The object to transform to Ensembl style

Value

The same `x` object with the styles of the seqlevels set to Ensembl

Examples

```
#GRanges
seg.data <- regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014630,
seg.data <- EnsemblStyle(seg.data)

#List of GRanges
seg.data <- list(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,
                b=regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014
seg.data <- EnsemblStyle(seg.data)

#GRangesList
seg.data <- GRangesList(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(
                b = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,
seg.data <- EnsemblStyle(seg.data)
```

getBAFColumn

getBAFColumn

Description

Identify the column in a data.frame or equivalent with the B-allele frequency information

Usage

```
getBAFColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

`df` (data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where `names(df)` works.

`col` (number or character) The column to identify. If `NULL` an heuristic will be used to automatically identify the column. It can also be a number or a character to define the exact column to return.(defaults to `NULL`)

`avoid.pattern` (character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to `""`)

`needed` (logical) Whether the column is needed or not. If `TRUE`, an error will be raised if the column is not found. (defaults to `TRUE`)

`verbose` Whether to show information messages. (defaults to `TRUE`)

Details

Identify the column of a data.frame or equivalent that contains the bi-allelic frequency information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getBAFColumn(df = df)
col.num <- getBAFColumn(df = df, col = "BAF")
```

getChrColumn

getChrColumn

Description

Identify the column in a data.frame or equivalent with the chromosome information

Usage

```
getChrColumn(df, col=NULL, avoid.pattern = NULL, needed=TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the chromosome information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getChrColumn(df = df)
col.num <- getChrColumn(df = df, col = "chromosome")
```

getColumn

getColumn

Description

Use simple pattern matching to try to identify a column in a data.frame or equivalent by its name

Usage

```
getColumn(df, col=NULL, pattern="", avoid.pattern = NULL, msg.col.name="", needed=TRUE, verbose = T
```

Arguments

df	(data.frame or equivalent) The object were columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
pattern	(character) The pattern to match the column name. If more than one column matches the pattern, the first one (leftmost) will be returned. The pattern may be any valid regular expression. (defaults to "")
avoid.pattern	(character) The pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
msg.col.name	(character) Only used in the error message to make the message clearer. The name of the column we are searching for. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will use pattern matching to try to identify which column of a data.frame contains a certain data. It will return its number. If col is specified it will not use pattern matching but identify if a column with that exact name exists and return its position.

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id" = "rs1234", "endogenous" = FALSE, "chromosome" = "chr1", "Start" = 0, "end.position" = 100,
"copy.number.level" = 3, "LOH" = 0, "median.value.per.segment" = 1.2,
"BAF" = 0.2, "Log Ratio" = 1.5, "strange.name" = "strange.value")
```

```
col.num <- getColumn(df = df, pattern = "Chr|chr", msg.col.name = "Chromosome", needed = TRUE)
col.num <- getColumn(df = df, col = "chromosome", msg.col.name = "Chromosome", needed = TRUE)
col.num <- getColumn(df = df, col = 3, msg.col.name = "Chromosome", needed = TRUE)
```

```
col.num <- getColumn(df = df, pattern = "end", msg.col.name = "End", needed = TRUE)
col.num <- getColumn(df = df, pattern = "end", avoid.pattern = "endogenous", msg.col.name = "End", needed = TRUE)
```

getCopyNumberColors *getCopyNumberColors*

Description

Get the colors representing the copy number levels

Usage

```
getCopyNumberColors(colors=NULL)
```

Arguments

colors (character) Either a palette name (i.e. "green_orange_red") or a vector of colors. If NULL the default palette ("green_orange_red") will be returned. (defaults to NULL)

Details

This function returns a vector of colors with names from 0 to the length of the vector. The colors will be used to represent copy numbers from 0 (homozygous deletion) to the copy number equal to the length of the vector (typically 7 or 8). The function has a single parameter 'colors', which can be either the name of one of the available palettes or the a vector of valid color specifications (i.e. c("red", "#FFAAAA", "gray", "#AAAAFF", "#5555FF", "#0000FF")). If 'colors' is a palette name, the palette will be returned. If color is a color vector, it will be returned with the names set as needed.

Available palettes are: "gree_orange_red" and "red_blue"

Value

A vector of colors with the names set to the positions in the vector.

Examples

```

getCopyNumberColors()

getCopyNumberColors("red_blue")

getCopyNumberColors(c("red", "#FFAAAA", "gray", "#AAAAFF", "#5555FF", "#0000FF"))

```

```

getCopyNumberColumn   getCopyNumberColumn

```

Description

Identify the column in a data.frame or equivalent with the copy number information

Usage

```
getCopyNumberColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object were columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the copy number information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```

df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getCopyNumberColumn(df = df)
col.num <- getCopyNumberColumn(df = df, col = "copy.number.level")

```

getEndColumn	<i>getEndColumn</i>
--------------	---------------------

Description

Identify the column in a data.frame or equivalent with the end position information

Usage

```
getEndColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the position information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234","chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getEndColumn(df = df)
col.num <- getEndColumn(df = df, col = "end.position")
```

getIDColumn	<i>getIDColumn</i>
-------------	--------------------

Description

Identify the column in a data.frame or equivalent with the ID information

Usage

```
getIDColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object were columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains ID information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getIDColumn(df = df)
col.num <- getIDColumn(df = df, col = "id")
```

getLOHColumn	<i>getLOHColumn</i>
--------------	---------------------

Description

Identify the column in a data.frame or equivalent with LOH information

Usage

```
getLOHColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the LOH information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234","chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getLOHColumn(df = df)
col.num <- getLOHColumn(df = df, col = "LOH")
```

getLRRColumn	<i>getLRRColumn</i>
--------------	---------------------

Description

Identify the column in a data.frame or equivalent with the Log Ratio information

Usage

```
getLRRColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object were columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the Log Ratio information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234","chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getLRRColumn(df = df)
col.num <- getLRRColumn(df = df, col = "Log.Ratio")
```

getPosColumn	<i>getPosColumn</i>
--------------	---------------------

Description

Identify the column in a data.frame or equivalent with the position information

Usage

```
getPosColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the position information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234","chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getPosColumn(df = df)
col.num <- getPosColumn(df = df, col = "strange.name")
```

getSegmentValueColumn *getSegmentValueColumn*

Description

Identify the column in a data.frame or equivalent with the position of the segment value information.

Usage

```
getSegmentValueColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame or equivalent that contains the segment information and return its position.

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234","chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getSegmentValueColumn(df = df)
col.num <- getSegmentValueColumn(df = df, col = "median.value.per.segment")
```

getStartColumn	<i>getStartColumn</i>
----------------	-----------------------

Description

Identify the column in a data.frame with the start position information

Usage

```
getStartColumn(df, col = NULL, avoid.pattern = NULL, needed = TRUE, verbose = TRUE)
```

Arguments

df	(data.frame or equivalent) The object where columns are searched. It must be either a data.frame or an object where names(df) works.
col	(number or character) The column to identify. If NULL an heuristic will be used to automatically identify the column. It can also be a number or a character to define the exact column to return.(defaults to NULL)
avoid.pattern	(character) An optional pattern to avoid on the column name. The pattern may be any valid regular expression. (defaults to "")
needed	(logical) Whether the column is needed or not. If TRUE, an error will be raised if the column is not found. (defaults to TRUE)
verbose	Whether to show information messages. (defaults to TRUE)

Details

Identify the column of a data.frame that contains the position information and return its position

Value

The number of the column matching the specification or NULL if no column was found.

Examples

```
df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
col.num <- getStartColumn(df = df )
col.num <- getStartColumn(df = df, col = "Start")
```

loadCopyNumberCalls *loadCopyNumberCalls*

Description

Loads copy number calls from a tabular format

Usage

```
loadCopyNumberCalls(cnv.data, chr.col = NULL, start.col = NULL, end.col = NULL, cn.col = NULL, loh.col = NULL, segment.value.col = NULL, genome = NULL, verbose = TRUE)
```

Arguments

<code>cnv.data</code>	Either the name of the file with the data or a variable containing the data
<code>chr.col</code>	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
<code>start.col</code>	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to NULL)
<code>end.col</code>	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to NULL)
<code>cn.col</code>	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
<code>loh.col</code>	(number or character) The name or number of the column with LOH information. If NULL, it is automatically identified. (defaults to NULL)
<code>segment.value.col</code>	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to NULL)
<code>genome</code>	(character) The name of the genome (defaults to NULL)
<code>verbose</code>	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from any "bed-like" data structure in R or file. Internally it uses the `toGRanges` function from `regioneR` package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A `GRanges` with a range per copy number segment

Examples

```
df <- data.frame("id"= "rs1234", "chromosome"="chr1", "Start"=0, "end.position"=100,
"copy.number.level"=3, "LOH"=0, "median.value.per.segment"=1.2,
"BAF"=0.2, "Log Ratio"=1.5, "strange.name"="strange.value")
```

```
cnv.call <- loadCopyNumberCalls(cnv.data = df)
```

```
loadCopyNumberCallsCnmops
      loadCopyNumberCallsCnmops
```

Description

Loads copy number calls from either cn.mops result class or in a tabular format

Usage

```
loadCopyNumberCallsCnmops(cn.mops.res, chr.col = NULL, start.col = NULL, end.col = NULL, cn.col = "C
```

Arguments

cn.mops.res	The name of the file with the data or the name of the variable with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to NULL)
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to NULL)
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to "CN")
segment.value.col	(number or character) The name or number of the column with segment value. It can be mean or median. If NULL, it is automatically identified. (defaults to "median")
genome	(character) The name of the genome (defaults to NULL)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from either cn.mops result class or in a tabular format from a file. Internally it uses the `toGRanges` function from `regioneR` package and can work with any format accepted by it, including R objects and local or remote files. Column names of the format loaded are specified as default but, if no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment or a list of GRanges with a GRanges per sample.

Examples

```
# loadCopyNumberCallsCnmops from cn.mops result class:
#NOT RUN - Example loading data from a results object created by cn.mops
# require(cn.mops)
# data(cn.mops, package = "cn.mops")

# cn.mops.res <- cn.mops(XRanges)
```

```
# cn.mops.res <- calcIntegerCopyNumbers(cn.mops.res)
# cnv.call <- loadCopyNumberCallsCnmops(cn.mops.res = cn.mops.res)

# loadCopyNumberCallsCnmops from a file where cn.mops result was saved:
cn.mops.res <- system.file("extdata", "cn.mops.segmentation.csv", package = "CopyNumberPlots", mustWork = TRUE)
cnv.call <- loadCopyNumberCallsCnmops(cn.mops.res = cn.mops.res)
```

```
loadCopyNumberCallsCNVkit
      loadCopyNumberCallsCNVkit
```

Description

Loads copy number calls from CNVkit.cns file format

Usage

```
loadCopyNumberCallsCNVkit(cnvkit.file, chr.col = "chromosome", start.col = "start", end.col = "end")
```

Arguments

cnvkit.file	The name of the file with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to "chromosome")
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to "start")
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to "end")
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to "log2")
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
genome	(character) The name of the genome (defaults to NULL)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from CNVkit.cns file format. Internally it uses the toGRanges function from regioneR package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment.

Examples

```
## loadCopyNumberCallsCNVkit from .cns file format:
## An example of .cns file format is found at https://github.com/etal/cnvkit/blob/master/test/formats/cl_seq.cns

cnvkit.file <- system.file("extdata", "CNVkit_output.cns", package = "CopyNumberPlots", mustWork = TRUE)
cnv.call <- loadCopyNumberCallsCNVkit(cnvkit.file)
```

```
loadCopyNumberCallsDECoN
      loadCopyNumberCallsDECoN
```

Description

Loads copy number calls from DECoN output file

Usage

```
loadCopyNumberCallsDECoN(decon.file, chr.col = NULL, start.col = "Start", end.col = "End", cn.col = NA)
```

Arguments

decon.file	The name of the file with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to "Start")
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to "End")
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NA)
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to NULL)
genome	(character) The name of the genome. (defaults to NULL)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from DECoN output file. Internally it uses the `toGRanges` function from `regioneR` package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment or a list of GRanges with a GRanges per sample.

Examples

```
decon.file <- system.file("extdata", "DECoN_output.txt", package = "CopyNumberPlots", mustWork = TRUE)
cn.calls <- loadCopyNumberCallsDECoN(decon.file = decon.file)
```

```
loadCopyNumberCallsDNACopy
      loadCopyNumberCallsDNACopy
```

Description

Loads copy number calls from DNACopy results.

Usage

```
loadCopyNumberCallsDNACopy(DNACopy.data, chr.col = "chrom", start.col = "loc.start", end.col = "loc.end")
```

Arguments

DNACopy.data	The name of the file with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to "chrom")
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to "loc.start")
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to "loc.end")
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to "seg.mean")
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
chr.transformation	(character) The transformation of the chromosome names in a comma separated "key:value" format.(defaults to "23:X,24:Y,25:MT")
genome	(character) The name of the genome (defaults to NULL)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from DNACopy data structure in R. Internally it uses the toGRanges function from regioneR package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment or a list of GRanges with a GRanges per sample.

Examples

```

library(DNAcopy)

data(coriell)
CNA.object <- suppressWarnings(CNA(cbind(coriell$Coriell.05296), coriell$Chromosome, coriell$Position, data.

smoothed.CNA.object <- smooth.CNA(CNA.object)
DNAcopy.data <- segment(smoothed.CNA.object, verbose=1)

cnv.call <- loadCopyNumberCallsDNAcopy(DNAcopy.data = DNAcopy.data)

# more than 1 sample
CNA.object <- CNA(genomdat = cbind(coriell$Coriell.05296, coriell$Coriell.13330), chrom = coriell$Chromosome,
smoothed.CNA.object <- smooth.CNA(CNA.object)
DNAcopy.data <- segment(smoothed.CNA.object, verbose=1)

cnv.call <- loadCopyNumberCallsDNAcopy(DNAcopy.data = DNAcopy.data)

```

```

loadCopyNumberCallsPanelcnmops
      loadCopyNumberCallsPanelcnmops

```

Description

Loads copy number calls from either cn.mops result class or in a tabular format

Usage

```
loadCopyNumberCallsPanelcnmops(panelcn.mops.res, chr.col = NULL, start.col = NULL, end.col = NULL,
```

Arguments

panelcn.mops.res	The name of the file with the data or the name of the variable with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to NULL)
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to NULL)
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to NULL)
genome	(character) The name of the genome (defaults to NULL)
verbose	(character) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from panelcn.mops resulttable or in a tabular format or file. Internally it uses the toGRanges function from regioneR package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment or a list of GRanges with a GRanges per sample.

Examples

```
## loadCopyNumberCallsPanelcnmops from panelcn.mops resulttable:
library(panelcn.mops)
data(panelcn.mops, package = "panelcn.mops")
XandCB <- test
sampleNames <- colnames(elementMetadata(XandCB))
elementMetadata(XandCB) <- cbind(elementMetadata(XandCB), elementMetadata(control))

resulttable <- createResultTable(resultlist = resultlist, XandCB = XandCB, countWindows = countWindows, sampleNames = sampleNames)
panelcn.mops.res <- resulttable[[1]]
cnv.call <- loadCopyNumberCallsPanelcnmops(panelcn.mops.res = panelcn.mops.res)
```

loadCopyNumberCallspennCNV

loadCopyNumberCallspennCNV

Description

Loads copy number calls from pennCNV.rawcnv file format

Usage

```
loadCopyNumberCallspennCNV (pennCNV.file, chr.col = NULL, start.col = NULL, end.col = NULL, cn.col = NULL)
```

Arguments

pennCNV.file	The name of the file with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to NULL)
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to NULL)
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to NULL)
genome	(character) The name of the genome (defaults to NULL)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load copy number calls from pennCNV.rawcnv file format. Internally it uses the toGRanges function from regioneR package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A GRanges with a range per copy number segment or a list of GRanges with a GRanges per sample.

Examples

```
## loadCopyNumberCallspennCNV from .rawcnv file format:
## The file to run the example can be found in: http://penncnv.openbioinformatics.org/en/latest/user-guide/tes

pennCNV.file <- system.file("extdata", "pennCNV.rawcnv", package = "CopyNumberPlots", mustWork = TRUE)
cnv.call <- loadCopyNumberCallspennCNV(pennCNV.file = pennCNV.file)
```

```
loadCopyNumberCallsSeg
      loadCopyNumberCallsSeg
```

Description

Loads copy number calls from .seg file format

Usage

```
loadCopyNumberCallsSeg (seg.file, chr.col = "chrom", start.col = "loc.start", end.col = "loc.end", s
```

Arguments

seg.file	The name of the file with the data
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to "chrom")
start.col	(number or character) The name or number of the column with start position information. If NULL, it is automatically identified. (defaults to "loc.start")
end.col	(number or character) The name or number of the column with end position information. If NULL, it is automatically identified. (defaults to "loc.end")
segment.value.col	(number or character) The name or number of the column with segment value. If NULL, it is automatically identified. (defaults to "seg.mean")
cn.col	(number or character) The name or number of the column with CN information. If NULL, it is automatically identified. (defaults to NULL)
genome	(character) The name of the genome (defaults to NULL)
chr.transformation	(character)(character) The transformation of the chromosome names in a comma separated "key:value" format as detailed at https://cnvkit.readthedocs.io/en/stable/importexport.html#seg . (defaults to "23:X,24:Y,25:MT")
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will load segments data from .seg file format. Internally it uses the `toGRanges` function from `regioner` package and can work with any format accepted by it, including R objects and local or remote files. If no column names are specified, it will use simple heuristics to try to identify the relevant data columns.

Value

A `GRanges` with a range per copy number segment

Examples

```
## loadCopyNumberCallsSeg from .seg file format:
## the file to run in the example can be found in:
## https://software.broadinstitute.org/software/igv/SEG
## under example.seg file name.

seg.file <- system.file("extdata", "DNACopy_output.seg", package = "CopyNumberPlots", mustWork = TRUE)
cnv.call <- loadCopyNumberCallsSeg(seg.file = seg.file)
```

loadSNPData

loadSNPData

Description

Loads SNP array data in a tabular format

Usage

```
loadSNPData(snp.data, chr.col = NULL, start.col = NULL, end.col = NULL, pos.col = NULL, baf.col = NULL)
```

Arguments

<code>snp.data</code>	Either the name of the file with the data or a variable containing the data.
<code>chr.col</code>	(number or character) The name or number of the column with chromosome information. If <code>NULL</code> , it is automatically identified. (defaults to <code>NULL</code>)
<code>start.col</code>	(number or character) the name or number of the column with start position
<code>end.col</code>	(number or character) the name or number of the column with end position
<code>pos.col</code>	(number or character) The name or number of the column with position information. If <code>NULL</code> , it is automatically identified. (defaults to <code>NULL</code>)
<code>baf.col</code>	(number or character) The name or number of the column with BAF information. If <code>NULL</code> , it is automatically identified. (defaults to <code>NULL</code>)
<code>lrr.col</code>	(number or character) The name or number of the column with LRR information. If <code>NULL</code> , it is automatically identified. (defaults to <code>NULL</code>)
<code>id.col</code>	(number or character) The name or number of the column with SNP identifier information. If <code>NULL</code> , it is automatically identified. (defaults to <code>NULL</code>)
<code>genome</code>	(character) The name of the genome (defaults to "hg19")
<code>verbose</code>	Whether information messages should be generated. (defaults to <code>TRUE</code>)

Details

Given a file name or data in a tabular format, the function loads SNP array data in a tabular format. It will try to identify the columns with the relevant information (chr, position, BAF, LRR, etc...) or will use the column number or name supplied by the user, if any. It will convert the tabular data into a GRanges, with one range per SNP in the table.

Value

A GRanges with a range per SNP

Examples

```
# There are two examples of possible files to load.
snp.data1 <- system.file("extdata", "snp.data_test.csv", package = "CopyNumberPlots", mustWork=TRUE)
snps <- loadSNPData(snp.data = snp.data1)

snp.data2 <- system.file("extdata", "snp.data_test2.csv", package = "CopyNumberPlots", mustWork=TRUE)
snps <- loadSNPData(snp.data = snp.data2)
```

loadSNPDataDNAcopy *loadSNPDataDNAcopy*

Description

Loads SNP array data in a tabular format using data from DNAcopy rawdata or DNAcopy results

Usage

```
loadSNPDataDNAcopy (snp.data, chr.col = "chrom", start.col = NULL, end.col = NULL, pos.col = "maploc
```

Arguments

snp.data	Either the name of the file with the data or a variable containing the data.
chr.col	(number or character) The name or number of the column with chromosome information. If NULL, it is automatically identified. (defaults to NULL)
start.col	(number or character) the name or number of the column with start position
end.col	(number or character) the name of number of the column with end position
pos.col	(number or character) The name or number of the column with position information. If NULL, it is automatically identified. (defaults to NULL)
lrr.col	(number or character) The name or number of the column with LRR information. If NULL, it is automatically identified. (defaults to NULL)
chr.transformation	(character) The transformation of the chromosome names in a comma separated "key:value" format.(defaults to "23:X,24:Y,25:MT")
genome	(character) The name of the genome (defaults to "hg19")
na.rm	(logical) Whether to remove NA values. (defaults to FALSE)
verbose	Whether information messages should be generated. (defaults to TRUE)

Details

Given a DNACopy rawdata or DNACopy results object, the function load SNP array data in a tabular format. It will try to identify the columns with the relevant information (chr, position, BAF, LRR, etc...) or will use the column number or name supplied by the user, if any. It will convert the tabular data into a GRanges, with one range per SNP in the table.

Value

A list of GRanges with a range per SNP and one GRanges per sample.

Examples

```
library(DNACopy)
data(coriell)
#one sample
CNA.object <- CNA(cbind(coriell$Coriell.05296), coriell$Chromosome, coriell$Position, data.type="logratio")
CNA.object <- smooth.CNA(CNA.object)
snps <- loadSNPDataDNACopy(snp.data = CNA.object, na.rm = TRUE)

# more than 1 sample
CNA.object <- CNA(genomdat = cbind(coriell$Coriell.05296, coriell$Coriell.13330), chrom = coriell$Chromosome,
CNA.object <- smooth.CNA(CNA.object)
snps <- loadSNPDataDNACopy(snp.data = CNA.object, na.rm = TRUE)

#If the data come from DNACopy results
DNACopy.object <- segment(CNA.object, verbose=1)
snps <- loadSNPDataDNACopy(snp.data = DNACopy.object)
```

loadSNPDataFromVCF *loadSNPDataFromVCF*

Description

Load BAF-like data from a VCF file based on the variant allele frequency

Usage

```
loadSNPDataFromVCF(vcf.file, regions=NULL, genome="hg19", mirror.baf=TRUE, verbose=TRUE)
```

Arguments

vcf.file	The name of the VCF file with the data
regions	The regions to which we will limit the import (defaults to NULL)
genome	(a character)The name of the genome (defaults to "hg19")
mirror.baf	Flip the baf of about half the snps (the ones in odd positions in the genome) to achieve a mirror-like effect as in SNP arrays (defaults to TRUE)
verbose	Wether information messages should be generated. (defaults to TRUE)

Details

Given a VCF file the function will compute BAF-like values based on the variant allele frequency contained in it and return a GRanges object with a column named "baf".

Value

A GRanges object with a range per variant and a column named baf

Examples

```
vcf.file <- system.file("extdata", "example.vcf.gz", package = "CopyNumberPlots", mustWork = TRUE)
# These examples fail in windows. Commenting them out temporarily
# snps <- loadSNPDataFromVCF(vcf.file)

#kp <- plotKaryotype(plot.type = 4)
#plotBAF(kp, snps = snps, labels = names(snps))
```

plotBAF

*plotBAF***Description**

Plot the B-allele frequency (BAF) data

Usage

```
plotBAF(karyoplot, snps, baf.column="baf", labels=NULL, points.cex=0.3, points.col="#333333", poin
```

Arguments

karyoplot	(a KaryoPlot object) The object returned by the plotKaryotype function and representing the current active plot.
snps	(a GRanges, a list of GRanges or a GRangesList) An object with the positions of the SNPs and a column with the BAF values. Other columns are ignored. If it's a list of GRanges with different samples, all samples will be plotted, splitting the total plot space between them.
baf.column	(a character) The name of the column in snps with the BAF values. (defaults to "baf")
labels	(a character) The text of the label to identify the data. If NA, no label will be plotted. If NULL, if snps is a single sample GRanges it will default to "BAF", if it's a list of samples it will default to the names in the list or consecutive numbers if names(snps) is NULL. (defaults to NULL)
points.cex	(numeric) The size of the points. (defaults to 0.3)
points.col	(a color) The color of the points (defaults to "#333333")
points.pch	(numeric) The shape of the points. (defaults to 16, a filled circle)
label.cex	(numeric) The size of the label (defaults to 1.5)
label.srt	(numeric) The rotation of the label (defaults to 90, vertical text)
label.margin	(numeric) The margin between the label and the origin of the plot in plot coordinates (the width of the plot is 1). (defaults to 0.03)
add.axis	(logical) Whether to add an axis (defaults to TRUE)
axis.cex	(numeric) The size of the axis labels. (defaults to 1.2)

<code>r0</code>	(numeric) (karyoploteR parameter) <code>r0</code> and <code>r1</code> define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If <code>NULL</code> , they are set to the min and max of the data panel, it is, to use all the available space. (defaults to <code>NULL</code>)
<code>r1</code>	(numeric) (karyoploteR parameter) <code>r0</code> and <code>r1</code> define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If <code>NULL</code> , they are set to the min and max of the data panel, it is, to use all the available space. (defaults to <code>NULL</code>)
<code>track.margin</code>	(numeric) If <code>snps</code> is a list object, this is the margin between the samples BAF. (defaults to 0.1)
<code>data.panel</code>	(numeric) (karyoploteR parameter) The identifier of the data panel where the data is to be plotted. The available data panels depend on the plot type selected in the call to <code>plotKaryotype</code> . (defaults to 1)
<code>verbose</code>	(logical) Whether messages with information on the processing should be generated (defaults to <code>FALSE</code>)
<code>...</code>	The ellipsis operator can be used to specify any additional graphical parameters. Any additional parameter will be passed to the internal calls to karyoploteR functions.

Details

This function plots the B-allele frequency (BAF) values on the genome. BAF values represent the frequency of one of the alleles (NOT always the minor allele) in the sample and usually come from SNP-array. However, it's possible to get similar values from NGS variant calling data ([loadSNPDataFromVCF](#) for example, will load a standard VCF and generate BAF-like values). The function plots the data points, an optional axis and an optional label identifying the data. The function expects a `GRanges` object with the position of the SNPs with a column (usually named 'baf') with the BAF values or any object valid to [toGRanges](#). This object can be created with [loadSNPData](#).

Value

Invisibly returns the karyoploteR object representing the plot. With it it is possible to add other elements to the plot using standard karyoploteR functions

Examples

```
pos <- sort(floor(runif(1000, 1, 10000)))
baf.data <- toGRanges("chr1", pos, pos)
baf.data$baf <- rnorm(1000, mean = 0.5, sd = 0.05)
baf.data$baf[1:400] <- baf.data$baf[1:400] + c(0.2, -0.2)

kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotBAF(kp, baf.data)

names(mcols(baf.data)) <- "values"
kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotBAF(kp, baf.data, baf.column="values", r0=0, r1=0.5, points.col="red", labels="Values")
plotBAF(kp, baf.data, baf.column=1, r0=0.5, r1=1, points.col="orange", labels="First", label.cex=0.8, points.
```

```

#Plotting a list
baf.data2 <- baf.data
baf.data2$baf <- rnorm(1000, mean = 0.5, sd = 0.05)
baf.data$baf <- rnorm(1000, mean = 0.5, sd = 0.05)
baf.data$baf[1:400] <- baf.data$baf[1:400] + c(0.2, -0.2)

baf.list <- list(Tumor=baf.data, Normal=baf.data2)

kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotBAF(kp, baf.list, labels=NULL)

kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotBAF(kp, baf.list, labels=NULL, r1=0.8, label.cex=0.8, axis.cex=0.4)
kpRect(kp, chr="chr1", x0=0, x1=pos[400], y0=0, y1=0.8, border="red")
kpPlotNames(kp, chr="chr1", x0=0, x1=pos[400], y0=0, y1=0.8, labels = "Alteration", position = "top", col="red")

```

plotCopyNumberCalls *plotCopyNumberCalls*

Description

Plot the segments representing the copy number calls by any algorithm

Usage

```
plotCopyNumberCalls(karyoplot, cn.calls, cn.values=NULL, cn.column="cn", cn.colors=NULL, loh.values=NULL)
```

Arguments

karyoplot	A karyoplot object
cn.calls	(a GRanges, a list of GRanges or a GRangesList) An object with the positions of the CN calls and a column with the CN values. Other columns are ignored. If it's a list of GRanges with different samples, all samples will be plotted, splitting the total plot space between them.
cn.values	(integer vector) The CN values. If NULL, they will be extracted from the cn.calls (defaults to NULL)
cn.column	(integer or character vector) The name or number of the column with CN information.(defaults to "cn")
cn.colors	(colors) The colors assigned to gains and losses (defaults to NULL)
loh.values	(logical vector) A logical vector that indicates whether there is or not LOH. (defaults to NULL)
loh.column	(number or character) The name or number of the column with LRR information. (defaults to "loh")
loh.color	(a color) The color assigned to LOH values. (defaults to "#1E90FF")
loh.height	(numeric) The proportion of r0 and r1 of the vertical space over each chromosome dedicated to loh. It is dedicated the 30% of the vertical space by default.(defaults to 0.3)

labels	(character) The text of the label to identify the data. If NA, no label will be plotted. If NULL, if snps is a single sample GRanges it will default to "CN", if it's a list of samples it will default to the names in the list or consecutive numbers if names(snps) is NULL. (defaults to NULL)
label.cex	(numeric) The size of the label (defaults to 1)
label2.cex	(numeric) The size of the label 2. If NULL label2.cex will be label.cex. (defaults to NULL)
track.margin	(numeric) If cn.calls is a list object, this is the margin between the samples CN. (defaults to 0.01)
r0	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)(defaults to 0)
r1	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)(defaults to 1)
...	The ellipsis operator can be used to specify any additional graphical parameters. Any additional parameter will be passed to the internal calls to karyoploteR functions.

Details

Plots the copy number calls as colored rectangles in the karyoplot. Each copy number status has its own color (including 2n, normal genome) and these colors may be specified by cn.colors. If LOH data is available it will be plotted below the copy number data, with a colored rectangle for every LOH region. The input is simply a GRanges object with an additional column containing the copy number status (as integers) and optionally another column containing the LOH status of each region.

If there's only one label, it will be used to label both Copy Number and LOH. If there are at least two labels, the first one is used to label the Copy Number and the second one to label the LOH.

If the function is called with a list of GRanges it plots every GRanges independently as different tracks one below the other. Track positioning is based on 'autotrack' and the margin between track is controlled by 'track.margin'.

Value

Invisibly returns the karyoplot object representing the plot. With it it is possible to add other elements to the plot using standard karyoploteR functions

Examples

```
s1.calls.file <- system.file("extdata", "S1.segments.txt", package = "CopyNumberPlots", mustWork = TRUE)
s1.calls <- loadCopyNumberCalls(s1.calls.file)
```

```
s2.calls.file <- system.file("extdata", "S2.segments.txt", package = "CopyNumberPlots", mustWork = TRUE)
s2.calls <- loadCopyNumberCalls(s2.calls.file)
```

```

kp <- plotKaryotype(chromosomes="chr1")
plotCopyNumberCalls(kp, s1.calls)

kp <- plotKaryotype(chromosomes="chr1")
plotCopyNumberCalls(kp, s1.calls, cn.colors="red_blue")

#List of GRanges
cn.calls <- list(s1=s1.calls, s2 =s2.calls)

kp <-plotKaryotype(chromosomes="chr1")
plotCopyNumberCalls(kp, cn.calls, cn.colors="red_blue")

```

```

plotCopyNumberCallsAsLines
      plotCopyNumberCallsAsLines

```

Description

Plot the segments representing the copy number calls by any algorithm

Usage

```
plotCopyNumberCallsAsLines(karyoplot, cn.calls, style="line", cn.column="cn", labels=NULL, label.cex=1)
```

Arguments

karyoplot	(a KaryoPlot object) The object returned by the plotKaryotype function and representing the current active plot.
cn.calls	(a GRanges, a list of GRanges or a GRangesList) An object with the positions of the CN calls and a column with the CN values. Other columns are ignored. If it's a list of GRanges with different samples, all samples will be plotted, splitting the total plot space between them.
style	(character) The style in which the lines can be plot. It could be as lines or segments. (defaults to "line")
cn.column	(integer or character vector) The name or number of the column with CN information.(defaults to "cn")
labels	(character) The text of the label to identify the data. If NA, no label will be plotted. If NULL, if snps is a single sample GRanges it will default to "Segments", if it's a list of samples it will default to the names in the list or consecutive numbers if names(snps) is NULL. (defaults to NULL)
label.cex	(numeric) The size of the label (defaults to 1)
add.axis	(logical) Whether to plot an axis (defaults to TRUE)
axis.cex	(numeric) The size of the axis labels.(defaults to 1)
numticks	The number of ticks in the axis (defaults to NULL)
col	(color) The color of the lines (defaults to "black")
ymin	(numeric) (karyoploteR parameter) The minimum value of y to be plotted. If NULL, it is set to the min value of the selected data panel. (defaults to -4)

<code>ymax</code>	(numeric) (karyoploteR parameter) (numeric) The maximum value of y to be plotted. If NULL, it is set to the max value of the selected data panel. (defaults to 2)
<code>r0</code>	(numeric) (karyoploteR parameter) <code>r0</code> and <code>r1</code> define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to 0)
<code>r1</code>	(numeric) (karyoploteR parameter) <code>r0</code> and <code>r1</code> define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to 1)
<code>...</code>	The ellipsis operator can be used to specify any additional graphical parameters. Any additional parameter will be passed to the internal calls to karyoploteR functions.

Details

Plots the segments

Value

Invisibly returns the karyoplot object representing the plot. With it it is possible to add other elements to the plot using standard karyoploteR functions

Examples

```
cncalls.file <- system.file("extdata", "S1.segments.txt", package = "CopyNumberPlots", mustWork = TRUE)
cncalls <- loadCopyNumberCalls(cncalls.file)
```

```
kp <- plotKaryotype("hg19")
plotCopyNumberCallsAsLines(kp, cncalls)
```

```
kp <- plotKaryotype("hg19", chromosomes="chr3")
plotCopyNumberCalls(kp, cncalls, r0=0, r1=0.2)
plotCopyNumberCallsAsLines(kp, cncalls, r0=0.25, r1=0.55)
plotCopyNumberCallsAsLines(kp, cncalls, r0=0.65, r1=0.95, style="segments", col="red", ymin=0, ymax=4, numtic
```

```
kp <- plotKaryotype("hg19")
plotCopyNumberCallsAsLines(kp, cncalls, r0=0.2, r1=0.4, style="segments", add.axis=FALSE, labels="CopyNumber"
```

```
#List of GRanges
cncalls.list <- list(s1=cncalls, s2 =cncalls)
kp <- plotKaryotype("hg19")
plotCopyNumberCallsAsLines(kp, cncalls.list, style="segments", add.axis=FALSE)
```

plotCopyNumberSummary *plotCopyNumberSummary*

Description

Plot a summary of copy number status over a number of samples using a histogram-like representation.

Usage

```
plotCopyNumberSummary(karyoplot, cn.calls, direction="in", gain.color=NULL, normal.color=NULL, loss.color=NULL, add.grid=FALSE, grid.color="white", labels, label.cex, label.srt, pos, r0, r1, ...)
```

Arguments

karyoplot	(a KaryoPlot object) The object returned by the plotKaryotype function and representing the current active plot.
cn.calls	(a list of GRanges or a GRangesList) A list of GRanges or a GRangesList containing the GRanges objects with cn.column value
direction	The direction to which the coverage plot point, either "in" for inward or "out" for outward. (defaults to "in")
gain.color	(color) The color assigned to gains (defaults to NULL)
normal.color	(color) The color assigned to normal ploidy (defaults to NULL)
loss.color	(colors) The color assigned to losses (defaults to NULL)
add.grid	(logical) Whether to add lines as a grid in the plot (defaults to FALSE)
grid.color	(color) The color of the grid (defaults to "white")
labels	(a character) The text of the label to identify the data. If NA, no label will be plotted. If NULL, if snps is a single sample GRanges it will default to "CN", if it's a list of samples it will default to the names in the list or consecutive numbers if names(snps) is NULL. (defaults to NULL)
label.cex	(numeric) The size of the label (defaults to 1.5)
label.srt	(numeric) The rotation of the label (defaults to 90, vertical text)
pos	The position of the label (defaults to 2)
r0	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)
r1	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot different data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)
...	The ellipsis operator can be used to specify any additional graphical parameters. Any additional parameter will be passed to the internal calls to karyoploteR functions.

Details

2 types of plots. Convergent or divergent barplots

Value

Invisibly returns the karyoplot object representing the plot. With it it is possible to add other elements to the plot using standard karyoploteR functions

Examples

```
all.scnas <- list(
  loadCopyNumberCalls(system.file("extdata", "S1.segments.txt", package = "CopyNumberPlots", mustWork = TRUE),
    loadCopyNumberCalls(system.file("extdata", "S2.segments.txt", package = "CopyNumberPlots", mustWork = TRUE),
    loadCopyNumberCalls(system.file("extdata", "S3.segments.txt", package = "CopyNumberPlots", mustWork = TRUE)
)

kp <- plotKaryotype(chromosomes="chr1")
plotCopyNumberCalls(kp, all.scnas, r0=0.4, r1=1)
plotCopyNumberSummary(kp, all.scnas, r0=0, r1=0.35)

kp <- plotKaryotype(chromosomes="chr1")
plotCopyNumberSummary(kp, all.scnas, gain.col="blue", loss.col="red", labels="Copy Number", r0=0, r1=0.3, labels.offset=0.1)
plotCopyNumberSummary(kp, all.scnas, direction="out", add.grid=TRUE, r0=0.35, r1=0.65)
plotCopyNumberSummary(kp, all.scnas, direction="out", r0=0.7, r1=1)
kpAxis(kp, ymin=0, ymax=10, r0=0.85, r1=1, tick.pos = c(0,5,10))
kpAxis(kp, ymin=0, ymax=10, r0=0.85, r1=0.7, tick.pos = c(5,10))

#NOT RUN (time constraints in Bioconductor checks):
# Use a random example with more realistic results
# gg <- filterChromosomes(getGenome("hg19"))

# all.scnas <- list()
# for(i in seq_len(10)) {
#   scnas <- createRandomRegions(40, 10e6, 10e6)
#   scnas$cn <- floor(runif(40, 0, 4))
#   scnas$loh <- ifelse(scnas$cn<2, 1, 0)
#   normal.regs <- subtractRegions(gg, scnas)
#   normal.regs$cn <- 2
#   scnas <- sort(c(scnas, normal.regs))
#   all.scnas[[paste0("samp", i)]] <- scnas
# }

# kp <- plotKaryotype("hg19", plot.type=4)
# plotCopyNumberSummary(kp, all.scnas)

# kp <- plotKaryotype("hg19", plot.type=4)
# plotCopyNumberSummary(kp, all.scnas, gain.col="blue", loss.col="red", labels="Copy Number", r0=0, r1=0.3, labels.offset=0.1)
# plotCopyNumberSummary(kp, all.scnas, direction="out", add.grid=TRUE, r0=0.35, r1=0.65)
# plotCopyNumberSummary(kp, all.scnas, direction="out", r0=0.7, r1=1)
# kpAxis(kp, ymin=0, ymax=10, r0=0.85, r1=1, tick.pos = c(0,5,10))
# kpAxis(kp, ymin=0, ymax=10, r0=0.85, r1=0.7, tick.pos = c(5,10))
```

plotLRR

*plotLRR***Description**

Plots the raw SNP array data using karyoploteR

Usage

```
plotLRR(karyoplot, snps, lrr.column="lrr", labels="LRR", ymin=-4, ymax=2, out.of.range = "points",
```

Arguments

karyoplot	(a KaryoPlot object) The object returned by the plotKaryotype function and representing the current active plot.
snps	(a GRanges, a list of GRanges or a GRangesList) An object with the positions of the SNPs and a column with the LRR values. Other columns are ignored. If it's a list of GRanges with different samples, all samples will be plotted, splitting the total plot space between them.
lrr.column	(number or character) The name or number of the column with LRR information. (defaults to "lrr")
labels	(character) The text of the label to identify the data. If NA, no label will be plotted. If NULL, if snps is a single sample GRanges it will default to "LRR", if it's a list of samples it will default to the names in the list or consecutive numbers if names(snps) is NULL.(defaults to "LRR")
ymin	(numeric) (karyoploteR parameter) The minimum value of y to be plotted. If NULL, it is set to the min value of the selected data panel. (defaults to -4)
ymax	(numeric) (karyoploteR parameter) (numeric) The maximum value of y to be plotted. If NULL, it is set to the max value of the selected data panel. (defaults to 2)
out.of.range	(a character) Either to plot "points" or "density" (defaults to "points")
out.of.range.col	The color the out-of-range points should be plotted (defaults to "red")
density.height	The height of the maximum density peak if out.of.range is "density" (defaults to 0.05)
density.window	The window used to compute the uot-of-range density (defaults to 1e5)
line.at.0	(logical) Whether to plot an horizontal line at 0. (defaults to TRUE)
line.at.0.col	(color) The color of the horizontal line plotted at 0. (defaults to "blue")
r0	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot differents data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)
r1	(numeric) (karyoploteR parameter) r0 and r1 define the vertical range of the data panel to be used to draw this plot. They can be used to split the data panel in different vertical ranges (similar to tracks in a genome browser) to plot differents data. If NULL, they are set to the min and max of the data panel, it is, to use all the available space. (defaults to NULL)

<code>points.cex</code>	(numeric) The size of the points. (defaults to 0.3)
<code>points.col</code>	(a color) The color of the points (defaults to "#333333")
<code>points.pch</code>	(numeric) The shape of the points. (defaults to 16, a filled circle)
<code>label.cex</code>	(numeric) The size of the label (defaults to 1.5)
<code>label.srt</code>	(numeric) The rotation of the label (defaults to 90, vertical text)
<code>label.margin</code>	(numeric) The margin between the label and the origin of the plot in plot coordinates (the width of the plot is 1). (defaults to 0.03)
<code>add.axis</code>	(logical) Whether to add an axis (defaults to TRUE)
<code>axis.cex</code>	(numeric) The size of the axis labels. (defaults to 1.2)
<code>track.margin</code>	(numeric) If <code>snp</code> s is a list object, this is the margin between the samples BAF. (defaults to 0.1)
<code>data.panel</code>	(numeric) (karyoploteR parameter) The identifier of the data panel where the data is to be plotted. The available data panels depend on the plot type selected in the call to <code>plotKaryotype</code> . (defaults to 1)
<code>verbose</code>	(logical) Whether messages with information on the processing should be generated (defaults to FALSE)
<code>...</code>	The ellipsis operator can be used to specify any additional graphical parameters. Any additional parameter will be passed to the internal calls to karyoploteR functions.

Details

Creates a plot with the LRR values along the genome

Value

Invisibly returns the karyoplot object representing the plot. With it it is possible to add other elements to the plot using standard karyoploteR functions

Examples

```
pos <- floor(runif(1000, 1, 10000))
lrr.data <- toGRanges("chr1", pos, pos)
lrr.data$lrr <- rnorm(1000, mean = 0, sd = 0.3)
```

```
kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotLRR(kp, lrr.data)
```

```
kp <- plotKaryotype(zoom=toGRanges("chr1", 1, 10000))
plotLRR(kp, lrr.data, lrr.column=1, points.col="orange", labels="First", label.cex=0.8, points.cex=1.4)
```

```
prepareLabels      prepareLabels
```

Description

Prepare the Labels to plot.

Usage

```
prepareLabels(labels, x)
```

Arguments

`labels` (character) labels to plot. (defaults to NULL)
`x` (list or GRangesList) The list or GRangesList where extracting the labels

Value

prepareLabels return a vector with the same length as the length of `x`. If `labels` is NULL and `x` have names, it will return the names of `x`. If there are not names it will return numbers as labels. If `labels` is not NULL, prepareLabels will cut or recycle the names as needed.

Examples

```
#List of GRanges
seg.data <- list(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014,8014,8014,8014), end = c(50000,8014,8014,8014,8014,8014))),
                b = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014,8014,8014,8014), end = c(50000,8014,8014,8014,8014,8014))))
prepareLabels(x = seg.data)

#GRangesList
seg.data <- GRangesList(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014,8014,8014,8014), end = c(50000,8014,8014,8014,8014,8014))),
                       b = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014,8014,8014,8014), end = c(50000,8014,8014,8014,8014,8014))))
prepareLabels(x = seg.data)
```

```
removeNAs          removeNAs
```

Description

Removing NA from snp data.

Usage

```
removeNAs(snp.data, lrr.na = TRUE, baf.na = TRUE, id.na = TRUE, verbose = TRUE)
```

Arguments

snp.data	(GRanges, GRangesList or list) A GRanges, GRangesList or a list of GRanges.
lrr.na	(logical) Whether to remove the rows that have NAs in the lrr column. (defaults to TRUE)
baf.na	(logical) Whether to remove the rows that have NAs in the baf column. (defaults to TRUE)
id.na	(logical) Whether to remove the rows that have NAs in the id column. (defaults to TRUE)
verbose	(logical) Whether to show information messages. (defaults to TRUE)

Details

This function will remove rows with NA values in snp data. We can decide which columns we take into account to detect NAs, using the lrr.na, baf.na and id.na parameters.

Value

A GRanges or a list of GRanges where the NA values have been removed.

Examples

```
#GRanges
seg.data <- regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014630,
seg.data <- removeNAs(snp.data = seg.data)

#List of GRanges
seg.data <- list(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,
b=regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(0,50000,8014
seg.data <- removeNAs(snp.data = seg.data)

#GRangesList
seg.data <- GRangesList(a = regioneR::toGRanges(data.frame(chr = c("chr1", "chr1", "chr2", "chr5"), start = c(
seg.data <- removeNAs(snp.data = seg.data)
```

transformChr

transformChr

Description

Transformation of the chromosomes

Usage

```
transformChr(chr, chr.transformation = "23:X,24:Y,25:MT")
```

Arguments

chr	(character) The chromosome names to transform
chr.transformation	(character) The transformation of the chromosomes names in a comma separated "key:value" format.(defaults to "23:X,24:Y,25:MT")

Details

This function will transform the name of the chromosomes, according to the parameter `chr.transformation`. This is useful in situations where files, such as `.seg` files as the ones generated by CNVkit, have the chromosome names as numbers. In order to transform the sexual and mitochondrial chromosomes from numbers back to characters, we can use this function. The exact transformation might be provided as described at <https://cnvkit.readthedocs.io/en/stable/importexport.html#import-seg>, (e.g. "key:value")

Value

A character vector where the name of the chromosomes have been changed according to `chr.transformation` parameter.

Examples

```
seg.file <- system.file("extdata", "DNACopy_output.seg", package = "CopyNumberPlots", mustWork = TRUE)
seg.data <- read.table(file = seg.file, sep = "\t", skip = 1, stringsAsFactors = FALSE)
colnames(seg.data) <- c("ID", "chrom", "loc.start", "loc.end", "num.mark", "seg.mean")

# here we have the name of the chromosomes in a number format and how many segments are in each one.
table(seg.data$chrom)

# by this way we have the name 23 and 24 respectively transformed to X and Y.
seg.data$chrom <- transformChr(chr = seg.data$chrom, chr.transformation = "23:X,24:Y,25:MT")
table(seg.data$chrom)
```

UCSCStyle

UCSCStyle

Description

Set the style of the chromosome names to UCSC ("chr1" instead of "1")

Usage

```
UCSCStyle(x)
```

Arguments

`x` (GRanges, GRangesList or list of GRanges) The object to transform to UCSC style

Value

The same `x` object with the styles of the seqlevels set to UCSC

Examples

```
#GRanges
seg.data <- regioneR::toGRanges(data.frame(chr = c("1", "1", "2", "5"), start = c(0,50000,8014630,14523572), e
seg.data <- UCSCStyle(seg.data)

#List of GRanges
seg.data <- list(a = regioneR::toGRanges(data.frame(chr = c("1", "1", "2", "5"), start = c(0,50000,8014630,1452
                b=regioneR::toGRanges(data.frame(chr = c("1", "1", "2", "5"), start = c(0,50000,8014630,14523572)
seg.data <- UCSCStyle(seg.data)

#GRangesList
seg.data <- GRangesList(a = regioneR::toGRanges(data.frame(chr = c("1", "1", "2", "5"), start = c(0,50000,8014630,14523572)
                b = regioneR::toGRanges(data.frame(chr = c("1", "1", "2", "5"), start = c(0,50000,8014630,14523572)
seg.data <- UCSCStyle(seg.data)
```


Index

colByCopyNumber, 2

EnsemblStyle, 3

getBAFColumn, 4
getChrColumn, 5
getColumn, 6
getCopyNumberColors, 3, 7
getCopyNumberColumn, 8
getEndColumn, 9
getIDColumn, 10
getLOHColumn, 11
getLRRColumn, 12
getPosColumn, 13
getSegmentValueColumn, 14
getStartColumn, 15

loadCopyNumberCalls, 16
loadCopyNumberCallsCnmops, 17
loadCopyNumberCallsCNVkit, 18
loadCopyNumberCallsDECoN, 19
loadCopyNumberCallsDNAcopy, 20
loadCopyNumberCallsPanelcnmops, 21
loadCopyNumberCallspennCNV, 22
loadCopyNumberCallsSeg, 23
loadSNPData, 24, 28
loadSNPDataDNAcopy, 25
loadSNPDataFromVCF, 26, 28

plotBAF, 3, 27
plotCopyNumberCalls, 29
plotCopyNumberCallsAsLines, 31
plotCopyNumberSummary, 33
plotKaryotype, 27, 28, 31, 33, 35, 36
plotLRR, 35
prepareLabels, 37

removeNAs, 37

toGRanges, 3, 28
transformChr, 38

UCSCStyle, 39