

iCARE(Individualized Coherent Absolute Risk Estimators) Package

November 25, 2024

```
> library(iCARE)
```

Example 1.A

Load the breast cancer data.

```
> data("bc_data", package="iCARE")
```

In this example, we will estimate the risk of breast cancer in ages 50-80. A SNP-only model is fit, with no specific genotypes supplied for estimation. The population disease rates are from SEER.

```
> res_snps_miss = computeAbsoluteRisk(model.snp.info = bc_72_snps,
+                                     model.disease.incidence.rates = bc_inc,
+                                     model.competing.incidence.rates = mort_inc,
+                                     apply.age.start = 50,
+                                     apply.age.interval.length = 30,
+                                     return.refs.risk=TRUE)
```

Note: You did not provide apply.snp.profile. Will impute SNPs for 10000 people.

If require more, please provide apply.snp.profile input.

```
[1] "Note: As specified, the model does not adjust SNP imputations for family history."
      user system elapsed
6.418   0.158   6.575
```

Compute a summary of the risks and visualize the results


```
> summary(res_snps_miss$risk)
```

```
Risk_Estimate
Min.      :0.09601
1st Qu.  :0.09601
Median   :0.09601
Mean     :0.09601
3rd Qu.  :0.09601
Max.     :0.09601
```

```
> summary(res_snps_miss$refs.risk)
```

	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
	0.05826	0.08638	0.09517	0.09601	0.10453	0.16032

```
> plot(density(res_snps_miss$risk), lwd=2,
+      main="SNP-only Risk Stratification: Ages 50-80",
+      xlab="Absolute Risk of Breast Cancer")
```



Example 1.B

In this example, we will again estimate the risk of breast cancer in ages 50-80. This time however, three specific genotypes are supplied for estimation (with some missing data). The argument `return.refs.risk = TRUE`, includes the referent dataset risks be included in results.

```
> res_snps_dat = computeAbsoluteRisk(model.snp.info = bc_72_snps,
+                                   model.disease.incidence.rates = bc_inc,
+                                   model.competing.incidence.rates = mort_inc,
+                                   apply.age.start = 50,
+                                   apply.age.interval.length = 30,
+                                   apply.snp.profile = new_snp_prof,
+                                   return.refs.risk = TRUE)
```


```
[1] "Note: As specified, the model does not adjust SNP imputations for family history."
      user system elapsed
0.147   0.044   0.191
```

```
> names(res_snps_dat)
```

```
[1] "risk"      "details"   "beta.used" "refs.risk"
```

Visualize the Results

```
> plot(density(res_snps_dat$refs.risk), lwd=2,
+      main="Referent SNP-only Risk Distribution: Ages 50-80",
+      xlab="Absolute Risk of Breast Cancer")
> abline(v=res_snps_dat$risk, col="red")
> legend("topright", legend="New Profiles", col="red", lwd=1)
```



Example 2

In this example, we will estimate the risk of breast cancer in ages 50-80 by fitting a model with 13 risk factors and 72 SNPs.

```
> res_covs_snps = computeAbsoluteRisk(model.formula=bc_model_formula,
+                                     model.cov.info=bc_model_cov_info,
+                                     model.snp.info=bc_72_snps,
+                                     model.log.RR=bc_model_log_or,
+                                     model.ref.dataset=ref_cov_dat,
+                                     model.disease.incidence.rates=bc_inc,
+                                     model.competing.incidence.rates=mort_inc,
+                                     model.bin.fh.name="famhist",
+                                     apply.age.start=50,
+                                     apply.age.interval.length=30,
+                                     apply.cov.profile=new_cov_prof,
```


1	1	1	0	0	0	0	8	0
2	1	0	0	0	0	0	10	0
3	0	0	0	0	0	0	1	0
	birth_dec	agemeno_dec	height_dec	bmi_dec	rd_menohrt	rd2_everhrt_e		
1	2	2	6	10	1	0		
2	2	1	6	4	1	0		
3	1	7	1	10	1	0		
	rd2_everhrt_c	rd2_currhrt	alcoholweek_dec	ever_smoke				
1	0	0		1	1			
2	0	0		6	0			
3	0	0		1	1			

Session Information

```
> sessionInfo()
```

R Under development (unstable) (2024-11-20 r87352)

Platform: aarch64-apple-darwin20

Running under: macOS Ventura 13.7.1

Matrix products: default

BLAS: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRblas.0.dylib

LAPACK: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRlapack.dylib;

locale:

[1] C/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8

time zone: America/New_York

tzcode source: internal

attached base packages:

[1] stats graphics grDevices utils datasets methods base

other attached packages:

[1] iCARE_1.35.0 Hmisc_5.2-0 gtools_3.9.5 plotrix_3.8-4

loaded via a namespace (and not attached):

[1] gtable_0.3.6	dplyr_1.1.4	compiler_4.5.0	rpart_4.1.23
[5] tidyselect_1.2.1	htmlTable_2.4.3	stringr_1.5.1	gridExtra_2.3
[9] cluster_2.1.6	scales_1.3.0	fastmap_1.2.0	ggplot2_3.5.1
[13] R6_2.5.1	generics_0.1.3	Formula_1.2-5	knitr_1.49
[17] htmlwidgets_1.6.4	backports_1.5.0	checkmate_2.3.2	tibble_3.2.1
[21] munsell_0.5.1	nnet_7.3-19	pillar_1.9.0	rlang_1.1.4
[25] utf8_1.2.4	stringi_1.8.4	xfun_0.49	cli_3.6.3
[29] magrittr_2.0.3	digest_0.6.37	grid_4.5.0	rstudioapi_0.17.1
[33] base64enc_0.1-3	lifecycle_1.0.4	vctrs_0.6.5	data.table_1.16.2
[37] evaluate_1.0.1	glue_1.8.0	fansi_1.0.6	colorspace_2.1-1
[41] rmarkdown_2.29	foreign_0.8-87	tools_4.5.0	pkgconfig_2.0.3
[45] htmltools_0.5.8.1			